3200263 https://www.phoenixcontact.com/us/products/3200263



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Ferrule, color: silver

Your advantages

· The insulation reliability of close connections is increased and the splicing of wires is prevented

Commercial data

Item number	3200263
Packing unit	1,000 pc
Minimum order quantity	1,000 pc
Sales key	BH34
Product key	BH3412
Catalog page	Page 480 (C-3-2019)
GTIN	4017918093914
Weight per piece (including packing)	0.058 g
Weight per piece (excluding packing)	0.058 g
Customs tariff number	85369010
Country of origin	DE

3200263

https://www.phoenixcontact.com/us/products/3200263



Technical data

Product properties

Product type	Cable end sleeve
Conductor category	stranded conductors, class 2, 5, 6 / B, C, K, M

Connection data

Conductor connection	
Conductor cross section flexible max.	1.5 mm ²
Conductor cross section AWG max.	16
Stripping length	7 mm

Dimensions

Dimensional drawing	
Maximum stripping length	7 mm
Ferrule diameter	1.7 mm
Sleeve wall thickness	0.15 mm
Inner dimensions of the insulating collar	2.8 mm

Material specifications

Color	silver
Material	CU-DHP
Flammability rating according to UL 94	HB
Coating	tin-plated (galvanic)
Components	free from silicone and halogen

Environmental and real-life conditions

Ambient conditions	
Permanent temperature	105 °C
Short-term temperature	120 °C

Standards and regulations

Design according to standard	
Design according to standard	DIN 46228-1, UL 486F-A

3200263 https://www.phoenixcontact.com/us/products/3200263



Classifications

ECLASS

ECLASS-11.0	27400201
ECLASS-13.0	27400201
ECLASS-12.0	27400201

ETIM

	ETIM 9.0	EC000005
UNSPSC		
	UNSPSC 21.0	27121700

3200263 https://www.phoenixcontact.com/us/products/3200263



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com