3200357

https://www.phoenixcontact.com/us/products/3200357



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Ferrule, color: silver

### Commercial data

Item number	3200357
Packing unit	100 pc
Minimum order quantity	100 pc
Sales key	BH34
Product key	BH3412
Catalog page	Page 480 (C-3-2019)
GTIN	4017918094003
Weight per piece (including packing)	0.544 g
Weight per piece (excluding packing)	0.525 g
Customs tariff number	85369010
Country of origin	DE

3200357

https://www.phoenixcontact.com/us/products/3200357



### Technical data

General	These ferrules are not included in DIN 46228-1: 1992-08
oduct properties	
Product type	Cable end sleeve
Conductor category	stranded conductors, class 2, 5, 6 / B, C, K, M
onnection data	
Conductor connection	
Conductor cross section flexible max.	25 mm <sup>2</sup>
Conductor cross section AWG max.	4
Stripping length	12 mm
imensions	
Dimensional drawing	
Maximum stripping length	12 mm
Ferrule diameter	7.3 mm
Sleeve wall thickness	0.2 mm
Inner dimensions of the insulating collar	9.5 mm
aterial specifications	
Color	silver
Material	CU-DHP
Coating	tin-plated (galvanic)

Ambient conditions		
Permanent temperature	105 °C	
Short-term temperature	120 °C	

3200357

https://www.phoenixcontact.com/us/products/3200357



### Classifications

#### ECLASS

ECLASS-11.0	27400201
ECLASS-13.0	27400201
ECLASS-12.0	27400201

#### ETIM

	ETIM 9.0	EC000005		
UNSPSC				
	UNSPSC 21.0	27121700		

3200357 https://www.phoenixcontact.com/us/products/3200357



### Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com