


https://www.phoenixcontact.com/us/products/3200386



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.





Commercial data

Item number	3200386
Packing unit	100 pc
Minimum order quantity	100 pc
Sales key	BH34
Product key	BH3412
Catalog page	Page 480 (C-3-2019)
GTIN	4017918094034
Weight per piece (including packing)	0.902 g
Weight per piece (excluding packing)	0.87 g
Customs tariff number	85369010
Country of origin	DE



https://www.phoenixcontact.com/us/products/3200386



Technical data

Notes

	General	These ferrules are not included in DIN 46228-1: 1992-08
Pr	roduct properties	
	Product type	Cable end sleeve

Connection data

Conductor connection

Conductor cross section flexible max.	25 mm²
Conductor cross section AWG max.	4
Stripping length	20 mm

Dimensions

Dimensional drawing	
Maximum stripping length	20 mm
Ferrule diameter	7.3 mm
Sleeve wall thickness	0.2 mm
Inner dimensions of the insulating collar	9.5 mm

Material specifications

Color	silver
Material	CU-DHP
Coating	tin-plated (galvanic)

Environmental and real-life conditions

Ambient conditions

Permanent temperature	105 °C
Short-term temperature	120 °C



https://www.phoenixcontact.com/us/products/3200386



Classifications

ECLASS

	ECLASS-11.0	27400201
	ECLASS-12.0	27400201
	ECLASS-13.0	27400201
ETIM		
	ETIM 9.0	EC000005

UNSPSC

UNSPSC 21.0 27121700	
----------------------	--

3200386

https://www.phoenixcontact.com/us/products/3200386



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com