

# P-FIX-3,5 - Spare knife

3210361

<https://www.phoenixcontact.com/us/products/3210361>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Spare knife, depth: 8.6 mm, width: 2.6 mm, height: 10.6 mm, color: gray



## Your advantages

- Can be used in all ...-TG disconnect terminals with 3.5mm spacing from the CLIPLINE complete system
- The P-FIX contact metal seals the disconnect point with the same shape and cannot be removed again once fitted

## Commercial data

|                                      |               |
|--------------------------------------|---------------|
| Item number                          | 3210361       |
| Packing unit                         | 50 pc         |
| Minimum order quantity               | 50 pc         |
| Sales key                            | BE29          |
| Product key                          | BE2ZWX        |
| GTIN                                 | 4046356944977 |
| Weight per piece (including packing) | 0.3 g         |
| Weight per piece (excluding packing) | 0.3 g         |
| Customs tariff number                | 85389099      |
| Country of origin                    | DE            |

# P-FIX-3,5 - Spare knife



3210361

<https://www.phoenixcontact.com/us/products/3210361>

## Technical data

### Product properties

|              |       |
|--------------|-------|
| Product type | Knife |
|--------------|-------|

### Dimensions

|        |         |
|--------|---------|
| Width  | 2.6 mm  |
| Height | 10.6 mm |
| Depth  | 8.6 mm  |

### Material specifications

|   |        |
|---|--------|
| Color   | gray   |
| Flammability rating according to UL 94                                  | V0     |
| Insulating material   | PA     |
| Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21)) | 125 °C |
| Relative insulation material temperature index (Elec., UL 746 B)        | 125 °C |

### Environmental and real-life conditions

#### Ambient conditions

|  |   |
|--|---|
| Ambient temperature (operation)          | -60 °C ... 105 °C (max. short-term operating temperature RTI Elec.)       |
| Ambient temperature (storage/transport)  | -25 °C ... 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly)           | -5 °C ... 70 °C   |
| Ambient temperature (actuation)          | -5 °C ... 70 °C   |
| Permissible humidity (storage/transport) | 30 % ... 70 %   |

# P-FIX-3,5 - Spare knife



3210361

<https://www.phoenixcontact.com/us/products/3210361>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27141190 |
| ECLASS-12.0 | 27141190 |
| ECLASS-13.0 | 27141190 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC002848 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 39121400 |
|-------------|----------|

# P-FIX-3,5 - Spare knife



3210361

<https://www.phoenixcontact.com/us/products/3210361>

## Environmental product compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|            | No hazardous substances above threshold values          |

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)