

https://www.phoenixcontact.com/us/products/3212824



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable housing, pitch: 35 mm, depth: 36.8 mm, width: 35 mm, height: 19.9 mm, number of positions: 10, color: gray

### Your advantages

- · Robust cable housing for strain relief on connecting cables
- · Can be aligned without any loss of pitch
- · Additional scope for marking plugs

#### Commercial data

Item number	3212824
Packing unit	25 pc
Minimum order quantity	25 pc
Sales key	BE22
Product key	BE224Z
Catalog page	Page 366 (C-1-2019)
GTIN	4046356573597
Weight per piece (including packing)	10.436 g
Weight per piece (excluding packing)	10.29 g
Customs tariff number	39269097
Country of origin	PL



https://www.phoenixcontact.com/us/products/3212824



### Technical data

#### Product properties

Product type	Cable housing
Number of positions	10
Pitch	35 mm

#### Material specifications

Color	gray
Material	PA
Flammability rating according to UL 94	V0
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	130 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

#### Dimensions

Width	35 mm
Height	19.9 mm
Depth	36.8 mm
Pitch	35 mm



https://www.phoenixcontact.com/us/products/3212824



## Classifications

UNSPSC 21.0

#### **ECLASS**

ECL	_ASS-11.0	27440202
ECL	LASS-12.0	27440202
ECL	LASS-13.0	27440202
ETIM		
ETIM	M 9.0	EC000437
UNSPSC		

31261500

3212824

https://www.phoenixcontact.com/us/products/3212824



## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com