PH 1,5/S/14 - Cable housing

3212866

https://www.phoenixcontact.com/us/products/3212866

PHŒNIX CONTACT

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable housing, pitch: 49 mm, depth: 36.8 mm, width: 49 mm, height: 19.9 mm, number of positions: 14, color: gray

Your advantages

- · Robust cable housing for strain relief on connecting cables
- · Can be aligned without any loss of pitch
- Additional scope for marking plugs

Commercial data

Item number	3212866
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BE22
Product key	BE224Z
Catalog page	Page 366 (C-1-2019)
GTIN	4046356573634
Weight per piece (including packing)	16.95 g
Weight per piece (excluding packing)	16.3 g
Customs tariff number	39269097
Country of origin	PL

PH 1,5/S/14 - Cable housing

3212866

https://www.phoenixcontact.com/us/products/3212866



Technical data

Product properties

Product type	Cable housing
Number of positions	14
Pitch	49 mm

Material specifications

Color	gray
Material	PA
Flammability rating according to UL 94	V0
Static insulating material application in cold	-60 °C
Temperature index of insulation material (DIN EN 60216-1 (VDE 0304-21))	130 °C
Relative insulation material temperature index (Elec., UL 746 B)	130 °C
Fire protection for rail vehicles (DIN EN 45545-2) R22	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R23	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R24	HL 1 - HL 3
Fire protection for rail vehicles (DIN EN 45545-2) R26	HL 1 - HL 3
Calorimetric heat release NFPA 130 (ASTM E 1354)	28 MJ/kg
Surface flammability NFPA 130 (ASTM E 162)	passed
Specific optical density of smoke NFPA 130 (ASTM E 662)	passed
Smoke gas toxicity NFPA 130 (SMP 800C)	passed

Dimensions

Width	49 mm
Height	19.9 mm
Depth	36.8 mm
Pitch	49 mm

PH 1,5/S/14 - Cable housing

3212866

https://www.phoenixcontact.com/us/products/3212866




Classifications

ECLASS

ECLASS-12.0 27440202 ECLASS-13.0 27440202	ECLASS-11.0	27440202
ECLASS-13.0 27440202	ECLASS-12.0	27440202
	ECLASS-13.0	27440202

ETIM

	ETIM 9.0	EC000437
UNSPSC		
	UNSPSC 21.0	31261500



3212866 https://www.phoenixcontact.com/us/products/3212866



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com