

https://www.phoenixcontact.com/us/products/3216263



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Vertical potential bridge, to connect the upper and lower level

Commercial data

| Item number | 3216263 |
|--------------------------------------|---------------------|
| Packing unit | 10 pc |
| Minimum order quantity | 10 pc |
| Sales key | BE29 |
| Product key | BE2Z2X |
| Catalog page | Page 404 (C-1-2019) |
| GTIN | 4046356572064 |
| Weight per piece (including packing) | 0.64 g |
| Weight per piece (excluding packing) | 0.614 g |
| Customs tariff number | 85366990 |
| Country of origin | PL |



https://www.phoenixcontact.com/us/products/3216263



Technical data

Product properties

| Product type | Vertical bridge |
|---------------------|-----------------|
| Number of positions | 1 |

Electrical properties

| Maximum load current | 16 A (The current values for the jumpers can deviate when used |
|----------------------|---|
| | in different modular terminal blocks. The precise values can be |
| | found in the accessories data for the respective modular terminal |
| | blocks.) |

Connection data

| Maximum load current | 16 A (The current values for the jumpers can deviate when used in different modular terminal blocks. The precise values can be found in the accessories data for the respective modular terminal blocks.) |
|----------------------|---|
|----------------------|---|

Dimensions

| Width | 3.5 mm |
|--------|---------|
| Height | 3 mm |
| Depth | 33.7 mm |
| Length | 3 mm |

Material specifications

| Color | black |
|---------------------|--------|
| Material | Copper |
| Insulating material | PA |

Environmental and real-life conditions

Ambient conditions

| Ambient temperature (operation) | -60 °C 105 °C |
|--|---|
| Ambient temperature (storage/transport) | -25 °C 60 °C (for a short time, not exceeding 24 h, -60 °C to +70 °C) |
| Ambient temperature (assembly) | -5 °C 70 °C |
| Ambient temperature (actuation) | -5 °C 70 °C |
| Permissible humidity (storage/transport) | 30 % 70 % |

Mounting

| Mounting type | Plug-in mounting |
|---------------|------------------|



https://www.phoenixcontact.com/us/products/3216263



Classifications

UNSPSC 21.0

ECLASS

| ECLASS-11.0 | 27141140 |
|-------------|----------|
| ECLASS-12.0 | 27141140 |
| ECLASS-13.0 | 27250303 |
| ETIM | |
| ETIM 9.0 | EC000489 |
| UNSPSC | |

39121400



https://www.phoenixcontact.com/us/products/3216263



Environmental product compliance

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|
| | No hazardous substances above threshold values |

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com