

https://www.phoenixcontact.com/us/products/3240066



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Pin cable lug, blue, 1.5 - 2.5 mm², L1=12 mm

Your advantages

- "Easy Entry" for easy and reliable conductor entry
- · Halogen-free
- · Hard-soldered crimping zone for maximum pull-out forces
- Electrogalvanized

Commercial data

Item number	3240066
Packing unit	100 pc
Minimum order quantity	100 pc
Sales key	BH34
Product key	BH3461
Catalog page	Page 496 (C-3-2019)
GTIN	4046356452847
Weight per piece (including packing)	0.936 g
Weight per piece (excluding packing)	0.936 g
Customs tariff number	85366990
Country of origin	CN



https://www.phoenixcontact.com/us/products/3240066



Technical data

Product properties

	Product type	Connector
El	ectrical properties	
	Fuse	yes

Dimensions

Dimensional drawing	
Length of the insulating material sleeve	11 mm
Length contact range	12 mm
Maximum stripping length	8 mm
Min. material thickness	0.8 mm
Inner dimensions of the insulating collar	4.5 mm
Internal dimensions	
Internal diameter	2 mm

Material specifications

Color	blue
Material	Copper
Flammability rating according to UL 94	V2
Coating	tin-plated
Insulating material	PA
Components	halogen-free

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C 105 °C



https://www.phoenixcontact.com/us/products/3240066



Classifications

UNSPSC 21.0

ECLASS

	ECLASS-11.0	27400204
	ECLASS-12.0	27400204
	ECLASS-13.0	27400204
ETIM		
	ETIM 9.0	EC001052
UNSPSC		

27121700

3240066

https://www.phoenixcontact.com/us/products/3240066



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com