

https://www.phoenixcontact.com/us/products/3240639



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable duct for installation and mounting in control cabinets, white, comprising upper part and mounting base, width: 100 mm, height: 80 mm, length: 2000 mm

Your advantages

- · Predetermined breaking point enables tool-free, burr-free removal of bars
- · Thanks to its leverage and special cutting geometry, the PPS CD cable duct cutter enables easy, burr-free cutting with minimum effort
- · Easy, burr-free cutting with minimum effort using the CUTFOX-CD cable duct cutter
- · The wide, diagonal heads of the cable duct bars make it easy to fit the cover and hold it securely in place
- · Installed conductors are securely held in place by means of wire retaining clips that can be snapped onto bars on the side
- · Plastic body-bound rivets enable easy fixing of cable ducts using the rivet setting tool

Commercial data

| Item number | 3240639 |
|--------------------------------------|---------------------|
| Packing unit | 6 pc |
| Minimum order quantity | 6 pc |
| Sales key | BE74 |
| Product key | BE7433 |
| Catalog page | Page 581 (C-3-2019) |
| GTIN | 4046356629652 |
| Weight per piece (including packing) | 1,890 g |
| Weight per piece (excluding packing) | 1,890 g |
| Customs tariff number | 39259020 |
| Country of origin | DE |



https://www.phoenixcontact.com/us/products/3240639



Technical data

Product properties

| | Product type | Wiring duct |
|----|-----------------------|-------------|
| Co | onnection data | |
| | Nominal cross section | 5577 mm² |

Dimensions

| Dimensional drawing | 6.5 |
|---------------------|---------|
| Width | 100 mm |
| Height | 2000 mm |
| Depth | 80 mm |
| Length | 2000 mm |

Material specifications

| Color | white |
|----------------------------------------|-----------|
| Material | PVC |
| Flammability rating according to UL 94 | V0 |
| Components | Lead-free |

Cable/line

| Halogen-free | no |
|--------------|----|

Environmental and real-life conditions

Ambient conditions

| Ambient temperature (operation) | -5 °C 60 °C |
|---------------------------------|-------------|
|---------------------------------|-------------|



https://www.phoenixcontact.com/us/products/3240639



Classifications

UNSPSC 21.0

ECLASS

| | ECLASS-11.0 | 27400703 |
|------|-------------|----------|
| | ECLASS-12.0 | 27400703 |
| | ECLASS-13.0 | 27400703 |
| ETIM | | |
| | ETIM 9.0 | EC000012 |
| UN | ISPSC | |

39131700



https://www.phoenixcontact.com/us/products/3240639



Environmental product compliance

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---------------------------------------------------------|
| | No hazardous substances above threshold values |

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com