

# WT-E HF 3,6X150 - Cable tie



3240718

<https://www.phoenixcontact.com/us/products/3240718>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable binders ideal for permanent fastening to virtually any surface, with fastening lug for screwing or fixing with rivets

## Commercial data

Item number	3240718
Packing unit	100 pc
Minimum order quantity	100 pc
Sales key	BE07
Product key	BE7133
Catalog page	Page 618 (C-3-2019)
GTIN	4046356704342
Weight per piece (including packing)	0.872 g
Weight per piece (excluding packing)	0.872 g
Customs tariff number	39269097
Country of origin	HR

# WT-E HF 3,6X150 - Cable tie

3240718

<https://www.phoenixcontact.com/us/products/3240718>



## Technical data

### Product properties

Product type	Cable tie
Type	Internal teeth
Tensile strength GRP	130 N

### Dimensions

Width	3.6 mm
Length	150 mm
Hole diameter	4.5 mm

### Material specifications

RoHS compliant	yes
Color	transparent
Material	PA 6.6
Flammability rating according to UL 94	V2
Components	free from silicone and halogen

### Cable/line

External cable diameter	2 mm ... 32 mm
Tensile strength	130 N

### Environmental and real-life conditions

#### Ambient conditions

Optimum ambient temperature (storage/transport)	23.00 °C 50.00 % Polyamide 6.6 has pronounced hygroscopic properties. It absorbs or releases water in accordance with the level of humidity within its environment. Its properties are ideal when the percentage of water is 2 - 3%. The packaging, which is tailored specifically to the product concerned, contains the optimum level of moisture. To ensure that the ideal properties are maintained, the following points should be observed during storage: Keep product stored inside sealed original packaging, carry out any product processing soon after breaking open the packaging, avoid direct sunlight, avoid direct heat.
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (assembly)	-10 °C ... 60 °C
Resistance to UV radiation	no
Short-term temperature	110 °C
Recommended storage conditions	23 °C/50 % relative humidity. Storage in a dry and dark place in the original packaging is recommended.

### Standards and regulations

Resistance to UV radiation	no
----------------------------	----

### Mounting

# WT-E HF 3,6X150 - Cable tie

3240718

<https://www.phoenixcontact.com/us/products/3240718>



Mounting type	Cannot be removed
	Screw mounting

# WT-E HF 3,6X150 - Cable tie

3240718

<https://www.phoenixcontact.com/us/products/3240718>



## Classifications

### ECLASS

ECLASS-11.0	27140702
ECLASS-12.0	27140702
ECLASS-13.0	27140702

### ETIM

ETIM 9.0	EC000046
----------	----------

### UNSPSC

UNSPSC 21.0	39121700
-------------	----------

# WT-E HF 3,6X150 - Cable tie

3240718

<https://www.phoenixcontact.com/us/products/3240718>



## Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)