

WT-STEEL S 7,9X838 - Cable tie

3240725

<https://www.phoenixcontact.com/us/products/3240725>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable binders, made from rust-free stainless steel (AISI 304), suitable for harsh ambient conditions, with ball lock, for quick and secure bundling and fastening

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 3240725 |
| Packing unit | 100 pc |
| Minimum order quantity | 100 pc |
| Sales key | BE07 |
| Product key | BE7132 |
| Catalog page | Page 620 (C-3-2019) |
| GTIN | 4046356704410 |
| Weight per piece (including packing) | 15 g |
| Weight per piece (excluding packing) | 15.2 g |
| Customs tariff number | 73269098 |
| Country of origin | GB |

WT-STEEL S 7,9X838 - Cable tie



3240725

<https://www.phoenixcontact.com/us/products/3240725>

Technical data

Product properties

| | |
|----------------------|-------------|
| Product type | Cable tie |
| Type | Steel strip |
| Tensile strength GRP | 1335 N |

Dimensions

| | |
|-------------------------|---------|
| Width | 7.9 mm |
| Length | 838 mm |
| Max. material thickness | 0.25 mm |

Material specifications

| | |
|----------------|---------------------------------|
| RoHS compliant | yes |
| Color | silver |
| Material | Stainless steel 1.4301/AISI 304 |
| Components | free from silicone and halogen |

Cable/line

| | |
|-------------------------|-------------|
| External cable diameter | ≤ 254.00 mm |
| Tensile strength | 1335 N |

Environmental and real-life conditions

Ambient conditions

| | |
|---------------------------------|-------------------|
| Ambient temperature (operation) | -80 °C ... 538 °C |
| Ambient temperature (assembly) | -80 °C ... 538 °C |
| Resistance to UV radiation | yes |

Standards and regulations

| | |
|----------------------------|-----|
| Resistance to UV radiation | yes |
|----------------------------|-----|

Mounting

| | |
|---------------|-------------------|
| Mounting type | Cannot be removed |
|---------------|-------------------|

WT-STEEL S 7,9X838 - Cable tie



3240725

<https://www.phoenixcontact.com/us/products/3240725>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27140702 |
| ECLASS-12.0 | 27140702 |
| ECLASS-13.0 | 27140702 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC000046 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 39121700 |
|-------------|----------|

WT-STEEL S 7,9X838 - Cable tie



3240725

<https://www.phoenixcontact.com/us/products/3240725>

Environmental product compliance

| | |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
| | No hazardous substances above threshold values |

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com