

3240827

https://www.phoenixcontact.com/us/products/3240827

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable binders, made from rust-free stainless steel (AISI 316), suitable for the harshest of ambient conditions (for example, salt water), with ball lock, for quick and secure bundling and fastening

Commercial data

Item number	3240827
Packing unit	100 pc
Minimum order quantity	100 pc
Sales key	BE07
Product key	BE7132
Catalog page	Page 621 (C-3-2019)
GTIN	4046356705752
Weight per piece (including packing)	5.893 g
Weight per piece (excluding packing)	5.893 g
Customs tariff number	73269098
Country of origin	GB



https://www.phoenixcontact.com/us/products/3240827



Technical data

Product properties

Product type	Cable tie
Туре	Steel strip
Tensile strength GRP	1335 N

Dimensions

Width	7.9 mm
Length	259 mm
Max. material thickness	0.25 mm

Material specifications

Color	silver
Material	Stainless steel 1.4401/AISI 316
Components	free from silicone and halogen

Cable/line

External cable diameter	≤ 69.00 mm
Tensile strength	1335 N

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-80 °C 538 °C
Ambient temperature (assembly)	-80 °C 538 °C
Resistance to UV radiation	yes

Standards and regulations

Resistance to UV radiation	ves	
Resistance to uv radiation	yes	

Mounting

Mounting type	Cannot be removed



3240827

https://www.phoenixcontact.com/us/products/3240827

Classifications

UNSPSC 21.0

ECLASS

27140702
27140702
27140702
EC000046

39121700



https://www.phoenixcontact.com/us/products/3240827



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 @ - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com