

# WP-SPIRAL PU C HF 14 - Protective hose



3240857

<https://www.phoenixcontact.com/us/products/3240857>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Protective hose, material: PU, filament: PUR sheathed spring steel, UV-resistant: no, flexible, degree of protection: IP68, color: blue, flammability rating in acc. with UL 94: V2, inner diameter: 10 mm, Total length: 10 m

## Commercial data

|                                      |                     |
|--------------------------------------|---------------------|
| Item number                          | 3240857             |
| Packing unit                         | 1 m                 |
| Minimum order quantity               | 1 m                 |
| Sales key                            | BF68                |
| Product key                          | BF7DSA              |
| Catalog page                         | Page 593 (C-3-2019) |
| GTIN                                 | 4046356736831       |
| Weight per piece (including packing) | 776 g               |
| Weight per piece (excluding packing) | 776 g               |
| Customs tariff number                | 39173200            |
| Country of origin                    | DE                  |

# WP-SPIRAL PU C HF 14 - Protective hose



3240857

<https://www.phoenixcontact.com/us/products/3240857>

## Technical data

### Notes

|         |  |
|---------|--|
| General | Protective hose length is measured stretched out; length tolerance $\pm 5\%$ |
|---------|--|

### Product properties

|                      |                 |
|----------------------|-----------------|
| Product type         | Corrugated pipe |
| Tensile strength GRP | 100 N           |

### Dimensions

#### External dimensions

|                  |       |
|------------------|-------|
| Outside diameter | 14 mm |
|------------------|-------|

#### Internal dimensions

|                   |       |
|-------------------|-------|
| Internal diameter | 10 mm |
|-------------------|-------|

### Material specifications

|  |  |
|--|--|
| Material                               | PU                                       |
| Material Coil                          | PUR                                      |
| Flammability rating according to UL 94 | V2                                       |
| Components                             | free from silicone, halogen, and cadmium |

### Cable/line

|                         |       |
|-------------------------|-------|
| Bending radius, dynamic | 25 mm |
| Bending radius, static  | 10 mm |
| Tensile strength        | 100 N |
| Halogen-free            | yes   |

### Environmental and real-life conditions

#### Ambient conditions

|                                 |                   |
|---------------------------------|-------------------|
| Degree of protection            | IP68              |
| Ambient temperature (operation) | -40 °C ... 100 °C |
| Resistance to UV radiation      | no                |
| Short-term temperature          | 120 °C            |

### Standards and regulations

|                            |    |
|----------------------------|----|
| Resistance to UV radiation | no |
|----------------------------|----|

# WP-SPIRAL PU C HF 14 - Protective hose



3240857

<https://www.phoenixcontact.com/us/products/3240857>

## Classifications

### ECLASS

|             |          |
|-------------|----------|
| ECLASS-11.0 | 27430304 |
| ECLASS-12.0 | 27430304 |
| ECLASS-13.0 | 27430304 |

### ETIM

|          |          |
|----------|----------|
| ETIM 9.0 | EC001177 |
|----------|----------|

### UNSPSC

|             |          |
|-------------|----------|
| UNSPSC 21.0 | 40141700 |
|-------------|----------|

# WP-SPIRAL PU C HF 14 - Protective hose



3240857

<https://www.phoenixcontact.com/us/products/3240857>

## Environmental product compliance

|            |   |
|------------|---|
| China RoHS | Environmentally friendly use period: unlimited = EFUP-e<br>No hazardous substances above threshold values |
|------------|---|

Phoenix Contact 2024 © - all rights reserved  
<https://www.phoenixcontact.com>

Phoenix Contact USA  
586 Fulling Mill Road  
Middletown, PA 17057, United States  
(+717) 944-1300  
[info@phoenixcon.com](mailto:info@phoenixcon.com)