

3240877

https://www.phoenixcontact.com/us/products/3240877

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable gland, Pg thread, IP68/69k protection, straight

# Commercial data

| Item number                          | 3240877             |
|--------------------------------------|---------------------|
| Packing unit                         | 50 pc               |
| Minimum order quantity               | 50 pc               |
| Sales key                            | BF68                |
| Product key                          | BF7DSA              |
| Catalog page                         | Page 587 (C-3-2019) |
| GTIN                                 | 4046356709842       |
| Weight per piece (including packing) | 11.73 g             |
| Weight per piece (excluding packing) | 11.73 g             |
| Customs tariff number                | 39174000            |
| Country of origin                    | DE                  |



3240877

https://www.phoenixcontact.com/us/products/3240877

# Technical data

## Product properties

| Product type                 | Corrugated pipe screw connection |
|------------------------------|----------------------------------|
| Application                  | Cable gland                      |
| Type of the screw connection | Conduit adapter                  |
| Туре                         | Outer thread                     |
| Cable outlet                 | straight                         |
| Thread type                  | Pg                               |

## **Dimensions**

| Width                    | 29.5 mm |
|--------------------------|---------|
| Height                   | 46 mm   |
| Wrench size for mounting | 27 mm   |

## Material specifications

| Material                               | PA 6                                     |
|--|--|
| Flammability rating according to UL 94 | V2                                       |
| Material for screw connection          | PA                                       |
| Components                             | free from silicone, halogen, and cadmium |

# Cable/line

| Halogen-free | yes |
|--------------|-----|

# Mechanical properties

#### Mechanical data

| Type of the screw connection | Conduit adapter |
|------------------------------|-----------------|

## Environmental and real-life conditions

## Ambient conditions

| Degree of protection            | IP68          |
|---------------------------------|---------------|
|                                 | IP69K         |
| Ambient temperature (operation) | -40 °C 120 °C |

# Mounting

| Wrench size | 27 mm |
|-------------|-------|



3240877

https://www.phoenixcontact.com/us/products/3240877

# Classifications

UNSPSC 21.0

## **ECLASS**

| ECLASS-11.0 | 27430311 |
|-------------|----------|
| ECLASS-12.0 | 27430311 |
| ECLASS-13.0 | 27430311 |
| ETIM        |          |
| ETIM 9.0    | EC001178 |
| UNSPSC      |          |

39121300



3240877

https://www.phoenixcontact.com/us/products/3240877

# Environmental product compliance

| China RoHS | Environmentally friendly use period: unlimited = EFUP-e |
|------------|---|
|            | No hazardous substances above threshold values          |

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com