

WP-EC TPE HF 34,5 BK - Transition sleeve from hose to cable



3240979

<https://www.phoenixcontact.com/us/products/3240979>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Transition sleeve from hose to cable, material: TPE, color: black, flammability rating in acc. with UL 94: HB

Commercial data

Item number	3240979
Packing unit	25 pc
Minimum order quantity	25 pc
Sales key	BF68
Product key	BF7DSA
Catalog page	Page 585 (C-3-2019)
GTIN	4046356710978
Weight per piece (including packing)	9.232 g
Weight per piece (excluding packing)	9.232 g
Customs tariff number	39174000
Country of origin	DE

WP-EC TPE HF 34,5 BK - Transition sleeve from hose to cable



3240979

<https://www.phoenixcontact.com/us/products/3240979>

Technical data

Product properties

Product type	Protective cap
--------------	----------------

Dimensions

Length	44.2 mm
Diameter	34.5 mm

Material specifications

Material	TPE
Flammability rating according to UL 94	HB
Components	halogen-free

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-40 °C ... 120 °C
Short-term temperature	150 °C

WP-EC TPE HF 34,5 BK - Transition sleeve from hose to cable



3240979

<https://www.phoenixcontact.com/us/products/3240979>

Classifications

ECLASS

ECLASS-11.0	27430316
ECLASS-12.0	27430316
ECLASS-13.0	27430316

ETIM

ETIM 9.0	EC000519
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

WP-EC TPE HF 34,5 BK - Transition sleeve from hose to cable



3240979
<https://www.phoenixcontact.com/us/products/3240979>

Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com