

WP-GT BRASS PG36 - Screw connection



3241029

<https://www.phoenixcontact.com/us/products/3241029>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable gland made from brass with Pg thread, rotatable, IP40 protection

Commercial data

| | |
|--------------------------------------|---------------------|
| Item number | 3241029 |
| Packing unit | 2 pc |
| Minimum order quantity | 2 pc |
| Sales key | BF68 |
| Product key | BF7DSA |
| Catalog page | Page 599 (C-3-2019) |
| GTIN | 4046356711654 |
| Weight per piece (including packing) | 167.5 g |
| Weight per piece (excluding packing) | 167.5 g |
| Customs tariff number | 74122000 |
| Country of origin | DE |

WP-GT BRASS PG36 - Screw connection



3241029

<https://www.phoenixcontact.com/us/products/3241029>

Technical data

Product properties

| | |
|------------------------------|----------------------------------|
| Product type | Corrugated pipe screw connection |
| Type of the screw connection | Conduit adapter |
| Type | Outer thread |
| Cable outlet | straight |
| Thread type | Pg |

Dimensions

| | |
|--------------------------|-------|
| Width | 58 mm |
| Height | 40 mm |
| Length | 40 mm |
| Wrench size for mounting | 55 mm |

External dimensions

| | |
|------------------|-------|
| Outside diameter | 45 mm |
|------------------|-------|

Internal dimensions

| | |
|-------------------|---------|
| Internal diameter | 36.5 mm |
|-------------------|---------|

Material specifications

| | |
|------------|----------------------|
| Color | Brass |
| Material | Brass, nickel-plated |
| Components | halogen-free |

Mechanical properties

Mechanical data

| | |
|------------------------------|-----------------|
| Type of the screw connection | Conduit adapter |
|------------------------------|-----------------|

Environmental and real-life conditions

Ambient conditions

| | |
|---------------------------------|-------------------|
| Degree of protection | IP40 |
| Ambient temperature (operation) | -40 °C ... 250 °C |

Mounting

| | |
|-------------|-------|
| Wrench size | 55 mm |
|-------------|-------|

WP-GT BRASS PG36 - Screw connection



3241029

<https://www.phoenixcontact.com/us/products/3241029>

Classifications

ECLASS

| | |
|-------------|----------|
| ECLASS-11.0 | 27430310 |
| ECLASS-13.0 | 27430310 |
| ECLASS-12.0 | 27430310 |

ETIM

| | |
|----------|----------|
| ETIM 9.0 | EC001180 |
|----------|----------|

UNSPSC

| | |
|-------------|----------|
| UNSPSC 21.0 | 40141700 |
|-------------|----------|

WP-GT BRASS PG36 - Screw connection



3241029

<https://www.phoenixcontact.com/us/products/3241029>

Environmental product compliance

| | |
|------------|--|
| REACH SVHC | Lead 7439-92-1 |
| China RoHS | Environmentally Friendly Use Period = 50 years |
| | For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com