## WP-G BRASS IP65 M10 - Screw connection

#### 3241058

https://www.phoenixcontact.com/us/products/3241058

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.



Cable gland made from brass with metric thread, IP65 protection

### Commercial data

| Item number                          | 3241058             |
|--------------------------------------|---------------------|
| Packing unit                         | 10 pc               |
| Minimum order quantity               | 10 pc               |
| Sales key                            | BF68                |
| Product key                          | BF7DSA              |
| Catalog page                         | Page 600 (C-3-2019) |
| GTIN                                 | 4046356712088       |
| Weight per piece (including packing) | 14.32 g             |
| Weight per piece (excluding packing) | 14.32 g             |
| Customs tariff number                | 74122000            |
| Country of origin                    | DE                  |

PHENIX

# WP-G BRASS IP65 M10 - Screw connection

3241058

https://www.phoenixcontact.com/us/products/3241058



## Technical data

#### Product properties

| Product type                          | Corrugated pipe screw connection |
|---------------------------------------|----------------------------------|
| Туре                                  | Outer thread                     |
| Cable outlet                          | straight                         |
| Thread type                           | metric                           |
| mensions                              |                                  |
| Width                                 | 19 mm                            |
| Height                                | 31 mm                            |
| Length                                | 31 mm                            |
| Wrench size for mounting              | 15 mm                            |
|                                       | 17 mm                            |
| External dimensions                   |                                  |
| Outside diameter                      | 10 mm                            |
| Internal dimensions                   |                                  |
| Internal diameter                     | 6 mm                             |
| aterial specifications                |                                  |
| Material                              | Brass, nickel-plated             |
| Components                            | halogen-free                     |
| nvironmental and real-life conditions |                                  |
| Degree of protection                  | IP65                             |
|                                       | -40 °C 125 °C                    |

#### Mounting

| Wrench size | 15 mm |
|-------------|-------|
|-------------|-------|

3241058

https://www.phoenixcontact.com/us/products/3241058



## Classifications

#### ECLASS

| ECLASS-11.0 | 27430310 |
|-------------|----------|
| ECLASS-12.0 | 27430310 |
| ECLASS-13.0 | 27430310 |

### ETIM

|        | ETIM 9.0    | EC001180 |  |  |
|--------|-------------|----------|--|--|
| UNSPSC |             |          |  |  |
|        | UNSPSC 21.0 | 40141700 |  |  |

## WP-G BRASS IP65 M10 - Screw connection

3241058

https://www.phoenixcontact.com/us/products/3241058



### Environmental product compliance

| REACh SVHC | Lead 7439-92-1  |
|------------|---|
|            |   |
|            |   |
| China RoHS | Environmentally Friendly Use Period = 50 years  |
|            | For information on hazardous substances, refer to the<br>manufacturer's declaration available under "Downloads" |

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com