WG-D HF 16 BK - Cable driller

3241106

https://www.phoenixcontact.com/us/products/3241106

PHŒNIX CONTACT

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Cable drillers, for fast and tool-free bundling of conductors and cables, removable and reusable



Commercial data

Item number	3241106
Packing unit	500 pc
Minimum order quantity	500 pc
Sales key	BE07
Product key	BE7133
Catalog page	Page 623 (C-3-2019)
GTIN	4046356717359
Weight per piece (including packing)	0.723 g
Weight per piece (excluding packing)	0.624 g
Customs tariff number	39269097
Country of origin	TW

WG-D HF 16 BK - Cable driller

3241106

https://www.phoenixcontact.com/us/products/3241106



Technical data

Product properties

Product type	Cable tie
Туре	Notched strip
Tensile strength GRP	0 N

Dimensions

Width	16 mm
Length	34.5 mm

Material specifications

Material PA 6.6 Flammability rating according to UL 94 V2 Components free from silicone and halogen	Color	black
	Material	PA 6.6
Components free from silicone and halogen	Flammability rating according to UL 94	V2
	Components	free from silicone and halogen

Cable/line

External cable diameter	13.5 mm 16 mm
Tensile strength	0 N

Environmental and real-life conditions

Optimum ambient temperature (storage/transport)	23.00 °C 50.00 % Polyamide 6.6 has pronounced hygroscopic properties. It absorbs or releases water in accordance with the level of humidity within its environment. Its properties are ideal when the percentage of water is 2 - 3%. The packaging, which is tailored specifically to the product concerned, contains the optimum level of moisture. To ensure that the ideal properties are maintained, the following points should be observed during storage: Keep product stored inside sealed original packaging, carry out any product processing soon after breaking open the packaging, avoid direct sunlight, avoid direct heat.
Ambient temperature (operation)	-40 °C 85 °C
Ambient temperature (assembly)	-10 °C 60 °C
Resistance to UV radiation	no
indards and regulations	
Resistance to UV radiation	no

Mounting type	Twist

WG-D HF 16 BK - Cable driller

3241106

https://www.phoenixcontact.com/us/products/3241106



Classifications

ECLASS

ECLASS-11.0	27140702
ECLASS-12.0	27140702
ECLASS-13.0	27140702

ETIM

	ETIM 9.0	EC000046
UNSPSC		
	UNSPSC 21.0	39121700



3241106

https://www.phoenixcontact.com/us/products/3241106



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved https://www.phoenixcontact.com

Phoenix Contact USA 586 Fulling Mill Road Middletown, PA 17057, United States (+717) 944-1300 info@phoenixcon.com