

WP-OR M16 - Sealing ring

3241189

<https://www.phoenixcontact.com/us/products/3241189>



Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Sealing ring, for threads M16, color: black



Your advantages

- The properties of the Perbunan O-rings, such as their resistance to oil and seal against water and dust, mean that they can be used in a wide range of applications

Commercial data

Item number	3241189
Packing unit	50 pc
Minimum order quantity	50 pc
Sales key	BF68
Product key	BF7DSA
Catalog page	Page 607 (C-3-2019)
GTIN	4046356785952
Weight per piece (including packing)	0.238 g
Weight per piece (excluding packing)	0.238 g
Customs tariff number	40169300
Country of origin	DE

WP-OR M16 - Sealing ring

3241189

<https://www.phoenixcontact.com/us/products/3241189>



Technical data

Product properties

Product type	Seal
Thread type	M16

Dimensions

Height	2 mm
Thread type connection side	M16

Internal dimensions

Internal diameter	14 mm
-------------------	-------

Material specifications

Material	Perbunan
----------	----------

Environmental and real-life conditions

Ambient conditions

Ambient temperature (operation)	-20 °C ... 120 °C
---------------------------------	-------------------

WP-OR M16 - Sealing ring

3241189

<https://www.phoenixcontact.com/us/products/3241189>



Classifications

ECLASS

ECLASS-11.0	27430319
ECLASS-12.0	27430319
ECLASS-13.0	27430319

ETIM

ETIM 9.0	EC001181
----------	----------

UNSPSC

UNSPSC 21.0	39121400
-------------	----------

WP-OR M16 - Sealing ring

3241189

<https://www.phoenixcontact.com/us/products/3241189>



Environmental product compliance

China RoHS	Environmentally friendly use period: unlimited = EFUP-e
	No hazardous substances above threshold values

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com