

BMK 20X 8 YE - Fabric label sheet



5031388

<https://www.phoenixcontact.com/us/products/5031388>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Fabric label sheet, Sheet, yellow, unlabeled, can be labeled with: CMS-P1-PLOTTER, PLOTMARK, mounting type: adhesive, lettering field size: 20 x 8 mm, Number of individual labels: 270



Your advantages

- Available in various dimensions
- Self-adhesive labels for labeling by hand or with a plotter
- Secure adhesion even on curved or uneven surfaces as well as round corners
- Labeling service: Phoenix Contact can custom-label all BMK ... markers according to your requirements

Commercial data

Item number	5031388
Packing unit	10 pc
Minimum order quantity	10 pc
Sales key	BG13
Product key	BG2414
Catalog page	Page 345 (C-3-2019)
GTIN	4017918095413
Weight per piece (including packing)	11.29 g
Weight per piece (excluding packing)	10.6 g
Customs tariff number	39199080
Country of origin	BE

BMK 20X 8 YE - Fabric label sheet



5031388

<https://www.phoenixcontact.com/us/products/5031388>

Technical data

Product properties

Product type	Device marking
Marking	
Number of individual labels	270
Number of individual labels per row	9
Identification technology	Plotter

Mounting

Mounting type	adhesive
---------------	----------

Material specifications

Adhesive	Acrylic
Color	yellow
Material	Polyester foil
Flammability rating according to UL 94	V0
Base element material	Polyester foil
Components	Silicone-free

Environmental and real-life conditions

Test for substances that would hinder coating with paint or varnish

Result	Test passed
--------	-------------

UV resistance

Specification	ISO 4892-2:2013-03 (following)
Result	Test passed
Test duration	96 h

Wipe resistance of inscriptions

Specification	DIN EN 61010-1 (VDE 0411-1):2011-07
	DIN EN 62208 (VDE 0660-511):2012-06 (in parts)
Isopropyl [CAS No. 67-63-0]	Test passed
n-Hexane [CAS No. 110-54-3]	Test passed
Water + Petroleum ether [CAS No. 64742-82-1]	Test passed

Testing in a condensation changing climate in the presence of sulfur dioxide

Specification	DIN 50018:2013-05
Result	Test passed
Climate level	AHT 1.0 S
Cycles	2

BMK 20X 8 YE - Fabric label sheet



5031388

<https://www.phoenixcontact.com/us/products/5031388>

Salt spray test

Specification	DIN EN 60068-2-11:2000-02
Result	Test passed

Ambient conditions

Ambient temperature (operation)	-40 °C ... 80 °C
Recommended ambient temperature (storage/transport)	23 °C
Recommended humidity (storage/transport)	50 % (Storage in a dry and dark place in the original packaging is recommended)

Dimensions

Width	20 mm
Length	8 mm

Notes

General	Can be labeled with CMS
---------	-------------------------

BMK 20X 8 YE - Fabric label sheet



5031388
<https://www.phoenixcontact.com/us/products/5031388>

Classifications

ECLASS

ECLASS-11.0	27281103
ECLASS-12.0	27281103
ECLASS-13.0	27281103

ETIM

ETIM 9.0	EC001288
----------	----------

UNSPSC

UNSPSC 21.0	39131500
-------------	----------

Phoenix Contact 2024 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com