

Data sheet | Item number: 2000-2291  
End and intermediate plate; 0.7 mm thick; gray

[www.wago.com/2000-2291](http://www.wago.com/2000-2291)



## Data

### Geometrical Data

Width	0.7 mm / 0.028 inch
Height	51.7 mm / 2.035 inch
Depth	70 mm / 2.756 inch

### Material Data

Color	gray
Fire load	0.062 MJ
Weight	2.1 g

### Commercial data

Product Group	22 (TOPJOB S)
Packaging type	BOX
Country of origin	DE

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.



GTIN 4050821037187

Customs Tariff No. 85389099990

## Counterpart

## Downloads

### Documentation

#### Additional Information

Technical explanations	Apr 3, 2019	pdf 2.1 MB	Download
------------------------	-------------	---------------	----------

## CAD/CAE-Data

### CAD data

2D/3D Models 2000-2291	URL	Download
------------------------	-----	----------

### CAE data

EPLAN Data Portal 2000-2291	URL	Download
-----------------------------	-----	----------

WSCAD Universe 2000-2291	URL	Download
--------------------------	-----	----------

## Installation Notes

## Product family

### TOPJOB® S

TOPJOB® S: In various industrial applications and modern building installations, WAGO's wide and versatile range of rail-mount terminal blocks provides more than just reliable electrical connections.

[Learn more about the product family.](#)

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.