

Data sheet | Item number: 267-124

Female connector; with direct ground contact; 4-pole; 1,00 mm²; white

www.wago.com/267-124



RoHS 
Compliant


[BOMcheck.net](https://www.bomcheck.net)

Color: 


Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com


Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



for 0.6 ... 1.0 mm plate thickness



Conductor support



① Diameter of drilled hole: 4.2 mm

② Diameter of drilled hole: 5.2 mm

Drilled hole for direct ground contact must be free of varnish and oxide films.

Equipped with varnished metal plates upon request.

1) Diameter of drilled hole: 4.2 mm 2) Diameter of drilled hole: 5.2 mm
Drilled hole for direct ground contact must be free of varnish and oxide films.
Equipped with varnished metal plates upon request.

Item description

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



- Flexible, modular 5- to 11-pole connector system
- Future system expansions possible
- Compact design

Data

Electrical data

Ratings per IEC/EN 60664-1

| | |
|---------------------------------|---|
| Rated voltage (III / 2) | 500 V |
| Rated impulse voltage (III / 2) | 4 kV |
| Rated current | 6 A |
| Legend (ratings) | (III / 2) $\hat{=}$ Overvoltage category III / Pollution degree 2 |

Approvals per UL 1059

| | |
|---------------|---------|
| Approvals per | UL 1059 |
|---------------|---------|

Connection data

| | |
|----------------------------|------------------|
| Strip length | 8 mm / 0.31 inch |
| No. of poles | 4 |
| Number of connection types | 1 |

Geometrical Data

| | |
|-------------------------|--------------------|
| Width | 32 mm / 1.26 inch |
| Height from the surface | 34 mm / 1.339 inch |
| Depth | 32 mm / 1.26 inch |

Material Data

| | |
|-----------------------------|-----------------------------------|
| Color | white |
| Material group | I |
| Insulating material | Polyamide 66 (PA 66) |
| Flammability class per UL94 | V0 |
| Clamping spring material | Chrome nickel spring steel (CrNi) |
| Contact material | Electrolytic copper (E_{Cu}) |
| Contact plating | tin-plated |

Subject to changes. Please also observe the further product documentation!



| | |
|-----------|----------|
| Fire load | 0.141 MJ |
| Weight | 7.7 g |

Environmental Requirements



| | |
|-----------------------|--------|
| Temperature stability | 105 °C |
|-----------------------|--------|

Commercial data


| | |
|--------------------|--------------------------------|
| Product Group | 8 (Misc. Chassis Mount Blocks) |
| Packaging type | bag |
| Country of origin | PL |
| GTIN | 4044918499552 |
| Customs Tariff No. | 85369010000 |

Approvals / Certificates

Country specific Approvals

| Logo | Approval | Additional Approval Text | Certificate name |
|--|---|--------------------------|------------------|
| | CCA DEKRA Certification B.V. | EN 61984 | NL-47718 |
|  | KEMA/KEUR DEKRA Certification B.V. | EN 61984 | 71-100641 |
|  | VDE VDE Prüf- und Zertifizierungsinstitut | EN 61984 | 40032309 |

UL-Approvals

| Logo | Approval | Additional Approval Text | Certificate name |
|--|---|--------------------------|------------------|
|  | UL Underwriters Laboratories Inc. | UL 1977 | 20130910-E45171 |

Counterpart

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.



Downloads

Documentation

Additional Information

| | | | |
|------------------------|-------------|---------------|----------|
| Technical explanations | Apr 3, 2019 | pdf 3.6 MB | Download |
|------------------------|-------------|---------------|----------|

CAD/CAE-Data

CAD data

| | | |
|----------------------|-----|----------|
| 2D/3D Models 267-124 | URL | Download |
|----------------------|-----|----------|

CAE data

| | | |
|---------------------------|-----|----------|
| EPLAN Data Portal 267-124 | URL | Download |
|---------------------------|-----|----------|

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.