



RoHS Compliant

BOMcheck.net

Data

Electrical data

Ratings per IEC/EN 60664-1

Rated voltage (III / 2)	400 V
Rated impulse voltage (III / 2)	4 kV
Rated current	18 A
Legend (ratings)	(III / 2) ≙ Overvoltage category III / Pollution degree 2

Approvals per UL 1059

Approvals per	UL 1059
---------------	---------

Connection data

Connection technology	PUSH WIRE®
Strip length	8 ... 9 mm / 0.31 ... 0.35 inch

Subject to changes. Please also observe the further product documentation!



Total number of connection points	12
Number of connection types	1

Geometrical Data

Width	28,5 mm / 1.122 inch
Height	19 mm / 0.748 inch
Depth	24,5 mm / 0.965 inch

Material Data

Fire load	0.165 MJ
Weight	9.9 g

Commercial data

Packaging type	bag
Country of origin	DE
GTIN	4017332038690
Customs Tariff No.	85369010000

Counterpart

Compatible products

ferrule

Item no.: 209-151 Pin terminals; insulated; suitable for 271 and 272 Series; green	www.wago.com/209-151
Item no.: 209-157 Pin terminals; insulated; suitable for 271 and 272 Series; blue	www.wago.com/209-157
Item no.: 209-164 Pin terminals; insulated; suitable for 271 and 272 Series; natural	www.wago.com/209-164

assembling

Item no.: 271-702 Pins; for plate thickness 1 mm	www.wago.com/271-702
Item no.: 271-711 Pins; for plate thickness 1 mm	www.wago.com/271-711
Item no.: 271-712 Pins; for plate thickness 1.5 mm	www.wago.com/271-712

Subject to changes. Please also observe the further product documentation!



Downloads

Documentation

Additional Information

Technical explanations	Apr 3, 2019	pdf 3.6 MB	Download
------------------------	-------------	---------------	----------

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.