

RoHS Compliant

BOMcheck.net

Data

Electrical data

Ratings per IEC/EN 60664-1

Rated voltage (III / 2)	400 V
Rated impulse voltage (III / 2)	4 kV
Rated current	18 A
Legend (ratings)	(III / 2) ≙ Overvoltage category III / Pollution degree 2

Approvals per UL 1059

Approvals per	UL 1059
---------------	---------

Connection data

Connection technology	PUSH WIRE®
Solid conductor	0,5 ... 1,5 mm ² / 20 ... 16 AWG

Subject to changes. Please also observe the further product documentation!

Strip length	8 ... 9 mm / 0.31 ... 0.35 inch
No. of poles	4
Solid conductor (2)	0,5 ... 2,5 mm ² / 20 ... 14 AWG
Total number of connection points	16
Total number of potentials	4
Number of connection types	1

Geometrical Data

Width	38,5 mm / 1.516 inch
Height	19 mm / 0.748 inch
Depth	24,5 mm / 0.965 inch

Material Data


Fire load	0.211 MJ
Weight	12.7 g

Commercial data


Packaging type	bag
Country of origin	DE
GTIN	4044918439688
Customs Tariff No.	85369010000

Approvals / Certificates

Country specific Approvals

Logo	Approval	Additional Approval Text	Certificate name
	CSA DEKRA Certification B.V.	C22.2 No. 158	70048844

UL-Approvals

Logo	Approval	Additional Approval Text	Certificate name
	UR Underwriters Laboratories Inc.	UL 1059	20190731- E45172

Subject to changes. Please also observe the further product documentation!

Counterpart

Compatible products

tools



Item no.: 249-100

Operating tool; for terminal blocks with snap-in ground contact

www.wago.com/249-100

assembling

Item no.: 271-702

Pins; for plate thickness 1 mm

www.wago.com/271-702

Item no.: 271-711

Pins; for plate thickness 1 mm

www.wago.com/271-711

Item no.: 271-712

Pins; for plate thickness 1.5 mm

www.wago.com/271-712

ferrule

Item no.: 209-151

Pin terminals; insulated; suitable for 271 and 272 Series; green

www.wago.com/209-151

Item no.: 209-157

Pin terminals; insulated; suitable for 271 and 272 Series; blue

www.wago.com/209-157

Item no.: 209-164

Pin terminals; insulated; suitable for 271 and 272 Series; natural

www.wago.com/209-164

Downloads

Documentation

Additional Information

Technical explanations

Apr 3, 2019

pdf
3.6 MB

Download

Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.