


Data sheet | Item number: 750-833
 Controller PROFIBUS Slave; 2,50 mm²; light gray

www.wago.com/750-833



RoHS Compliant ✓



BOMcheck.net

Color: ■

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.



Item description

The PROFIBUS DP/V1 Controller combines control functionality, I/O interface and fieldbus in one device.

Application programming is IEC 61131-3 compliant.

The programmer can access all fieldbus and I/O data.

Features and applications:

- Decentralized control to optimize support for a PLC or PC
- Divide complex applications into individually testable units
- Programmable fault response in the event of fieldbus failure
- Signal pre-processing to reduce fieldbus transmissions
- Directly control peripheral equipment for faster system response times
- Stand-alone, compact controller

Subject to changes. Please also observe the further product documentation!

Note:**Note: Configuration files required (GSD)!**

The GSD files can be downloaded for free at www.wago.com.

Data**Technical Data**

| | |
|--|---|
| Communication | PROFIBUS |
| Visualization | without |
| CPU | 16 bits |
| Programming languages per IEC 61131-3 | Instruction List (IL) Ladder Diagram (LD) Function Block Diagram (FBD), Continuous Function Chart (CFC) Structured Text (ST) Sequential Function Chart (SFC) |
| Programming environment | WAGO-I/O-PRO V2.3 (based on CODESYS V2.3) |
| Configuration options | GSD device description file WAGO-I/O-CHECK |
| Cycle time | < 3 ms for 1000 bit instructions/ 256 digital I/O |
| Baud rate | 9,6 kBd ... 12 MBd |
| Fieldbus segment length max. | 1200 m |
| Transmission medium (communication/fieldbus) | Cu cable per EN 50170 |
| Transmission time | typ. 1 ms (10 controllers; each 32 digital I/O and 12 Mbaud) max. 3.3 ms |
| Number of fieldbus nodes on the master max. | 96 |
| Max. no. of I/O points | 6,000 |
| Program memory | 128 kByte |
| Data memory | 64 kByte |
| Software non-volatile memory | 8 Kbytes |
| Memory for fieldbus input variables max. | 244 Byte |
| Memory for fieldbus output variables max. | 244 Byte |
| Number of modules per node max. | 63 |
| Input and output process image (Fieldbus) max. | 244 Byte/244 Byte |
| Indicators | LED (RUN) green: Fieldbus initialization, LED (BF, DIA, BUS) red: communication error, external diagnostics, configuration; LED (I/O, USR) red/green/orange: Local data bus status, status programmable by user; LED (A, B) green: System power supply status, field supply |
| System supply voltage | DC 24 V(-25 ... +30 %); via pluggable connector (CAGE CLAMP®) |

Subject to changes. Please also observe the further product documentation!



| | |
|--|--|
| | connection) |
| Input current typ. at rated load (24 V) | 500 mA |
| Efficiency of the power supply (typ.) at nominal load (24 V) | 87 % |
| Current consumption, system supply (5 V) | 200 mA |
| Total current for system supply | 1,800 mA |
| Field supply voltage | DC 24 V (-25 ... +30 %); via power jumper contacts |
| Current carrying capacity of the power jumper contacts | 10 A |
| Number of outgoing power jumper contacts | 3 |
| Isolation | 500 V system/field |
| Standard | EN 50170 |

Connection data

| | |
|---|--|
| Connection technology: communication/fieldbus | PROFIBUS: 1 x D-Sub 9 socket |
| Connection technology: system supply | 2 x CAGE CLAMP® |
| Connection technology: field supply | 6 x CAGE CLAMP® |
| Connection type (1) | System/field supply |
| Solid conductor | 0,08 ... 2,5 mm ² / 28 ... 14 AWG |
| Fine-stranded conductor | 0,08 ... 2,5 mm ² / 28 ... 14 AWG |
| Strip length | 8 ... 9 mm / 0.31 ... 0.35 inch |
| Connection technology: Device configuration | 1 x Male connector; 4-pole |

Geometrical Data

| | |
|---------------------------------------|----------------------|
| Width | 50,5 mm / 1.988 inch |
| Height | 71,1 mm / 2.799 inch |
| Height from upper-edge of DIN-35 rail | 63,9 mm / 2.516 inch |
| Depth | 100 mm / 3.937 inch |

Mechanical data

| | |
|--------------------|------------------------------|
| Weight | 186.9 g |
| Color | light gray |
| Housing material | Polycarbonate, polyamide 6.6 |
| Conformity marking | CE |

Environmental Requirements

| | |
|---|---------------|
| Surrounding air (operating) temperature | 0 ... 55 °C |
| Surrounding air (storage) temperature | -40 ... 85 °C |

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
 Hansastr. 27
 32423 Minden
 Phone: +49571 887-0 | Fax: +49571 887-169
 Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
 We are always happy to take your call at +49 (571) 887-44222.



| | |
|--|---|
| Protection class | IP20 |
| Degree of pollution (5) | 2 per IEC 61131-2 |
| Operating altitude | without temperature derating: 0 ... 2000 m; with temperature derating: 2000 ... 5000 m (0.5 K/100 m); 5000 m (max.) |
| Relative air humidity (no condensation) | 95 % |
| Mounting position | any |
| Type of mounting | DIN-35 rail |
| Vibration resistance | 4g per IEC 60068-2-6 |
| Shock resistance | 15g per IEC 60068-2-27 |
| EMC immunity to interference | per EN 61000-6-2, marine applications |
| EMC emission of interference | per EN 61000-6-4, marine applications |
| Exposure to pollutants | Per IEC 60068-2-42 and IEC 60068-2-43 |
| Fire load | 2.779 MJ |
| Permissible H ₂ S contaminant concentration at a relative humidity 75 % | 10 ppm |
| Permissible SO ₂ contaminant concentration at a relative humidity 75 % | 25 ppm |

Commercial data

| | |
|--------------------|-----------------|
| Product Group | 15 (Remote I/O) |
| Packaging type | BOX |
| Country of origin | DE |
| GTIN | 4045454527075 |
| Customs Tariff No. | 85371091990 |

Approvals / Certificates

Ex-Approvals


| Logo | Approval | Additional Approval Text | Certificate name |
|--|--|--------------------------|-----------------------------------|
|  | ATEX TUEV Nord Cert GmbH | EN 60079-0 | TÜV 07 ATEX 554086 X en. |
|  | TUEV Nord TUEV Nord Cert GmbH | IEC 60079-0 | IECEX TUN 09.0001 X |
| | UL Underwriters Laboratories Inc. (HAZARDOUS) | UL 121201 | E198726 Sec.1 |

Subject to changes. Please also observe the further product documentation!



LOCATIONS)

Country specific Approvals

| Logo | Approval | Additional Approval Text | Certificate name |
|--|--------------------------------------|--------------------------|-----------------------------|
|  | KC National Radio Research Agency | Article 58-2, Clause 3 | MSIP- REM-W43- PFC750 |

Ship Approvals

| Logo | Approval | Additional Approval Text | Certificate name |
|--|--|--------------------------|--------------------------|
|  | ABS American Bureau of Shipping | - | 19- HG1821926 |
|  | BV Bureau Veritas S.A. | - | 13453/DO BV |
|  | DNV GL Det Norske Veritas, Germanischer Lloyd | - | TAA0000194 |
|  | KR Korean Register of Shipping | - | KR HMB05880- AC001 |
|  | LR Lloyds Register | - | 02/20026 (E6) |
|  | NK Nippon Kaiji Kyokai | - | TA17255M |
|  | PRS Polski Rejestr Statków | - | TE/2236 /880590/19 |


Subject to changes. Please also observe the further product documentation!



RINA
RINA Germany GmbH

ELE066419XG



UL-Approvals

| Logo | Approval | Additional Approval Text | Certificate name |
|--|--|--------------------------|------------------|
|  | UL UL International Netherlands B.V. (ORDINARY LOCATIONS) | UL 508 | E175199 Sec.1 |

Counterpart

Compatible products






system box

| | | |
|--|---|--|
| | Item no.: 850-804 IP65 enclosure; Stainless steel; WxHxD (400x123x200 mm); 4 x M20, 16 x M16, 28 x M12 cable grip | www.wago.com/850-804 |
| | Item no.: 850-804/000-001 IP65 enclosure; Stainless steel; WxHxD (400x123x200 mm); 2 x M20, 13 x M16, 32 x M12 cable grip | www.wago.com/850-804/000-001 |
|  | Item no.: 850-805 IP65 enclosure; Stainless steel; WxHxD (600x123x200 mm); 4 x M20, 19 x M16, 67 x M12 cable grip | www.wago.com/850-805 |
| | Item no.: 850-814/002-000 IP65 enclosure; Sheet steel (RAL 7035); WxHxD (200x120x200 mm); without flange plate | www.wago.com/850-814/002-000 |
| | Item no.: 850-815/002-000 IP65 enclosure; Sheet steel (RAL 7035); WxHxD (300x120x200 mm); without flange plate | www.wago.com/850-815/002-000 |
|  | Item no.: 850-816/002-000 IP65 enclosure; Sheet steel (RAL 7035); WxHxD (400x120x200 mm); without flange plate | www.wago.com/850-816/002-000 |








Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com


Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.

| | | |
|--|--|--|
| | <p>Item no.: 850-817/002-000 IP65 enclosure; Sheet steel (RAL 7035); WxHxD (600x120x200 mm); without flange plate</p> | www.wago.com/850-817/002-000 |
|  | <p>Item no.: 850-825 IP65 enclosure; Aluminium (RAL 7032); WxHxD (160x100x160 mm); 9 x M12, 4 x M20</p> | www.wago.com/850-825 |
| | <p>Item no.: 850-826 IP65 enclosure; Aluminium (RAL 7032); WxHxD (240x100x160 mm); 4 x M20, 4 x M16, 14 x M12 cable grip</p> | www.wago.com/850-826 |
| | <p>Item no.: 850-826/002-000 IP65 enclosure; Aluminium (RAL 7035); WxHxD (240x100x160 mm); 4 x M20, 4 x M16, 14 x M12 cable grip</p> | www.wago.com/850-826/002-000 |
| | <p>Item no.: 850-827 IP65 enclosure; Aluminium (RAL 7032); WxHxD (320x100x160 mm); 4 x M20, 8 x M16, 17 x M12 cable grip</p> | www.wago.com/850-827 |
| | <p>Item no.: 850-827/002-000 IP65 enclosure; Aluminium (RAL 7035); WxHxD (320x100x160 mm); 4 x M20, 8 x M16, 17 x M12 cable grip</p> | www.wago.com/850-827/002-000 |
| | <p>Item no.: 850-828 IP65 enclosure; Aluminium (RAL 7032); WxHxD (480x100x160 mm); 4 x M20, 10 x M16, 35 x M12 cable grip</p> | www.wago.com/850-828 |
| | <p>Item no.: 850-828/002-000 IP65 enclosure; Aluminium (RAL 7035); WxHxD (480x100x160 mm); 4 x M20, 10 x M16, 35 x M12 cable grip</p> | www.wago.com/850-828/002-000 |
|  | <p>Item no.: 850-834 IP65 enclosure; Polyester (RAL 7032); WxHxD (164x100x164 mm); 9 x M12, 4 x M20</p> | www.wago.com/850-834 |
| | <p>Item no.: 850-835 IP65 enclosure; Polyester (RAL 7032); WxHxD (244x100x164 mm); 4 x M20, 4 x M16, 14 x M12 cable grip</p> | www.wago.com/850-835 |
|  | <p>Item no.: 850-836 IP65 enclosure; Polyester (RAL 7032); WxHxD (324x100x164 mm); 4 x M20, 8 x M16, 17 x M12 cable grip</p> | www.wago.com/850-836 |
| Carrier rail | | |
| | <p>Item no.: 210-112 Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 25 mm</p> | www.wago.com/210-112 |
|  | <p>Item no.: 210-113 Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; according to EN 60715</p> | www.wago.com/210-113 |
|  | <p>Item no.: 210-114 Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; similar to EN 60715</p> | www.wago.com/210-114 |
| | <p>Item no.: 210-115 Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; according to EN 60715; "Hole width 18 mm</p> | www.wago.com/210-115 |
| | <p>Item no.: 210-118 Steel carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715</p> | www.wago.com/210-118 |


Subject to changes. Please also observe the further product documentation!


| | | |
|--|---|--|
|  | Item no.: 210-196 Aluminum carrier rail; 35 x 8.2 mm; 1.6 mm thick; 2 m long; unslotted; similar to EN 60715; silver-colored | www.wago.com/210-196 |
|  | Item no.: 210-197 Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; similar to EN 60715 | www.wago.com/210-197 |
| | Item no.: 210-198 Copper carrier rail; 35 x 15 mm; 2.3 mm thick; 2 m long; unslotted; according to EN 60715; copper-colored | www.wago.com/210-198 |
| | Item no.: 210-504 Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; slotted; galvanized; according to EN 60715 | www.wago.com/210-504 |
|  | Item no.: 210-505 Steel carrier rail; 35 x 7.5 mm; 1 mm thick; 2 m long; unslotted; galvanized; according to EN 60715 | www.wago.com/210-505 |
| | Item no.: 210-506 Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; unslotted; galvanized; similar to EN 60715 | www.wago.com/210-506 |
| | Item no.: 210-508 Steel carrier rail; 35 x 15 mm; 1.5 mm thick; 2 m long; slotted; galvanized; similar to EN 60715 | www.wago.com/210-508 |
| wiring and connectors | | |
|  | Item no.: 750-960 Fieldbus Connector PROFIBUS; with D-sub male connector; 9-pole; light gray | www.wago.com/750-960 |
| General accessories | | |
|  | Item no.: 750-921 Bluetooth® Adapter; light gray | www.wago.com/750-921 |
|  | Item no.: 750-923 Configuration cable; USB connector; Length: 2.5 m; black | www.wago.com/750-923 |
| | Item no.: 750-923/000-001 Configuration cable; USB connector; Length: 5 m | www.wago.com/750-923/000-001 |
| Marking accessories | | |
| | Item no.: 2009-145 Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white | www.wago.com/2009-145 |
| | Item no.: 2009-145/000-002 Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white /000-002 | www.wago.com/2009-145/000-002 |
|  | Item no.: 2009-145/000-005 Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; red /000-005 | www.wago.com/2009-145/000-005 |


Subject to changes. Please also observe the further product documentation!

 **Item no.: 2009-145/000-006**
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; blue www.wago.com/2009-145/000-006

Item no.: 2009-145/000-007
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; white www.wago.com/2009-145/000-007


 **Item no.: 2009-145/000-012**
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; orange www.wago.com/2009-145/000-012

 **Item no.: 2009-145/000-023**
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; green www.wago.com/2009-145/000-023


 **Item no.: 2009-145/000-024**
Mini-WSB Inline; for Smart Printer; 1700 pieces on roll; stretchable 5 - 5.2 mm; plain; snap-on type; violet www.wago.com/2009-145/000-024

 **Item no.: 248-501**
Miniature WSB Quick marking system; plain; Marker width 5 mm; 10 strips with 10 markers per card www.wago.com/248-501

Item no.: 248-501/000-002
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; yellow www.wago.com/248-501/000-002

 **Item no.: 248-501/000-005**
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; red www.wago.com/248-501/000-005

Item no.: 248-501/000-006
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; blue www.wago.com/248-501/000-006

 **Item no.: 248-501/000-007**
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; gray www.wago.com/248-501/000-007

Item no.: 248-501/000-012
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; orange www.wago.com/248-501/000-012

Item no.: 248-501/000-017
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; light green www.wago.com/248-501/000-017

Item no.: 248-501/000-023
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; green www.wago.com/248-501/000-023

Subject to changes. Please also observe the further product documentation!



Item no.: 248-501/000-024
Mini-WSB marking card; as card; not stretchable; plain; snap-on type; violet

www.wago.com/248-501/000-024



Item no.: 750-100
Marker card; as a DIN A4 sheet; plain; white

www.wago.com/750-100



Item no.: 750-103
Group marker carrier; transparent

www.wago.com/750-103

Item no.: 750-106
Group marker carrier; transparent

www.wago.com/750-106

software

Item no.: 759-333
WAGO-I/O-PRO

www.wago.com/759-333

Item no.: 759-333/000-923
WAGO-I/O-PRO; USB-Set

www.wago.com/759-333/000-923



Item no.: 759-911
WAGO-I/O-PRO; CD

www.wago.com/759-911

shield connection

Item no.: 790-108
Shield clamping saddle; 11 mm wide; diameter of compatible conductor; 3 ... 8 mm

www.wago.com/790-108

Item no.: 790-116
Shield clamping saddle; 19 mm wide; diameter of compatible conductor; 7 ... 16 mm

www.wago.com/790-116

Item no.: 790-124
Shield clamping saddle; 27 mm wide; diameter of compatible conductor; 6 ... 24 mm

www.wago.com/790-124

Item no.: 790-140
Shield clamping saddle; diameter of compatible conductor

www.wago.com/790-140



Item no.: 790-208
Shield clamping saddle; 12.4 mm wide; 3 ... 8 mm

www.wago.com/790-208



Item no.: 790-216
Shield clamping saddle; 21.8 mm wide; 6 ... 16 mm

www.wago.com/790-216

Item no.: 790-220
Shield clamping saddle; 30 mm wide; 6 ... 20 mm

www.wago.com/790-220

Downloads

Documentation

Manual

PROFIBUS DP/V1 Programmable Fieldbus Controller

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG
Hansastr. 27
32423 Minden
Phone: +49571 887-0 | Fax: +49571 887-169
Email: info.de@wago.com | Web: www.wago.com

Do you have any questions about our products?
We are always happy to take your call at +49 (571) 887-44222.



| | | | |
|---|-------------------------|-----------------|----------|
| EN 50170, 12 MBaud, digital and analog signals | V 1.0.1 | pdf 2.7 MB | Download |
| WAGOupload For commissioning, management and configuration of ETHERNET 750 Series fieldbus controllers | V 6.0.0 Oct 29, 2019 | pdf 4.4 MB | Download |
| Additional Information | | | |
| Disposal; Electrical and electronic equipment, Packaging | V 1.0.0 | pdf 265.8 kB | Download |
| System Description | | | |
| Design Notes Basic conditions and recommendations for higher operational safety | V 2.0.0 | pdf 1.5 MB | Download |
| Overview on WAGO-I/O-SYSTEM 750 approvals | | pdf 780.2 kB | Download |
| 750 Controller, General Product Information | | pdf 621.9 kB | Download |
| Use in Hazardous Environments Term definition, marking and installation regulations | V 1.0.0 | pdf 1.0 MB | Download |

Application Notes

Application Note CoDeSys 2.3

| | | | |
|--|------------------------|-----------------|----------|
| HART Tool Routing via PROFIBUS with 750-833 and 750-333 (a116140) This application note describes how to set up asset management systems, which facilitate simple, efficient configuration of HART field devices. Using the Cerabar PMC51 (Endress+Hauser) as an example, connecting any HART sensor to a WAGO PROFIBUS controller and a WAGO PROFIBUS Coupler is explained. The cyclic PROFIBUS Master (750-8208) realizes the data exchange. As an acyclic master, a TH LINK PROFIBUS provides access for the plant asset management applications WAGOframe, PACTware and FieldCare. | 1.0.0 Mar 22, 2019 | pdf 5.3 MB | Download |
| Profibus PFC 750-833 Configuring & Networking (a202201) This document is to be used with the example node from the document PFC 101 Get Started Quick. The following describes Configuring and networking the example node using the software and equipment listed below. | V1.0.0 Nov 28, 2002 | zip 210.8 kB | Download |

Subject to changes. Please also observe the further product documentation!



Libraries

Library

| | | | |
|---|------------------------|-----------------|----------|
| Condition monitoring with 750-645 The WagoLib_VIO.lib library provides a function block which allows to configure the module 750-645. | V1.0.1 Jul 27, 2011 | zip 112.8 kB | Download |
| Control DC motor with 750-636 The "MC1_DC_Control.lib" library provides a function block which allows to configure the module 750-636 as well as to operate a DC motor. | V1.0.0 Nov 8, 2017 | zip 150.5 kB | Download |
| Connecting HART-Modules 750-482 and 750-484 The library "WagoLibHART_03.lib" offers a set of function blocks to execute HART-commands (Revision 5) in a PLC program. The principal item of this library is program HART_INFO, it identifies connected HART modules like 750-482 and coordinates the Kbus access. In addition you find with HART_FDT program that act as counterpart to WAGO-ModbusTCP-HART-DTM, who enable configuration of HART devices with every FDT-Frameapplication like "WAGOframe". | V3.1.0 Jan 19, 2018 | zip 331.0 kB | Download |

Engineering-Software

Configuration and Commissioning Software

| | | | |
|---|-------------------------|-----------------|----------|
| WAGO Extension Setting / Serie 750 | 2.0.2 Mar 9, 2011 | zip 5.4 MB | Download |
| WAGO-IO-PRO Demo-Version (759-912) / Serie 750, 758 und 762 | 2.3.9.55 Jul 3, 2015 | zip 108.3 MB | Download |

Runtime Software

Firmware

| | | | |
|--|--------------------|-----------------|----------|
| Firmware: 750-833 Controller PROFIBUS Slave; 2,50 mm ² ; light gray | 19 Feb 26, 2018 | zip 612.7 kB | Download |
|--|--------------------|-----------------|----------|

CAD/CAE-Data

CAD data

| | | |
|----------------------|-----|----------|
| 2D/3D Models 750-833 | URL | Download |
|----------------------|-----|----------|

CAE data

Subject to changes. Please also observe the further product documentation!



EPLAN Data Portal 750-833

[URL](#)

[Download](#)

WSCAD Universe 750-833

[URL](#)

[Download](#)

Device Files

Device Description File

| | | | |
|--|---------------------|-----------------|--------------------------|
| EDD Datei für SIMATIC PDM für 750-333, 750-833, 750-482, 750-484 | 1.0 Nov 22, 2010 | zip 185.2 kB | Download |
|--|---------------------|-----------------|--------------------------|

| | | | |
|---|---------------------|---------------|--------------------------|
| 750-910; GSD files for PROFIBUS / 750, 752, 755, 758 and 767 Series | 6.4 Nov 15, 2019 | zip 4.9 MB | Download |
|---|---------------------|---------------|--------------------------|

Device Driver

| | | | |
|--|-------------------------|---------------|--------------------------|
| WAGO USB Service Kabel Treiber / Serie 750 und 857 | 6.5.3.0 Sep 10, 2014 | zip 4.8 MB | Download |
|--|-------------------------|---------------|--------------------------|

Installation Notes

Product family

Controller 750

[Learn more about the product family.](#)

[Show all products from the family](#)

Subject to changes. Please also observe the further product documentation!