



# Data Connection data

No. of poles	3	

## Mechanical data

Mounting type	Snap-in
Suitable	for cutout

## Material Data

Color	white
Insulating material	Polyamide 66 (PA 66)
Flammability class per UL94	VO
Fire load	0.051 MJ
Weight	1.7 g

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG Hansastr. 27 32423 Minden Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.



## **Environmental Requirements**

Processing temperature	-5 +40 °C
Continuous operating temperature	-35 +85 ℃
Note on Continuous Service Temperature	Insulating parts for temperatures ≤ 105 °C

#### **Commercial data**

Product Group	20 (WINSTA)
Packaging type	BOX
Country of origin	DE
GTIN	4017332755450
Customs Tariff No.	39269097900

## Counterpart

Downloads CAD/CAE-Data CAD data		
2D/3D Models 770-693	URL	Download
CAE data		
WSCAD Universe 770-693	URL	Download

### Installation Notes

## **Product family**

<i>WINSTA</i>® MIDI Show all products from the family

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG Hansastr. 27 32423 Minden Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.