



Data Connection data

No. of poles

4

Mechanical data

Mounting type	Snap-in
Suitable	for cutout

Material Data

Color	white
Insulating material	Polyamide 66 (PA 66)
Flammability class per UL94	VO
Fire load	0.064 MJ
Weight	2.1 g

Environmental Requirements

Processing temperature	Processing	temperature
------------------------	------------	-------------

-5 ... +40 °C

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG	Do you have any questions about our products?
Hansastr. 27	We are always happy to take your call at +49 (571) 887-44222.
32423 Minden	
Phone: +49571 887-0 Fax: +49571 887-169	
Email: info.de@wago.com Web: www.wago.com	

www.wago.com/770-694



Continuous operating temperature	-35 +85 °C
Note on Continuous Service Temperature	Insulating parts for temperatures ≤ 105 °C

Commercial data

Product Group	20 (WINSTA)
Packaging type	BOX
Country of origin	DE
GTIN	4017332802154
Customs Tariff No.	39269097900

Counterpart

Downloads CAD/CAE-Data CAD data		
2D/3D Models 770-694	URL	Download
CAE data		
WSCAD Universe 770-694	URL	Download

Installation Notes

Product family

<i>WINSTA</i>® MIDI Show all products from the family

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG Hansastr. 27 32423 Minden Phone: +49571 887-0 | Fax: +49571 887-169 Email: info.de@wago.com | Web: www.wago.com Do you have any questions about our products? We are always happy to take your call at +49 (571) 887-44222.