

# Data sheet | Item number: 789-622

Current signal conditioner; Current input signal: 50 AAC; Modbus RTU;

Supply voltage: 24 VDC; Module width: 35 mm

[www.wago.com/789-622](http://www.wago.com/789-622)



RoHS  Compliant

[BOMcheck.net](https://www.bomcheck.net)

789-622

Pin	Function
1	Ub
2	
3	n.c.
4	A (Data+)
5	B (Data-)
6	n.c.
7	
8	GND

  

Modbus® Function	Read Holding Registers (0x03)
Address of Measured Value	0x0004
Data Type Measurement	Integer

  

id	Description
01	Illegal Function
03	Illegal Data
101	Overflow (Current > +83 A)
102	Underflow (Current < -3 A)

  

DIP Switch Adjustability  ON

Address	2	3	4	5	6	Terminating Resistor	DIP Switch 1
1						150 Ohm	<input checked="" type="checkbox"/>
2							
3							
4							
5							
6							
7							
8							
9							
10							
11							
12							
13							
14							
15							
16							
17							
18							
19							
20							
21							
22							
23							
24							
25							
26							
27							
28							
29							
30							
31							
32							

NOTICE:  
Only set the Modbus® address in the OFF state.

## Item description

### Short description:

This intelligent current sensor monitors AC currents and is mounted on DIN-35 rail.

## Data

### Technical Data

### Input

Input signal type

Electricity

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG

Hansastr. 27

32423 Minden

Phone: +49571 887-0 | Fax: +49571 887-169

Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?

We are always happy to take your call at +49 (571) 887-44222.



Input signal, current	AC 0 ... 50 A;
Resolution [bit]	14 Bit

### Communication

Communication	Modbus RTU
Interface	RS-485
Transmission channels	Half duplex; 8-bit data; 1 stop bit
Number of participants (max.)	32
Max. length of bus line	≤ 1200 m
Baud rate	19,2 kBd
Parity	Even
Terminating resistor	150 Ω (can be activated via DIP switch 1)

### Measurement error

Transmission error typ.	1 % (typ.); Max. 3 % of upper-range value (at room temperature)
Temperature coefficient	≤ 0.01 %/K

### Power supply

Nominal supply voltage $U_S$	DC 24 V
Supply voltage range	12 ... 34 VDC
Current consumption at supply voltage	≤ 8 mA

### Safety and protection:

Protection class	IP20
------------------	------

### Connection data

Feedthrough for measurement conductor	15 mm Ø
Connector	RJ-45

### Geometrical Data

Width	35 mm / 1.378 inch
Height from upper-edge of DIN-35 rail	55 mm / 2.165 inch
Depth	90 mm / 3.543 inch

Subject to changes. Please also observe the further product documentation!

## Mechanical data

Type of mounting	DIN-35 rail
------------------	-------------

## Material Data

Weight	77.2 g
--------	--------

## Environmental Requirements

Surrounding air (operating) temperature	-20 ... 70 °C
Surrounding air (storage) temperature	-40 ... 85 °C

## Standards and specifications

Conformity marking	CE
EMC immunity to interference	EN 61000-6-2
EMC emission of interference	EN 61000-6-4
Standards/specifications	DIN EN 50178

## Commercial data

Product Group	6 (Interface Electronics)
Packaging type	BOX
Country of origin	DE
GTIN	4050821374138
Customs Tariff No.	85437090300

## Counterpart

## Compatible products

### transfer module

<b>Item no.: 289-965</b> Interface module; 2xRJ-45; PCB terminal blocks, double-row; in mounting carrier	<a href="http://www.wago.com/289-965">www.wago.com/289-965</a>
<b>Item no.: 289-966</b> Interface module; 2xRJ-45; PCB terminal blocks, double-row; in mounting carrier; with shield connection	<a href="http://www.wago.com/289-966">www.wago.com/289-966</a>

### wiring and connectors

Subject to changes. Please also observe the further product documentation!



Item no.: 750-975

ETHERNET RJ-45 connector, IP20; ETHERNET 10/100 Mbit/s; for field assembly; light gray

[www.wago.com/750-975](http://www.wago.com/750-975)

## Downloads

### Documentation

#### Instruction Leaflet

Stromsensor, AC 0...50A	pdf 1.7 MB	Download
-------------------------	---------------	----------

#### Additional Information

Disposal; Electrical and electronic equipment, Packaging	V 1.0.0	pdf 265.8 kB	Download
--	---------	-----------------	----------

## CAD/CAE-Data

### CAD data

2D/3D Models 789-622	URL	Download
----------------------	-----	----------

### CAE data

EPLAN Data Portal 789-622	URL	Download
---------------------------	-----	----------

WSCAD Universe 789-622	URL	Download
------------------------	-----	----------

## Installation Notes

Subject to changes. Please also observe the further product documentation!

WAGO Kontakttechnik GmbH & Co. KG  
Hansastr. 27  
32423 Minden  
Phone: +49571 887-0 | Fax: +49571 887-169  
Email: [info.de@wago.com](mailto:info.de@wago.com) | Web: [www.wago.com](http://www.wago.com)

Do you have any questions about our products?  
We are always happy to take your call at +49 (571) 887-44222.