

### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

### **Product image**





### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

#### General ordering data

Delivery status	This article will no longer be available in the future.
Available until	2020-12-31
Туре	SAK 2.5 SW 1X1
Order No.	<u>0108560000</u>
Version	SAK Series, Feed-through terminal, Rated cross- section: 2.5 mm <sup>2</sup> , Screw connection, Busbar
GTIN (EAN)	4008190184032
Qty.	100 pc(s).
Alternative product	<u>1552790000</u>

# **Technical data**



### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Width	6 mm	Width (inches)	0.236 inch
Height	36.5 mm	Height (inches)	1.437 inch
Depth	67 mm	Depth (inches)	2.638 inch
Weight	8.63 g	Net weight	8.06 g
Temperatures			
	40.00		40.00
Storage temperature, max.	40 °C	Storage temperature, min.	10 °C
Storage temperature	<u>10 °C40 °C</u> 100 °C	Continuous operating temp., min.	-50 °C
Continuous operating temp., max.	100 °C		
Material data			
Material	PA 66	Colour	beige / yellow
UL 94 flammability rating	V-2		bolge / yellew
Version	Screw connection,	End cover plate required	
VEISION	With elbow connection, for screwable cross- connection, One end without connector		Yes
	for screwable cross- connection, One end	Number of clamping points per level	Yes 2
Number of levels	for screwable cross- connection, One end without connector	Number of clamping points per level Levels cross-connected internally	
Number of levels Number of potentials per tier	for screwable cross- connection, One end without connector 1		2
Number of levels Number of potentials per tier PE connection Additional technical data	for screwable cross- connection, One end without connector 1 1	Levels cross-connected internally	2 No
Number of levels Number of potentials per tier PE connection Additional technical data	for screwable cross- connection, One end without connector 1 1 No	Levels cross-connected internally Rail	2 No TS 32
Number of levels Number of potentials per tier PE connection Additional technical data Explosion-tested version	for screwable cross- connection, One end without connector 1 1 No No	Levels cross-connected internally Rail Installation advice	2 No TS 32 Busbar
Number of levels Number of potentials per tier PE connection Additional technical data	for screwable cross- connection, One end without connector 1 1 No	Levels cross-connected internally Rail	2 No TS 32

plastic collar DIN 46228/1, further connection, max. 2.5 mm<sup>2</sup>

# **Technical data**

**Conductors for clamping (rated connection)** 



### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Blade size	0.6 x 3.5 mm	Clamping range, max.	6 mm <sup>2</sup>
Clamping range, min.	0.33 mm <sup>2</sup>	Clamping screw	M 2.5
Connection cross-section, stranded,		Connection cross-section, stranded, m	in.
max.	2.5 mm <sup>2</sup>		0.5 mm <sup>2</sup>
Connection direction	on side	Gauge to IEC 60947-1	A3
Number of connections	1	Stripping length	10 mm
Tightening torque, max.	0.7 Nm	Tightening torque, min.	0.4 Nm
Twin wire-end ferrules, max.	1.5 mm <sup>2</sup>	Twin wire-end ferrules, min.	0.5 mm <sup>2</sup>
Type of connection		Wire connection cross section AWG,	
	Screw connection	max.	AWG 12
Wire connection cross section AWG, min.	AWG 22	Wire connection cross section, finely stranded, max.	4 mm <sup>2</sup>
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max.	2.5 mm <sup>2</sup>	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min.	0.5 mm²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max.	2.5 mm²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min.	0.5 mm²
Wire connection cross-section, finely stranded, min.	0.5 mm²	Wire connection cross-section, solid core, max.	6 mm <sup>2</sup>
Wire connection cross-section, solid			
core, min.	0.5 mm²		
Other connections			
Other connections Pin	1 x 1	Pin arrangement	top
Pin	1 x 1 right	Pin arrangement	top
		Pin arrangement	top
Pin Pin on side <b>Rating data</b>	right		
Pin Pin on side <b>Rating data</b> Rated cross-section	right 2.5 mm <sup>2</sup>	Rated voltage	250 V
Pin Pin on side <b>Rating data</b> Rated cross-section Rated current	right		
Pin Pin on side <b>Rating data</b>	right 2.5 mm <sup>2</sup> 8 A IEC 61210, In accordance	Rated voltage Current at maximum wires Volume resistance according to IEC	250 V 8 A
Pin Pin on side <b>Rating data</b> Rated cross-section Rated current Standards Power loss in accordance with IEC	right 2.5 mm <sup>2</sup> 8 A IEC 61210, In accordance with IEC 60947-7-1	Rated voltage Current at maximum wires Volume resistance according to IEC 60947-7-x	250 V 8 A 1.33 mΩ
Pin Pin on side Rating data Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x	right 2.5 mm <sup>2</sup> 8 A IEC 61210, In accordance with IEC 60947-7-1 0.77 W	Rated voltage Current at maximum wires Volume resistance according to IEC 60947-7-x	250 V 8 A 1.33 mΩ
Pin Pin on side Rating data Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x Pollution severity Classifications	right 2.5 mm <sup>2</sup> 8 A IEC 61210, In accordance with IEC 60947-7-1 0.77 W 3	Rated voltage Current at maximum wires Volume resistance according to IEC 60947-7-x Rated impulse withstand voltage	250 V 8 A 1.33 mΩ 4 kV
Pin Pin on side Rating data Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x Pollution severity	right 2.5 mm <sup>2</sup> 8 A IEC 61210, In accordance with IEC 60947-7-1 0.77 W	Rated voltage Current at maximum wires Volume resistance according to IEC 60947-7-x	250 V 8 A 1.33 mΩ

Approvals



ROHS

# **Technical data**



### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

User Documentation Safety note	<u>StorageConditionsTerminalBlocks</u>
Engineering Data	STEP
Engineering Data	EPLAN, WSCAD
Approval/Certificate/Document o Conformity	DE_PT1331_20160418_361_ISSUE01.pdf

Safety Information

Safety notice

**Downloads** 

### Accessories

#### Blank



### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

#### **General ordering data**

Туре	DEK 5/6.5 MC NE WS	Version
Order No.	<u>1609840000</u>	Dekafix, Terminal marker, 5 x 6.5 mm, Pitch in mm (P): 6.50
GTIN (EAN)	4008190203429	Weidmueller, white
Qty.	900 pc(s).	

#### Plus



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

### **General ordering data**

Туре	DEK 5/6 PLUS MC NE WS	Version
Order No.	<u>1011320000</u>	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4032248717644	Weidmueller, white
Qty.	1,000 pc(s).	

### Accessories

### End bracket



### **General ordering data**

Туре	EWK 1	Version
Order No.	0206160000	Accessories, End bracket
GTIN (EAN)	4008190080020	
Qty.	50 pc(s).	

different requirements.

### **Test plug**



### Current and voltage transformer wiring

Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.

General	ordering data	
Туре	PS 2.3 RT	Version
Order No.	<u>0180400000</u>	Accessories, Test plug
GTIN (EAN)	4008190060121	
Qty.	20 pc(s).	



### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Klippon® Connect with clamping yoke Technology The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of

### Accessories

### **Partition plates**



# Weidmüller 🔀

#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

#### **General ordering data**

Туре	WTW EN	Version
Order No.	<u>1058800000</u>	W-Series, Seperation plate
GTIN (EAN)	4008190140175	
Qty.	20 pc(s).	

### **Custom printing**

The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Туре	DEK 5/6 MC SDR	Version
Order No.	<u>1609830000</u>	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4008190456603	Weidmueller, To customer specification
Qty.	200 pc(s).	
czty.	200 pc(3).	
сиу. Туре	DEK 5/6 PLUS MC SDR	Version
		Version Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
Туре	DEK 5/6 PLUS MC SDR	

### Accessories

#### Blank



### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

#### **General ordering data**

Туре	DEK 5/5 MC NE WS	Version
Order No.	<u>1609801044</u>	Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00
GTIN (EAN)	4008190397111	Weidmueller, white
Qty.	1,000 pc(s).	

#### Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Туре	DEK 5/6 MC NE GN	Version
Order No.	<u>1238310000</u>	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4050118271812	Weidmueller, green
Qty.	1,000 pc(s).	

## Accessories



### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Туре	DEK 5/6 MC NE GE	Version
Order No.	<u>1238280000</u>	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4050118038750	Weidmueller, yellow
Qty.	1,000 pc(s).	
Туре	DEK 5/6 MC NE GR	Version
Order No.	<u>1238330000</u>	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4050118323306	Weidmueller, grey
Qty.	1,000 pc(s).	
Туре	DEK 5/6 MC NE WS	Version
Order No.	<u>1609820000</u>	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
GTIN (EAN)	4008190203436	Weidmueller, white
Qty.	1,000 pc(s).	
Туре	DEK 5/6 MC NE BL	Version
Type Order No.	DEK 5/6 MC NE BL 1238290000	Version Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
Order No.	<u>1238290000</u>	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
Order No. GTIN (EAN)	<u>1238290000</u> 4050118267327	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
Order No. GTIN (EAN) Qty.	1238290000 4050118267327 1,000 pc(s).	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00 Weidmueller, blue
Order No. GTIN (EAN) Qty. Type	1238290000 4050118267327 1,000 pc(s). DEK 5/6 MC NE OR	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00 Weidmueller, blue Version
Order No. GTIN (EAN) Qty. Type Order No.	1238290000 4050118267327 1,000 pc(s). DEK 5/6 MC NE OR 1912090000	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00 Weidmueller, blue Version Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
Order No. GTIN (EAN) Qty. Type Order No. GTIN (EAN)	1238290000         4050118267327         1,000 pc(s).         DEK 5/6 MC NE OR         1912090000         4032248540525	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00 Weidmueller, blue Version Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00
Order No. GTIN (EAN) Qty. Type Order No. GTIN (EAN) Qty.	1238290000 4050118267327 1,000 pc(s). DEK 5/6 MC NE OR 1912090000 4032248540525 1,000 pc(s).	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00 Weidmueller, blue Version Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00 Weidmueller, orange
Order No. GTIN (EAN) Qty. Type Order No. GTIN (EAN) Qty. Type	1238290000 4050118267327 1,000 pc(s). DEK 5/6 MC NE OR 1912090000 4032248540525 1,000 pc(s). DEK 5/6 MC NE BR	Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00 Weidmueller, blue Version Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00 Weidmueller, orange Version

### **Non-insulated sockets**



### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

	j	
Туре	STB 8.5/5/2.3/M3 SAK2.5	Version
Order No.	0280600000	Accessories, Socket
GTIN (EAN)	4008190023188	
Qty.	50 pc(s).	

### Accessories

### **DEK 5/6**





### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

#### WS/ DEK

MultiMark DEK/WS connector markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script. **Your benefits with MultiMark** 

### \_. . . . . . . . . .

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- · High flexibility thanks to manufacturer independence

### **General ordering data**

Туре	DEK 5/6 MM WS	Version
Order No.	<u>2007120000</u>	Dekafix, Terminal marker, 5 x 6 mm, Weidmueller, white
GTIN (EAN)	4050118392104	
Qty.	600 pc(s).	

### Q / SAK



#### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

### **General ordering data**

Туре	Q 10 SAK2.5	Version
Order No.	0368700000	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190107796	poles: 10
Qty.	20 pc(s).	
Туре	Q 3 SAK2.5	Version
Type Order No.	Q 3 SAK2.5 0337100000	Version SAK Series, Cross-connector, for cross-connection link, Number of

### Accessories



### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Туре	Q 2 SAK2.5	Version
Order No.	<u>0337000000</u>	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190005801	poles: 2
Qty.	50 pc(s).	
Туре	Q 4 SAK2.5	Version
Type Order No.	Q 4 SAK2.5 0337200000	Version SAK Series, Cross-connector, for cross-connection link, Number of

### Small partition



Klippon® Connect with clamping yoke Technology The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

#### **General ordering data**

Туре	TSCH 1	Version
Order No.	<u>0319160000</u>	SAK Series, Small partition, beige, 2 mm
GTIN (EAN)	4008190097219	
Qty.	100 pc(s).	

#### SchT group marker carrier



The SchT 5 S group tag carriers are clipped directly onto the TS 32 mounting rail (G-rail) or the TS 35 mounting rail (top-hat rail). It is therefore possible to label the terminal strip irrespective of the terminal and the type of terminal. SchT 5 and SchT 5 S are fitted with ESO 5, STR 5 protective strips.

The SchT 7 is a hinged group tag carrier for inlay tags which enables easy access to the clamping screw. The SchT 7 is fitted with ESO 7, STR 7 protective strips or DEK 5.

SchT 9/4 and SchT 14/6 are hinged group tag carriers for single dekafix and WS tags that enable easy access to the clamping screw.

SchT 9/4 and SchT 14/6 are fitted with WS or DEK. Inlay tags and protective strips can be found under "Accessories".

### **General ordering data**

Туре	SCHT 7	Version
Order No.	<u>0517960000</u>	SCHT, Terminal marker, 39.3 x 8 mm, Pitch in mm (P): 7.00
GTIN (EAN)	4008190001742	Weidmueller, white
Qty.	20 pc(s).	

### Accessories



### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

### End plates



### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

### **General ordering data**

Туре	AP SAK2.5	Version
Order No.	<u>0279560000</u>	SAK Series, End plate, 1.5 mm, beige, Direct mounting
GTIN (EAN)	4008190075736	
Qty.	20 pc(s).	
Туре	AP SAK2.5 BL	Version
Order No.	<u>0279580000</u>	SAK Series, End plate, 1.5 mm, blue, Direct mounting
GTIN (EAN)	4008190050702	
Qty.	20 pc(s).	

### **Partition plates**



Klippon® Connect with clamping yoke Technology The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

#### General ordering data

General	jj	
Туре	TW SAKS2 HP/DBR/2	Version
Order No.	<u>0607000000</u>	SAK Series, Seperation plate, 2 mm, dark brown, Used between
GTIN (EAN)	4008190002732	terminals
Qty.	20 pc(s).	
Туре	TW SAK2.5	Version
Order No.	0302860000	SAK Series, Seperation plate, 1.5 mm, beige, Direct mounting
GTIN (EAN)	4008190032968	
Qty.	20 pc(s).	
Туре	TW SAK2.5 BL	Version
Order No.	0302880000	SAK Series, Seperation plate, 1.5 mm, blue, Direct mounting
GTIN (EAN)	4008190047948	
Qty.	20 pc(s).	
Туре	TW SAK2.5 HP/TF/GE/1	Version
Order No.	<u>0297100000</u>	SAK Series, Seperation plate, 1 mm, yellow, Direct mounting
CTINI (EANI)	4008190161545	
GTIN (EAN)		
Qty.	20 pc(s).	

### Accessories

### **Custom printing**

					ļ



### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

	-	
Туре	DEK 5/6.5 MC SDR	Version
Order No.	<u>1609850000</u>	Dekafix, Terminal marker, 5 x 6.5 mm, Pitch in mm (P): 6.50
GTIN (EAN)	4008190456610	Weidmueller, To customer specification
Qty.	180 pc(s).	