

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Product image







Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

| Delivery status | This article will no longer be available in the future. |
|---------------------|---|
| Available until | 2020-12-31 |
| Туре | SAK 10 KRG |
| Order No. | 0110020000 |
| GTIN (EAN) | 4008190047214 |
| Qty. | 100 pc(s). |
| Alternative product | <u>1020300000</u> |



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Dimensions and weights

| Width | 10 mm | Width (inches) | 0.394 inch |
|------------|---------|-----------------|------------|
| Height | 40 mm | Height (inches) | 1.575 inch |
| Depth | 49 mm | Depth (inches) | 1.929 inch |
| Net weight | 22.68 g | | |

Temperatures

| Operating temperature range | For operating temperature range see EC Design Test Certificate / IEC Ex- | Storage temperature, max. | 10.00 |
|----------------------------------|--|----------------------------------|------------|
| | Certificate of Conformity | | 40 °C |
| Storage temperature, min. | 10 °C | Storage temperature | 10 °C40 °C |
| Continuous operating temp., min. | -60 °C | Continuous operating temp., max. | 130 °C |

Material data

| Material | KrG | Colour | medium yellow |
|---------------------------|----------|--------|---------------|
| UL 94 flammability rating | V-0, 5VA | | |

Rating data IECEx/ATEX

| Certificate No. (ATEX) | KEMA97ATEX1798U | Certificate No. (IECEX) | IECEXKEM06.0014U |
|--------------------------------|--|---------------------------------|------------------|
| Max. voltage (ATEX) | 550 V | Current (ATEX) | 50 A |
| Wire cross section max. (ATEX) | 10 mm² | Max. voltage (IECEX) | 550 V |
| Current (IECEX) | 50 A | Wire cross section max. (IECEX) | 10 mm² |
| Operating temperature range | For operating temperature range see EC Design Test Certificate / IEC Ex- Certificate of Conformity | Marking EN 60079-7 | Ex eb II C Gb |
| Ex 2014/34/EU label | II 2 G D | | |

System specifications

| Version | Screw connection, for screwable cross- connection, One end | End cover plate required | |
|-------------------------------------|--|-------------------------------|-----|
| | without connector | | Yes |
| Number of potentials | 1 | Number of levels | 1 |
| Number of clamping points per level | 2 | Number of potentials per tier | 1 |
| Levels cross-connected internally | No | PE connection | No |
| Rail | TS 32 | N-function | No |
| PE function | No | PEN function | No |

Additional technical data

| Open sides right Type of mounting Snap-on | Explosion-tested version | No | Number of similar terminals | 1 |
|---|--------------------------|-------|-----------------------------|---------|
| | Open sides | right | Type of mounting | Snap-on |

CSA rating data

| Certificate No. (CSA) | 154685-1501714 | Current size C (CSA) | 65 A |
|-------------------------------|----------------|-------------------------------|-------|
| Voltage size C (CSA) | 600 V | Wire cross section max. (CSA) | 6 AWG |
| Wire cross section min. (CSA) | 16 AWG | | |



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany Fon: +49 5231 14-0

Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Conductors for clamping (rated connection)

| Plada siza | 10 v 5 5 mm | Clamping range may | 16 mm² |
|--|--|--|---------------------------------------|
| Blade size | 1.0 x 5.5 mm | Clamping range, max. | |
| Clamping range, min. | 1.5 mm ² | Clamping screw | M 4 |
| Connection cross-section, stranded, max. | 16 mm ² | Connection cross-section, stranded, mir | n. 1.5 mm² |
| | | Cours to IFC 60047.1 | 86 |
| Connection direction | on side | Gauge to IEC 60947-1 | |
| Number of connections | 2 | Stripping length | 12 mm |
| Tightening torque, max. | 2.4 Nm | Tightening torque, min. | 2 Nm |
| Twin wire-end ferrules, max. | 6 mm ² | Twin wire-end ferrules, min. | 0.75 mm ² |
| Type of connection | Screw connection | Wire connection cross section AWG, | AWG 6 |
| Wire connection cross section AWG. | Screw connection | max. | AWG 6 |
| wire connection cross section AvvG, min. | AWG 14 | Wire connection cross section, finely stranded, max. | 16 mm² |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max. | 10 mm ² | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min. | 1.5 mm ² |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max. | 10 mm ² | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min. | 1.5 mm² |
| Wire connection cross-section, finely | | Wire connection cross-section, solid | |
| stranded, min. | 1.5 mm ² | core, max. | 10 mm ² |
| Wire connection cross-section, solid | 4.5 | | |
| core, min. | 1.5 mm ² | | |
| | | | |
| Rating data | | | |
| Rating data | | | |
| _ | 10? | Date developer | 999 V |
| Rated cross-section | 10 mm ² | Rated voltage | 800 V |
| Rated cross-section Rated current | 10 mm ² 57 A | Current at maximum wires | 800 V 76 A |
| Rated cross-section | 57 A | Current at maximum wires Volume resistance according to IEC | 76 A |
| Rated cross-section Rated current Standards | | Current at maximum wires Volume resistance according to IEC 60947-7-x | |
| Rated cross-section Rated current Standards Power loss in accordance with IEC | 57 A IEC 60947-7-1 | Current at maximum wires Volume resistance according to IEC | 76 A 0.56 mΩ |
| Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x | 57 A | Current at maximum wires Volume resistance according to IEC 60947-7-x | 76 A |
| Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x Pollution severity | 57 A IEC 60947-7-1 1.82 W | Current at maximum wires Volume resistance according to IEC 60947-7-x | 76 A 0.56 mΩ |
| Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x | 57 A IEC 60947-7-1 1.82 W | Current at maximum wires Volume resistance according to IEC 60947-7-x | 76 A 0.56 mΩ |
| Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x Pollution severity | 57 A IEC 60947-7-1 1.82 W | Current at maximum wires Volume resistance according to IEC 60947-7-x | 76 A 0.56 mΩ |
| Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x Pollution severity UL rating data | 57 A IEC 60947-7-1 1.82 W 3 | Current at maximum wires Volume resistance according to IEC 60947-7-x Rated impulse withstand voltage | 76 A 0.56 mΩ 8 kV |
| Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x Pollution severity UL rating data Certificate No. (UR) | 57 A IEC 60947-7-1 1.82 W 3 E60693 | Current at maximum wires Volume resistance according to IEC 60947-7-x Rated impulse withstand voltage Conductor size Factory wiring max. (UR | 76 A 0.56 mΩ 8 kV |
| Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x Pollution severity UL rating data Certificate No. (UR) Conductor size Factory wiring min. (UR) | 57 A IEC 60947-7-1 1.82 W 3 E60693 14 AWG | Current at maximum wires Volume resistance according to IEC 60947-7-x Rated impulse withstand voltage Conductor size Factory wiring max. (UR Conductor size Field wiring max. (UR) | 76 A 0.56 mΩ 8 kV) 6 AWG 6 AWG |
| Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x Pollution severity UL rating data Certificate No. (UR) Conductor size Factory wiring min. (UR) Conductor size Field wiring min. (UR) | 57 A IEC 60947-7-1 1.82 W 3 E60693 14 AWG 14 AWG | Current at maximum wires Volume resistance according to IEC 60947-7-x Rated impulse withstand voltage Conductor size Factory wiring max. (UR | 76 A 0.56 mΩ 8 kV |
| Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x Pollution severity UL rating data Certificate No. (UR) Conductor size Factory wiring min. (UR) | 57 A IEC 60947-7-1 1.82 W 3 E60693 14 AWG | Current at maximum wires Volume resistance according to IEC 60947-7-x Rated impulse withstand voltage Conductor size Factory wiring max. (UR Conductor size Field wiring max. (UR) | 76 A 0.56 mΩ 8 kV) 6 AWG 6 AWG |
| Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x Pollution severity UL rating data Certificate No. (UR) Conductor size Factory wiring min. (UR) Conductor size Field wiring min. (UR) | 57 A IEC 60947-7-1 1.82 W 3 E60693 14 AWG 14 AWG | Current at maximum wires Volume resistance according to IEC 60947-7-x Rated impulse withstand voltage Conductor size Factory wiring max. (UR Conductor size Field wiring max. (UR) | 76 A 0.56 mΩ 8 kV) 6 AWG 6 AWG |
| Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x Pollution severity UL rating data Certificate No. (UR) Conductor size Factory wiring min. (UR) Voltage size C (UR) Classifications | 57 A IEC 60947-7-1 1.82 W 3 E60693 14 AWG 14 AWG 600 V | Current at maximum wires Volume resistance according to IEC 60947-7-x Rated impulse withstand voltage Conductor size Factory wiring max. (UR Conductor size Field wiring max. (UR) Current size C (UR) | 76 A 0.56 mΩ 8 kV c) 6 AWG 6 AWG 60 A |
| Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x Pollution severity UL rating data Certificate No. (UR) Conductor size Factory wiring min. (UR) Conductor size Field wiring min. (UR) Voltage size C (UR) | 57 A IEC 60947-7-1 1.82 W 3 E60693 14 AWG 14 AWG | Current at maximum wires Volume resistance according to IEC 60947-7-x Rated impulse withstand voltage Conductor size Factory wiring max. (UR Conductor size Field wiring max. (UR) | 76 A 0.56 mΩ 8 kV) 6 AWG 6 AWG |
| Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x Pollution severity UL rating data Certificate No. (UR) Conductor size Factory wiring min. (UR) Voltage size C (UR) Classifications | 57 A IEC 60947-7-1 1.82 W 3 E60693 14 AWG 14 AWG 600 V | Current at maximum wires Volume resistance according to IEC 60947-7-x Rated impulse withstand voltage Conductor size Factory wiring max. (UR Conductor size Field wiring max. (UR) Current size C (UR) | 76 A 0.56 mΩ 8 kV c) 6 AWG 6 AWG 60 A |



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Approvals

Approvals





ROHS Conform

Downloads

| Approval/Certificate/Document of | Attestation Of Conformity |
|----------------------------------|---|
| Conformity | <u>DE_PT1341_20160414_013_ISSUE01.pdf</u> |
| Engineering Data | EPLAN, WSCAD |
| User Documentation | StorageConditionsTerminalBlocks |

Safety note

Safety notice Safety Information



SAK 10 KRG

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

DEK 5/6.5 MC NE WS Order No. 1609840000 GTIN (EAN) 4008190203429

900 pc(s).

Dekafix, Terminal marker, 5 x 6.5 mm, Pitch in mm (P): 6.50

Weidmueller, white

End bracket

Qty.



Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

| Туре | EWK 1 | Version |
|------------|---------------|--------------------------|
| Order No. | 0206160000 | Accessories, End bracket |
| GTIN (EAN) | 4008190080020 | |
| Qty. | 50 pc(s). | |
| Туре | EWK 2 | Version |
| Order No. | 0199360000 | Accessories, End bracket |
| GTIN (EAN) | 4008190023546 | |
| Qty. | 50 pc(s). | |
| Туре | EW 35 | Version |
| Order No. | 0383560000 | Accessories, End bracket |
| GTIN (EAN) | 4008190181314 | |
| Qty. | 50 pc(s). | |



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

| Туре | EWK 1 ALT | Version |
|------------|-------------------|--------------------------|
| Order No. | <u>0495160000</u> | Accessories, End bracket |
| GTIN (EAN) | 4008190160777 | |
| Qty. | 50 pc(s). | |
| Туре | WEW 32/1 | V: |
| турс | VVEVV 32/ I | Version |
| Order No. | 1067600000 | W-Series, End bracket |
| | , | |

Test plug



Current and voltage transformer wiring

Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.

General ordering data

| Туре | PS 4 F.STB 4 | Version |
|------------|---------------|------------------------|
| Order No. | 0299600000 | Accessories, Test plug |
| GTIN (EAN) | 4008190074043 | |
| Qty. | 20 pc(s). | |

Partition plates



Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

| Туре | WTW EN | Version |
|------------|---------------|----------------------------|
| Order No. | 1058800000 | W-Series, Seperation plate |
| GTIN (EAN) | 4008190140175 | |
| Qty. | 20 pc(s). | |



Weidmüller Interface GmbH & Co. KG

SAK Series

SAK 10 KRG

D-32758 Detmold


Klingenbergstraße 26

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

DEK 5/5 MC NE WS Order No. 1609801044 4008190397111 GTIN (EAN) Qty. 1,000 pc(s).

Version

Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00

Weidmueller, white

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

DEK 5/6 MC SDR Туре Order No. 1609830000 GTIN (EAN) 4008190456603 200 pc(s). Qty.

Version

Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00

Weidmueller, To customer specification



SAK 10 KRG

Accessories

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

DEK 5/8 PLUS MC NE WS

1046350000

4032248782055

Qty. 800 pc(s).

Order No.

GTIN (EAN)

Version

Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00

Weidmueller, white

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

DEK 5/8 MC SDR Туре

Order No. 1856750000 GTIN (EAN) 4032248400867

160 pc(s).

Version

Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00

Weidmueller, To customer specification



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Type DEK 5/8 PLUS MC SDR
Order No. 1046370000
GTIN (EAN) 4032248782079
Oty. 160 pc(s).

Version

Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00

Weidmueller, To customer specification

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type DEK 5/6 MC NE WS
Order No. 1609820000
GTIN (EAN) 4008190203436
Oty. 1,000 pc(s).

Version

Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00

Weidmueller, white

Q/SAK



Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

| Туре | Q 3 SAK10 | Version |
|-------------------|-------------------------|---|
| Order No. | 0457200000 | SAK Series, Cross-connector, for cross-connection link, Number of |
| GTIN (EAN) | 4008190135379 | poles: 3 |
| Qty. | 50 pc(s). | |
| | | |
| Туре | Q 2 SAK10 | Version |
| Type Order No. | Q 2 SAK10 0457100000 | Version SAK Series, Cross-connector, for cross-connection link, Number of |
| | | |



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

| Туре | Q 4 SAK10 | Version |
|------------|---------------|---|
| Order No. | 0457300000 | SAK Series, Cross-connector, for cross-connection link, Number of |
| GTIN (EAN) | 4008190129750 | poles: 4 |
| Qty. | 50 pc(s). | |
| Туре | Q 10 SAK10 | Version |
| Order No. | 0457400000 | SAK Series, Cross-connector, for cross-connection link, Number of |
| GTIN (EAN) | 4008190016166 | poles: 10 |
| Qty. | 20 pc(s). | |

Small partition



Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

| Туре | TSCH 1 | Version |
|------------|-------------------|--|
| Order No. | <u>0319160000</u> | SAK Series, Small partition, beige, 2 mm |
| GTIN (EAN) | 4008190097219 | |
| Qty. | 100 pc(s). | |

End plates



Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

| Туре | AP SAK4-10 I | Version |
|------------|-------------------|--|
| | | |
| Order No. | <u>0117910000</u> | SAK Series, End plate, 1.5 mm, Light Grey, Direct mounting |
| GTIN (EAN) | 4008190183707 | |
| Qty. | 20 pc(s). | |
| Туре | AP SAK4-10 | Version |
| Order No. | 0117960000 | SAK Series, End plate, 1.5 mm, beige, Direct mounting |
| GTIN (EAN) | 4008190081485 | |
| Qty. | 20 pc(s). | |
| Туре | AP SAK4-10 KRG/BL | Version |
| Order No. | 0117970000 | SAK Series, End plate, 1.5 mm, blue, Direct mounting |
| GTIN (EAN) | 4008190049607 | |
| Qty. | 20 pc(s). | |

Creation date April 30, 2020 6:58:23 PM CEST



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

| Туре | AP SAK4-10 RT | Version |
|--------------------|----------------------------|--|
| Order No. | 0117900000 | SAK Series, End plate, 1.5 mm, red, Direct mounting |
| GTIN (EAN) | 4008190125059 | |
| Qty. | 20 pc(s). | |
| Туре | AP SAK4-10 DB | Version |
| Order No. | <u>0105100000</u> | SAK Series, End plate, 1.5 mm, dark beige, Direct mounting |
| GTIN (EAN) | 4008190394875 | |
| Qty. | 20 pc(s). | |
| Туре | AP SAK4-10 KRG | Version |
| Order No. | 0117920000 | SAK Series, End plate, 1.5 mm, dark beige, yellow, Direct mounting |
| | | |
| GTIN (EAN) | 4008190135904 | |
| GTIN (EAN) Qty. | 4008190135904 20 pc(s). | |
| , , | | Version |
| Qty. | 20 pc(s). | Version SAK Series, End plate, 1.5 mm, blue, Direct mounting |
| Qty. | 20 pc(s). AP SAK4-10 BL | |

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

| Туре | DEK 5/5 MC SDR | Version |
|------------|-------------------|---|
| Order No. | <u>1609810000</u> | Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00 |
| GTIN (EAN) | 4008190456597 | Weidmueller, To customer specification |
| Qty. | 200 pc(s). | |



SAK 10 KRG

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Covers



Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

Туре AD 4 SAK10 Order No. 0178600000 GTIN (EAN) 4008190068288 50 pc(s). Qty.

SAK Series, cover plate, yellow, 25 mm

Partition plates



Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

| Туре | TW SAK4-10 EP/SW | Version |
|------------|-----------------------|---|
| Order No. | 0130100000 | SAK Series, Seperation plate, 2.53 mm, black, Direct mounting |
| GTIN (EAN) | 4008190407599 | |
| Qty. | 20 pc(s). | |
| Туре | TW SAK4-10 HP/DBR/0.5 | Version |
| Order No. | 0197100000 | SAK Series, Seperation plate, 0.5 mm, brown, dark beige, Direct |
| GTIN (EAN) | 4008190146627 | mounting |
| Qty. | 20 pc(s). | |
| Туре | TW 4 SAK4-10 | Version |
| Order No. | 0130160000 | SAK Series, Seperation plate, 1.5 mm, beige |
| GTIN (EAN) | 4008190096335 | |
| Qty. | 20 pc(s). | |
| Туре | TW SAK4-10 KRG/BL | Version |
| Order No. | 0130170000 | SAK Series, Seperation plate, 2.25 mm, blue, Direct mounting |
| GTIN (EAN) | 4008190063757 | |
| Qty. | 20 pc(s). | |
| Туре | TW SAK4-10 KRG | Version |
| Order No. | 0130120000 | SAK Series, Seperation plate, 2.25 mm, dark beige, yellow, Direct |
| GTIN (EAN) | 4008190139117 | mounting |
| | | |



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Type TW 4 SAK4-10 BL
Order No. 0130180000
GTIN (EAN) 4008190114138
Qty. 20 pc(s).

Version

SAK Series, Seperation plate, 1.5 mm, blue

Custom printing



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type DEK 5/6.5 MC SDR
Order No. 1609850000
GTIN (EAN) 4008190456610
Oty. 180 pc(s).

Version

Dekafix, Terminal marker, 5 x 6.5 mm, Pitch in mm (P): 6.50

Weidmueller, To customer specification

Slotted screwdriver

Slotted screwdriver with rounded blade SD DIN 5265, ISO 2380/2, output to DIN 5264, ISO 2380/1. ChromTop tip, SoftFinish grip



General ordering data

Type SDS 1.0X5.5X150
Order No. 9008350000
GTIN (EAN) 4032248056316
Oty. 1 pc(s).

Version

Screwdriver, Blade width (B): 5.5 mm, Blade length: 150 mm, Blade

thickness (A): 1 mm



SAK 10 KRG

Accessories

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Screwing



Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

Type BFSC M3X25

Order No. 0292500000

GTIN (EAN) 4008190177027

Qty. 100 pc(s).

Version

Accessories, Mounting screw, for cross-connection link

DEK 5/8



WS/DFK

MultiMark DEK/WS connector markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

General ordering data

 Type
 DEK 5/8 MM WS
 Version

 Order No.
 2007130000
 Dekafix, Terminal marker, 5 x 8 mm, Weidmueller, white

 GTIN (EAN)
 4050118392012

 Qty.
 500 pc(s).



SAK 10 KRG

Accessories

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Connection sleeves



Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

VH 12/4.9/3.3 024900

General ordering data

Туре VH 19/5/3.5 SAK4-16 Order No. 0285100000 SAK Series, Connecting sleeve, for cross-connection link, Number of GTIN (EAN) 4008190189297

Qty. 50 pc(s).

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Qty.

Туре DEK 5/8 MC NE WS Version Order No. 1856740000 Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00

GTIN (EAN) 4032248400850 Weidmueller, white 800 pc(s).