

CableLine CLI C 3-6 GE/SW T MP

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com



Similar to illustration

CLI C conductor markers are mounted on unconnected conductors. Four different sizes are available for labelling conductor cross-sections from 0.5 mm² to max. 70 mm². The markers are already printed and ready for use. Individual labelling is possible by combining the individual markers.

- Closed markers, reliable and for mounting on unconnected cables
- A special flexible bellow profile ensures a wide application range
- Fast and easy to fit – with minimal effort
- Corresponding accessories make labelling easy
- Permanent, high-quality labelling
- High contrast for optimum legibility

General ordering data

| | |
|------------|--|
| Type | CLI C 3-6 GE/SW T MP |
| Order No. | 0253411676 |
| Version | CableLine, Conductor and cable markers, 8 - 16 mm, 6 x 11 mm, yellow |
| GTIN (EAN) | 4008 190120832 |
| Qty. | 20 pc(s). |

Creation date April 30, 2020 9:37:59 PM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

CableLine
CLI C 3-6 GE/SW T MP

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

| | | | |
|------------|--------|-----------------|------------|
| Width | 11 mm | Width (inches) | 0.433 inch |
| Height | 6 mm | Height (inches) | 0.236 inch |
| Depth | 17 mm | Depth (inches) | 0.669 inch |
| Net weight | 0.75 g | | |

General data

| | | | |
|-----------------------------|----------------------------|--|------------|
| Colour | yellow | Colour of printing | black |
| Halogen | Yes | Insulation cross-section, max. | 16 mm |
| Material | PVC, soft, without Cadmium | Material colour according to resistance code | 4 |
| Operating temperature range | -30...80 °C | Orientation of print | horizontal |
| Printed characters | Upper-case letters | Printing | T |
| Printing method | hot-embossing | Type of printing | Standard |
| UL 94 flammability rating | V-0 | Version | MultiPack |
| Width | 11 mm | | |

Conductor and cable markers

| | | | |
|-------------------------------|--------------------|-------------------------------|--------------------|
| Conductor O.D. | 8 - 16 mm | Conductor O.D., max. | 16 mm |
| Conductor O.D., min. | 8 mm | Conductor cross-section, max. | 70 mm ² |
| Conductor cross-section, min. | 16 mm ² | Halogen | Yes |

Classifications

| | | | |
|-------------|-------------|------------|-------------|
| ETIM 6.0 | EC001530 | ETIM 7.0 | EC001530 |
| eClass 9.0 | 27-40-04-01 | eClass 9.1 | 27-40-04-01 |
| eClass 10.0 | 27-40-04-01 | UNSPSC | 44-12-17-08 |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|-----------------------------|--|
| Engineering Data | EPLAN, WSCAD |
| Product Change Notification | PCN CableLine_DE PCN CableLine_EN |

Data sheet

**CableLine
CLI C 3-6 GE/SW T MP**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings



Similar to illustration