

#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

## **Product image**







## Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

Delivery status	This article will no longer be available in the future.
Available until	2020-12-31
Туре	SAK 16 KRG
Order No.	0271020000
GTIN (EAN)	4008190120856
Qty.	50 pc(s).
Alternative product	<u>1020400000</u>



### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

## **Technical data**

## **Dimensions and weights**

Width	12 mm	Width (inches)	0.472 inch
Height	50 mm	Height (inches)	1.969 inch
Depth	57.5 mm	Depth (inches)	2.264 inch
Net weight	36.38 g		

## **Temperatures**

Operating temperature range	For operating temperature range see EC Design Test Certificate / IEC Ex-	Storage temperature, max.	
	Certificate of Conformity		40 °C
Storage temperature, min.	10 °C	Storage temperature	10 °C40 °C
Continuous operating temp., min.	-60 °C	Continuous operating temp., max.	130 °C

#### **Material data**

Material	KrG	Colour	medium yellow
UL 94 flammability rating	V-0, 5VA		

## **Rating data IECEx/ATEX**

Certificate No. (ATEX)	KEMA97ATEX1798U	Certificate No. (IECEX)	IECEXKEM06.0014U
Max. voltage (ATEX)	690 V	Current (ATEX)	66 A
Wire cross section max. (ATEX)	16 mm²	Max. voltage (IECEX)	690 V
Current (IECEX)	66 A	Wire cross section max. (IECEX)	16 mm²
Operating temperature range	For operating temperature range see EC Design Test Certificate / IEC Ex- Certificate of Conformity	Marking EN 60079-7	Ex eb II C Gb
Ex 2014/34/EU label	II 2 G D		

## **System specifications**

Version	Screw connection, for screwable cross- connection, One end	End cover plate required	
	without connector		Yes
Number of potentials	1	Number of levels	1
Number of clamping points per level	2	Number of potentials per tier	1
Levels cross-connected internally	No	PE connection	No
Rail	TS 32	N-function	No
PE function	No	PEN function	No

#### Additional technical data

Explosion-tested version	No	Number of similar terminals	1
Open sides	right	Type of mounting	Snap-on

## **CSA** rating data

Certificate No. (CSA)	154685-1501714	Current size C (CSA)	87 A
Voltage size C (CSA)	600 V	Wire cross section max. (CSA)	4 AWG
Wire cross section min. (CSA)	14 AWG		



### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083

www.weidmueller.com

## **Technical data**

## **Conductors for clamping (rated connection)**

Blade size	1.0 x 5.5 mm	Clamping range, max.	16 mm²
Clamping range, min.	2.5 mm <sup>2</sup>	Clamping range, max.  Clamping screw	M 4
Connection cross-section, stranded,	2.5 111111-	Connection cross-section, stranded, min	
max.	16 mm <sup>2</sup>	Connection cross-section, stranded, min	ı. 4 mm²
Connection direction	on side	Gauge to IEC 60947-1	B6
Number of connections	2	Stripping length	15 mm
	2.4 Nm		2 Nm
Tightening torque, max. Twin wire-end ferrules, max.	10 mm <sup>2</sup>	Tightening torque, min. Twin wire-end ferrules, min.	2 INTTI 1.5 mm <sup>2</sup>
<u> </u>	10 mm²	Wire connection cross section AWG.	1.5 mm²
Type of connection	Screw connection	max.	AWG 6
Wire connection cross section AWG,	OCIOW COMMODITION	Wire connection cross section, finely	AVVG
min.	AWG 12	stranded, max.	16 mm²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max.	16 mm²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min.	4 mm²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max.	16 mm²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min.	16 mm²
Wire connection cross-section, finely		Wire connection cross-section, solid	
stranded, min.	4 mm <sup>2</sup>	core, max.	10 mm <sup>2</sup>
Wire connection cross-section, solid core, min.	2.5 mm <sup>2</sup>		
<b>.</b>			
Rating data			
	16 mm <sup>2</sup>	Rated voltage	800 V
Rated cross-section Rated current	16 mm <sup>2</sup>	Rated voltage Current at maximum wires	800 V 76 A
Rated cross-section	76 A	Current at maximum wires  Volume resistance according to IEC	76 A
Rated cross-section Rated current Standards		Current at maximum wires  Volume resistance according to IEC 60947-7-x	
Rated cross-section Rated current Standards Power loss in accordance with IEC	76 A IEC 60947-7-1	Current at maximum wires  Volume resistance according to IEC	76 A 0.42 mΩ
Rated cross-section Rated current Standards	76 A	Current at maximum wires  Volume resistance according to IEC 60947-7-x	76 A
Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x	76 A IEC 60947-7-1 2.43 W	Current at maximum wires  Volume resistance according to IEC 60947-7-x	76 A 0.42 mΩ
Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x Pollution severity  UL rating data	76 A IEC 60947-7-1 2.43 W 3	Current at maximum wires  Volume resistance according to IEC 60947-7-x  Rated impulse withstand voltage	76 A 0.42 mΩ 8 kV
Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x Pollution severity  UL rating data  Certificate No. (UR)	76 A IEC 60947-7-1 2.43 W 3	Current at maximum wires  Volume resistance according to IEC 60947-7-x  Rated impulse withstand voltage  Conductor size Factory wiring max. (UR)	76 A 0.42 mΩ 8 kV
Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x Pollution severity  UL rating data  Certificate No. (UR) Conductor size Factory wiring min. (UR)	76 A IEC 60947-7-1 2.43 W 3 E60693 12 AWG	Current at maximum wires  Volume resistance according to IEC 60947-7-x  Rated impulse withstand voltage  Conductor size Factory wiring max. (UR)	76 A 0.42 mΩ 8 kV 4 AWG 4 AWG
Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x Pollution severity  UL rating data  Certificate No. (UR) Conductor size Factory wiring min. (UR) Conductor size Field wiring min. (UR)	76 A IEC 60947-7-1 2.43 W 3 E60693 12 AWG 12 AWG	Current at maximum wires  Volume resistance according to IEC 60947-7-x  Rated impulse withstand voltage  Conductor size Factory wiring max. (UR)	76 A 0.42 mΩ 8 kV
Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x Pollution severity	76 A IEC 60947-7-1 2.43 W 3 E60693 12 AWG	Current at maximum wires  Volume resistance according to IEC 60947-7-x  Rated impulse withstand voltage  Conductor size Factory wiring max. (UR)	76 A 0.42 mΩ 8 kV 4 AWG 4 AWG
Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x Pollution severity  UL rating data  Certificate No. (UR) Conductor size Factory wiring min. (UR) Conductor size Field wiring min. (UR)	76 A IEC 60947-7-1 2.43 W 3 E60693 12 AWG 12 AWG	Current at maximum wires  Volume resistance according to IEC 60947-7-x  Rated impulse withstand voltage  Conductor size Factory wiring max. (UR)	76 A 0.42 mΩ 8 kV 4 AWG 4 AWG
Rated cross-section Rated current Standards Power loss in accordance with IEC 60947-7-x Pollution severity  UL rating data  Certificate No. (UR) Conductor size Factory wiring min. (UR) Conductor size Field wiring min. (UR) Voltage size C (UR)	76 A IEC 60947-7-1 2.43 W 3 E60693 12 AWG 12 AWG	Current at maximum wires  Volume resistance according to IEC 60947-7-x  Rated impulse withstand voltage  Conductor size Factory wiring max. (UR)	76 A 0.42 mΩ 8 kV 4 AWG 4 AWG
Rated cross-section Rated current Standards  Power loss in accordance with IEC 60947-7-x Pollution severity  UL rating data  Certificate No. (UR) Conductor size Factory wiring min. (UR) Conductor size Field wiring min. (UR) Voltage size C (UR)  Classifications	76 A IEC 60947-7-1 2.43 W 3 E60693 12 AWG 12 AWG 600 V	Current at maximum wires  Volume resistance according to IEC 60947-7-x  Rated impulse withstand voltage  Conductor size Factory wiring max. (UR)  Current size C (UR)	76 A 0.42 mΩ 8 kV  9 4 AWG 4 AWG 80 A



### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

## **Technical data**

## **Approvals**

Approvals





ROHS Conform

#### **Downloads**

Approval/Certificate/Document of	Attestation Of Conformity
Conformity	DE_PT1341_20160414_021_ISSUE01.pdf
Engineering Data	EPLAN, WSCAD
Engineering Data	02631_SAK_16_KRG_DXF.dxf
User Documentation	<u>StorageConditionsTerminalBlocks</u>

## Safety note

Safety notice Safety Information



# Accessories

#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

#### **Test plug**



## **Current and voltage transformer wiring**

Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.


#### **General ordering data**

Type PS 4 F.STB 4
Order No. 0299600000
GTIN (EAN) 4008190074043
Oty. 20 pc(s).

Version

Accessories, Test plug

#### **Blank**



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

#### **General ordering data**

Type DEK 5/5 MC NE WS

Order No. 1609801044

GTIN (EAN) 4008190397111

Oty. 1,000 pc(s).

Version

Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00

Weidmueller, white



Accessories

#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

### **Custom printing**



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

### **General ordering data**

DEK 5/6 MC SDR Order No. 1609830000 4008190456603 GTIN (EAN) Qty. 200 pc(s).

Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00

Weidmueller, To customer specification

## Plus



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

#### General ordering data

DEK 5/8 PLUS MC NE WS Туре Order No. 1046350000

Version

Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00

GTIN (EAN) 4032248782055

800 pc(s). Qty

Weidmueller, white



## Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

## **Accessories**

**Custom printing** 



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number

markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

sequences and covers a wide range of ready-printed

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Туре	DEK 5/8 MC SDR	Version
Order No.	<u>1856750000</u>	Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00
GTIN (EAN)	4032248400867	Weidmueller, To customer specification
Qty.	160 pc(s).	
Туре	DEK 5/8 PLUS MC SDR	Version
Order No.	1046370000	Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00
	1040370000	Dekalix, Terminal marker, 5 x 6 mm, Filch in mm (F). 6.00
GTIN (EAN)	4032248782079	Weidmueller, To customer specification



## **SAK Series**

## **SAK 16 KRG**

## Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

## Accessories

## **Blank**



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

### **General ordering data**

DEK 5/6 MC NE WS Order No. 1609820000 GTIN (EAN) 4008190203436 1,000 pc(s). Qty.

Version

Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00

Weidmueller, white

## Q/SAK



## Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

Туре	Q 3 SAK16	Version
Order No.	0457600000	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190022280	poles: 3
Qty.	50 pc(s).	
Туре	Q 4 SAK16	Version
Order No.	0457700000	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190070823	poles: 4
Qty.	50 pc(s).	
Туре	Q 2 SAK16	Version
Order No.	0457500000	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190055349	poles: 2
Qty.	50 pc(s).	



#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

## **Accessories**

Туре	Q 10 SAK16	Version
Order No.	0457800000	SAK Series, 0
GTIN (EAN)	4008190082512	poles: 10
Qty.	20 pc(s).	

SAK Series, Cross-connector, for cross-connection link, Number of

## **End plates**



## Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

Туре	AP SAK16	Version
Order No.	<u>0271160000</u>	SAK Series, End plate, 1.5 mm, beige, Direct mounting
GTIN (EAN)	4008190120429	
Qty.	20 pc(s).	
Туре	AP SAK16 BL	Version
Order No.	<u>0271180000</u>	SAK Series, End plate, 1.5 mm, blue, Direct mounting
GTIN (EAN)	4008190169800	
Qty.	20 pc(s).	
Туре	AP SAK16 KRG	Version
Order No.	0271120000	SAK Series, End plate, 3 mm, dark beige, yellow, Direct mounting
GTIN (EAN)	4008190062606	
Qty.	20 pc(s).	
Туре	AP SAK35/TW SAK16 BL	Version
Order No.	0303680000	SAK Series, End plate, 1.5 mm, blue
GTIN (EAN)	4008190025199	
Qty.	10 pc(s).	
Туре	AP SAK35/TW SAK16	Version
Order No.	0303660000	SAK Series, End plate, 1.5 mm, beige
GTIN (EAN)	4008190110765	
Qty.	10 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

## **Accessories**

**QL / SAK 16** 



## Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

Туре	QL 4 SAK16	Version
Order No.	0470900000	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190112257	poles: 4
Qty.	50 pc(s).	
Туре	QL 3 SAK16	Version
Order No.	0470800000	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190011574	poles: 3
Qty.	50 pc(s).	
Туре	QL 2 SAK16	Version
Order No.	0470700000	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190182618	poles: 2
Qty.	50 pc(s).	
Туре	QL 10 SAK16	Version
Order No.	0471000000	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190150761	poles: 10



#### Weidmüller Interface GmbH & Co. KG Klingenbergstraße 26

D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

## **Accessories**

**Custom printing** 



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

## **General ordering data**

Type DEK 5/5 MC SDR
Order No. 1609810000
GTIN (EAN) 4008190456597
Qty. 200 pc(s).

Version

Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00

Weidmueller, To customer specification

## Covers



## Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

#### General ordering data

Type AD 4 SAK16
Order No. 0518200000
GTIN (EAN) 4008190122416
Oty. 50 pc(s).

Version

SAK Series, cover plate, yellow, 47.6 mm



## SAK 16 KRG

Accessories

#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

## Partition plates



## Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

#### **General ordering data**

Type TW SAK16 KRG
Order No. 0281120000
GTIN (EAN) 4008190072360
Oty. 20 pc(s).

Version

SAK Series, Seperation plate, 3 mm, dark beige, yellow, Used between

terminals, Direct mounting

## Screwing



## Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

#### **General ordering data**

Type BFSC M3X25
Order No. 0292500000
GTIN (EAN) 4008190177027
Oty. 100 pc(s).

Version

Accessories, Mounting screw, for cross-connection link



## **SAK Series**

## **SAK 16 KRG**

#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

## Accessories

#### **DEK 5/8**



### WS/ DEK

MultiMark DEK/WS connector markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

#### Your benefits with MultiMark

- · Firm hold and durable printing
- · Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

## **General ordering data**

Туре DEK 5/8 MM WS Version Order No. 2007130000 Dekafix, Terminal marker, 5 x 8 mm, Weidmueller, white GTIN (EAN) 4050118392012 500 pc(s). Qty.

## **Connection sleeves**



## Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

### VH 12/4.9/3.3 024900

#### **General ordering data**

Туре VH 19/5/3.5 SAK4-16 Order No. 0285100000 SAK Series, Connecting sleeve, for cross-connection link, Number of GTIN (EAN) 4008190189297 poles: 1 50 pc(s). Qty.



### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

## **Accessories**





The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

## **General ordering data**

ype DEK 5/8 MC NE WS Version

Order No. <u>1856740000</u> Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00

GTIN (EAN) 4032248400850 Weidmueller, white Oty. 800 pc(s).

Locking tabs



## Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

#### General ordering data

 Type
 VL 2 SAK16/SAKA
 Version

 Order No.
 0135800000
 SAK Series, Cross-connection lug, for cross-connection link, Number

 GTIN (EAN)
 4008190132088
 of poles: 2

 Qty.
 50 pc(s).