

#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

#### **Product image**







#### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

Туре	SAK 16
Order No.	<u>0271060000</u>
Version	SAK Series, Feed-through terminal, Rated cross-
	section: 16 mm <sup>2</sup> , Screw connection, beige
GTIN (EAN)	4008190078324
Qty.	50 pc(s).



#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

# **Technical data**

#### **Dimensions and weights**

Width	12 mm	Width (inches)	0.472 inch
Height	50 mm	Height (inches)	1.969 inch
Depth	57.5 mm	Depth (inches)	2.264 inch
Net weight	25.64 g		

#### **Temperatures**

Operating temperature range	For operating temperature range see EC Design Test Certificate / IEC Ex-	Storage temperature, max.	
	Certificate of Conformity		40 °C
Storage temperature, min.	10 °C	Storage temperature	10 °C40 °C
Continuous operating temp., min.	-50 °C	Continuous operating temp., max.	100 °C

#### **Material data**

Material	PA 66	Colour	beige / yellow
UL 94 flammability rating	V-2		

#### **Rating data IECEx/ATEX**

Certificate No. (ATEX)	KEMA97ATEX1798U	Certificate No. (IECEX)	IECEXKEM06.0014U
Max. voltage (ATEX)	690 V	Current (ATEX)	66 A
Wire cross section max. (ATEX)	16 mm²	Max. voltage (IECEX)	690 V
Current (IECEX)	66 A	Wire cross section max. (IECEX)	16 mm²
Operating temperature range	For operating temperature range see EC Design Test Certificate / IEC Ex- Certificate of Conformity	Marking EN 60079-7	Ex eb II C Gb
Ex 2014/34/EU label	II 2 G D		

#### **System specifications**

Version	Screw connection, for screwable cross- connection, One end	End cover plate required	
	without connector		Yes
Number of potentials	1	Number of levels	1
Number of clamping points per level	2	Number of potentials per tier	1
Levels cross-connected internally	No	PE connection	No
Rail	TS 32	N-function	No
PE function	No	PEN function	No

#### **Additional technical data**

Open sides right Type of mounting Snap-on	Explosion-tested version	No	Number of similar terminals	1
	Open sides	right	Type of mounting	Snap-on

#### **CSA** rating data

Certificate No. (CSA)	154685-1501714	Current size C (CSA)	87 A
Voltage size C (CSA)	600 V	Wire cross section max. (CSA)	4 AWG
Wire cross section min. (CSA)	14 AWG	_	



#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

# **Technical data**

#### **Conductors for clamping (additional connection)**

Conductor cross-section, flexible plus plastic collar DIN 46228/1, further connection, max.

16 mm<sup>2</sup>

#### **Conductors for clamping (rated connection)**

Blade size	1.0 x 5.5 mm	Clamping range, max.	16 mm²
Clamping range, min.	2.5 mm <sup>2</sup>	Clamping screw	M 4
Connection cross-section, stranded,		Connection cross-section, stranded, m	in.
max.	16 mm²		4 mm <sup>2</sup>
Connection direction	on side	Gauge to IEC 60947-1	B6
Number of connections	2	Stripping length	15 mm
Tightening torque, max.	2.64 Nm	Tightening torque, min.	2 Nm
Twin wire-end ferrules, max.	10 mm <sup>2</sup>	Twin wire-end ferrules, min.	1.5 mm <sup>2</sup>
Type of connection		Wire connection cross section AWG,	
	Screw connection	max.	AWG 6
Wire connection cross section AWG,		Wire connection cross section, finely	
min.	AWG 12	stranded, max.	16 mm <sup>2</sup>
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max.	16 mm²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min.	4 mm²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max.	16 mm²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min.	16 mm²
Wire connection cross-section, finely stranded, min.	4 mm²	Wire connection cross-section, solid core, max.	10 mm²
Wire connection cross-section, solid core, min.	2.5 mm <sup>2</sup>		

#### **Rating data**

Rated cross-section	16 mm²	Rated voltage	1,000 V
Rated current	76 A	Current at maximum wires	76 A
Standards		Volume resistance according to IE	EC
	IEC 60947-7-1	60947-7-x	$0.42~\text{m}\Omega$
Power loss in accordance with	h IEC	Rated impulse withstand voltage	
60947-7-x	2.43 W	•	8 kV
Pollution severity	3		

#### **UL** rating data

Certificate No. (UR)	E60693	Conductor size Factory wiring max. (UR)	4 AWG
Conductor size Factory wiring min. (UR)	12 AWG	Conductor size Field wiring max. (UR)	4 AWG
Conductor size Field wiring min. (UR)	12 AWG	Current size C (UR)	80 A
Voltage size C (UR)	600 V		

#### Classifications

ETIM 6.0	EC000897	ETIM 7.0	EC000897
eClass 9.0	27-14-11-20	eClass 9.1	27-14-11-20
eClass 10.0	27-14-11-20	UNSPSC	30-21-18-11



#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

# **Technical data**

#### **Approvals**

Approvals











ROHS Conform

#### **Downloads**

Approval/Certificate/Document of Conformity

ATEX Certificate
IECEx Certificate
CB Certificate
CB Test Certificate
DE PT1301 20160414 019 ISSUE01.pdf

Engineering Data

EPLAN, WSCAD

Engineering Data

O4038 SAK 16 DXF.dxf
STEP

User Documentation

Cross Connection Guide
StorageConditionsTerminalBlocks

#### Safety note

Safety notice Safety Information



# Accessories

#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

#### **Test plug**



#### **Current and voltage transformer wiring**

Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.


#### General ordering data

Type PS 4 F.STB 4
Order No. 0299600000
GTIN (EAN) 4008190074043
Oty. 20 pc(s).

Version

Accessories, Test plug

#### **Blank**



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

#### General ordering data

Type DEK 5/5 MC NE WS
Order No. 1609801044
GTIN (EAN) 4008190397111
Oty. 1,000 pc(s).

Version

Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00

Weidmueller, white



# **SAK 16**

**Custom printing** 

#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

#### **Accessories**



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number

markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

sequences and covers a wide range of ready-printed

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

#### General ordering data

Type DEK 5/6 MC SDR

Order No. 1609830000

GTIN (EAN) 4008190456603

Qty. 200 pc(s).

Version

Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00

Weidmueller, To customer specification

#### Plus



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

#### General ordering data

Type DEK 5/8 PLUS MC NE WS

Version

Order No. <u>1046350000</u> GTIN (EAN) 4032248782055 Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00

Weidmueller, white

Qty. 800 pc(s).



**Custom printing** 

#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

### **Accessories**



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number

sequences and covers a wide range of ready-printed

markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Туре	DEK 5/8 MC SDR	Version
Order No.	<u>1856750000</u>	Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00
GTIN (EAN)	4032248400867	Weidmueller, To customer specification
Qty.	160 pc(s).	
Туре	DEK 5/8 PLUS MC SDR	Version
Order No.	1046370000	Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00
OTINI (FARI)		
GTIN (EAN)	4032248782079	Weidmueller, To customer specification



#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

## **Accessories**

#### Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

#### **General ordering data**

Type DEK 5/6 MC NE WS
Order No. 1609820000
GTIN (EAN) 4008190203436
Qty. 1,000 pc(s).

Version

Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00

Weidmueller, white

#### Q/SAK



#### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

Туре	Q 3 SAK16	Version
Order No.	0457600000	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190022280	poles: 3
Qty.	50 pc(s).	
Туре	Q 4 SAK16	Version
Order No.	0457700000	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190070823	poles: 4
Qty.	50 pc(s).	
Туре	Q 2 SAK16	Version
Order No.	0457500000	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190055349	poles: 2
Qty.	50 pc(s).	



#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

### **Accessories**

Туре	Q 10 SAK16
Order No.	0457800000
GTIN (EAN)	4008190082512
Qty.	20 pc(s).

Version
SAK Series, Cross-connector, for cross-connection link, Number of

poles: 10

#### **Small partition**



#### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

#### **General ordering data**

Туре	ISCH 1
Order No.	0319160000
GTIN (EAN)	4008190097219
Qty.	100 pc(s).

Version

SAK Series, Small partition, beige, 2 mm

#### **End plates**



#### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

Туре	AP SAK16	Version
Order No.	0271160000	SAK Series, End plate, 1.5 mm, beige, Direct mounting
GTIN (EAN)	4008190120429	
Qty.	20 pc(s).	
Туре	AP SAK16 BL	Version
Order No.	0271180000	SAK Series, End plate, 1.5 mm, blue, Direct mounting
GTIN (EAN)	4008190169800	
Qty.	20 pc(s).	
Туре	AP SAK35/TW SAK16 BL	Version
Order No.	0303680000	SAK Series, End plate, 1.5 mm, blue
GTIN (EAN)	4008190025199	
Qty.	10 pc(s).	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

### **Accessories**

Туре	AP SAK35/TW SAK16	Version
Order No.	0303660000	SAK Series, End plate, 1.5 mm, beige
GTIN (EAN)	4008190110765	
Qty.	10 pc(s).	

#### **QL / SAK 16**



## Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

Туре	QL 4 SAK16	Version
Order No.	0470900000	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190112257	poles: 4
Qty.	50 pc(s).	
Туре	QL 3 SAK16	Version
Order No.	0470800000	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190011574	poles: 3
Qty.	50 pc(s).	
Туре	QL 2 SAK16	Version
Order No.	0470700000	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190182618	poles: 2
Qty.	50 pc(s).	
Туре	QL 10 SAK16	Version
Order No.	0471000000	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190150761	poles: 10
Qty.	20 pc(s).	



# Accessories

#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

#### **Custom printing**



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

#### **General ordering data**

Type DEK 5/5 MC SDR
Order No. 1609810000
GTIN (EAN) 4008190456597
Qty. 200 pc(s).

Version

Dekafix, Terminal marker, 5 x 5 mm, Pitch in mm (P): 5.00

Weidmueller, To customer specification

#### Covers



#### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

#### General ordering data

Type AD 3 SAK16
Order No. 0297800000
GTIN (EAN) 4008190080884
Oty. 50 pc(s).

Version

SAK Series, cover plate, yellow, 36 mm



# Accessories

#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

#### **Screwing**



#### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

#### General ordering data

Type BFSC M3X25

Order No. 0292500000

GTIN (EAN) 4008190177027

Qty. 100 pc(s).

Version

Accessories, Mounting screw, for cross-connection link

#### **DEK 5/8**



#### WS/DFK

MultiMark DEK/WS connector markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

#### Your benefits with MultiMark

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

#### **General ordering data**

 Type
 DEK 5/8 MM WS
 Version

 Order No.
 2007130000
 Dekafix, Terminal marker, 5 x 8 mm, Weidmueller, white

 GTIN (EAN)
 4050118392012

 Qty.
 500 pc(s).



Accessories

#### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

#### **Connection sleeves**



#### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

#### VH 12/4.9/3.3 024900

#### **General ordering data**

50 pc(s).

 Type
 VH 19/5/3.5 SAK4-16
 Version

 Order No.
 0285100000
 SAK Series, Connecting sleeve, for cross-connection link, Number of poles: 1

#### **Blank**

Qty.



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

**For custom printing:** Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

#### General ordering data

 Type
 DEK 5/8 MC NE WS
 Version

 Order No.
 1856740000
 Dekafix, Terminal marker, 5 x 8 mm, Pitch in mm (P): 8.00

 GTIN (EAN)
 4032248400850
 Weidmueller, white

 Qty.
 800 pc(s).



**Locking tabs** 

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

### **Accessories**



#### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

#### **General ordering data**

 Type
 VL 2 SAK16/SAKA
 Version

 Order No.
 0135800000
 SAK Series, Cross-connection lug, for cross-connection link, Number

 GTIN (EAN)
 4008190132088
 of poles: 2

 Qty.
 50 pc(s).