

### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

### **Product image**







### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

### **General ordering data**

Туре	DK 4/32 1D CSA A1
Order No.	<u>0484060000</u>
Version	SAK Series, Component terminal, Double-tier
	terminal, Rated cross-section: 4 mm², Screw
	connection
GTIN (EAN)	4008190006891
Qty.	25 pc(s).



### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

## **Technical data**

-			
Dim	ensions	and	weights

Width	6 mm	Width (inches)	0.236 inch
Height	50 mm	Height (inches)	1.969 inch
Depth	54 mm	Depth (inches)	2.126 inch
Net weight	13.12 g		

### **Temperatures**

Storage temperature, max.	40 °C	Storage temperature, min.	10 °C
Storage temperature	10 °C40 °C	Continuous operating temp., min.	-50 °C
Continuous operating temp., max.	100 °C		

### **Material data**

Material	PA 66	Colour	beige / yellow
UL 94 flammability rating	V-2		

### **System specifications**

Version	Screw connection, with diode, One end without	End cover plate required	
	connector		Yes
Number of potentials	1	Number of levels	2
Number of clamping points per level	2	Number of potentials per tier	1
Levels cross-connected internally	Yes	PE connection	No
Rail	TS 32	N-function	No
PE function	No	PEN function	No

### **Additional technical data**

Explosion-tested version	No	Number of similar terminals	1
Open sides	right	Type of mounting	Snap-on

### Component

Component 1	1 N 4007	Component current	1 A	
Component type	Diode	Component voltage	1,000 V	



## Technical data

### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

### **Conductors for clamping (rated connection)**

Blade size	0.6 x 3.5 mm	Clamping range, max.	4 mm <sup>2</sup>
Clamping range, min.	0.33 mm <sup>2</sup>	Clamping screw	M 3
Connection cross-section, stranded,		Connection cross-section, stranded, mi	in.
max.	4 mm <sup>2</sup>		0.5 mm <sup>2</sup>
Connection direction	on side	Gauge to IEC 60947-1	A3
Number of connections	4	Stripping length	9 mm
Tightening torque, max.	0.8 Nm	Tightening torque, min.	0.5 Nm
Torque level with DMS electric		Type of connection	
screwdriver	2		Screw connection
Wire connection cross section AWG,	·	Wire connection cross section AWG,	
max.	AWG 12	min.	AWG 22
Wire connection cross section, finely stranded, max.	4 mm²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max.	4 mm²
Wire connection cross-section, finely stranded with wire-end ferrules DIN		Wire connection cross-section, finely stranded, min.	
46228/1, min.	0.5 mm <sup>2</sup>		0.5 mm <sup>2</sup>
Wire connection cross-section, solid		Wire connection cross-section, solid	
core, max.	4 mm <sup>2</sup>	core, min.	0.5 mm <sup>2</sup>

### **Dimensions**

TS 32 offset	25 mm

### **Rating data**

Rated cross-section	4 mm <sup>2</sup>	Rated voltage	380 V	
Rated current	10 A	Current at maximum wires	10 A	
Volume resistance according to IEC		Power loss in accordance with IEC		
60947-7-x	1 mΩ	60947-7-x	1.02 W	
Pollution severity	3			

### Classifications

ETIM 6.0	EC000903	ETIM 7.0	EC000903
eClass 9.0	27-14-11-27	eClass 9.1	27-14-11-47
eClass 10.0	27-14-11-27	UNSPSC	30-21-18-11

### **Approvals**

Approvals



ROHS	Conform

### **Downloads**

Approval/Certificate/Document of	
Conformity	DE_PT1381_20160418_079_ISSUE01.pdf
Engineering Data	EPLAN, WSCAD
User Documentation	<u>StorageConditionsTerminalBlocks</u>

### Safety note

Safety notice	Safety Information



# Accessories

### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany Fon: +49 5231 14-0

Fax: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

### Q/AKZ



### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

### **General ordering data**

Туре	Q 2 AKZ4	Version
Order No.	0336400000	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190037680	poles: 2
Qty.	50 pc(s).	
Туре	Q 3 AKZ4	Version
Order No.	0336500000	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190121730	poles: 3
Qty.	50 pc(s).	
Туре	Q 10 AKZ4	Version
Order No.	0368600000	SAK Series, Cross-connector, for cross-connection link, Number of
Order No. GTIN (EAN)	<u>0368600000</u> 4008190056766	SAK Series, Cross-connector, for cross-connection link, Number of poles: 10
GTIN (EAN)	4008190056766	
GTIN (EAN) Qty.	4008190056766 20 pc(s).	poles: 10
GTIN (EAN) Qty. Type	4008190056766 20 pc(s). Q 4 AKZ4	poles: 10  Version

### **End bracket**



### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

### **General ordering data**

Туре	EWK 1	Version
Order No.	0206160000	Accessories, End bracket
GTIN (EAN)	4008190080020	
Qty.	50 pc(s).	
Туре	EW 35	Version
Type Order No.	EW 35 0383560000	Version Accessories, End bracket



# **SAK Series**

## **DK 4/32 1D CSA A1**

### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

### Accessories

**Test plug** 

### **Current and voltage transformer wiring**

Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.

### **General ordering data**

Туре PS 2.3 RT Order No. 0180400000 GTIN (EAN) 4008190060121 Qty. 20 pc(s).

Accessories, Test plug

### **QB RA**



### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

### **General ordering data**

Туре	QB 3 WI RA6 IS	Version
Order No.	0482800000	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190145217	poles: 3
Qty.	50 pc(s).	
Туре	QB 2 WI RA6 IS	Version
Order No.	0482700000	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190166021	poles: 2
Qty.	50 pc(s).	
Туре	QB 4 WI RA6 IS	Version
Order No.	0482900000	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190086169	poles: 4
Qty.	50 pc(s).	



## Accessories

### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany Fon: +49 5231 14-0

Fax: +49 5231 14-292083 www.weidmueller.com

### **Custom printing**



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

### **General ordering data**

	_	
Туре	DEK 5/6 MC SDR	Version
Order No.	<u>1609830000</u>	Dekafix, Terminal marker, 5 x 6 mm, Pitc
GTIN (EAN)	4008190456603	Weidmueller, To customer specification
Qty.	200 pc(s).	

### QВ



### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

### **General ordering data**

Туре	QB 75/6.2/9/WI	Version
Order No.	<u>0526400000</u>	SAK Series, Cross-connector, for cross-connection link, Number of
GTIN (EAN)	4008190099923	poles: 75
Qty.	10 pc(s).	
Туре	QB 75/6.2/15	Version
Type Order No.	QB 75/6.2/15 0535200000	Version SAK Series, Cross-connector, for cross-connection link, Number of

5 x 6 mm, Pitch in mm (P): 6.00



## Accessories

### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

### **Blank**



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- · Large range of ready-to-use markers
- · Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- · Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

### **General ordering data**

DEK 5/6 MC NE WS Order No. 1609820000 GTIN (EAN) 4008190203436 1,000 pc(s). Qty.

Version

Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00

Weidmueller, white

### Non-insulated sockets



### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

### General ordering data

Qty.

Туре STB 8.5/D4/2.3/M2.5 AKZ 0215700000 Order No.

GTIN (EAN) 4008190184872 50 pc(s).

Version

Accessories, Socket



## Accessories

### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

### **Connection sleeves**



### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

### VH 12/4.9/3.3 024900

### **General ordering data**

 Type
 VH 10/4/2.8 AKZ4
 Version

 Order No.
 0446600000
 SAK Series, Connecting sleeve, for cross-connection link, Number of poles: 1

 Qty.
 50 pc(s).

### **Small partition**



### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

### General ordering data

 Type
 TSCH 4 AKZ4
 Version

 Order No.
 0363360000
 SAK Series, Small partition, beige, 6 mm

 GTIN (EAN)
 4008190136680

 Qty.
 100 pc(s).



Accessories

### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

### Locking tabs



### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

### **General ordering data**

Type VL 2 SAK4
Order No. 0197000000
GTIN (EAN) 4008190000271
Oty. 50 pc(s).

Version

SAK Series, Cross-connection lug, for cross-connection link, Number

of poles: 2

### **End plates**



### Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easer and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

### **General ordering data**

 Type
 AP DK4
 Version

 Order No.
 0359260000
 SAK Series, End plate, 1.5 mm, beige, Direct mounting

 GTIN (EAN)
 4008190012991

 Qty.
 20 pc(s).