

**VPMS (blanking plug in brass)
VP 29-MS65**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



For sealing surplus threaded holes to maintain the IP class of protection

General ordering data

Type	VP 29-MS65
Order No.	0501100000
Version	VPMS (blanking plug in brass), Blanking plug, PG 29, 8 mm, Brass, nickel-plated
GTIN (EAN)	4008190126308
Qty.	50 pc(s).

Creation date May 1, 2020 12:23:33 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

Data sheet

**VPMS (blanking plug in brass)
VP 29-MS65**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

Length	12 mm	Length (inches)	0.472 inch
Height	12 mm	Height (inches)	0.472 inch
Net weight	20.4 g	Diameter	40 mm

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

General information

Material	Brass, nickel-plated	Cable glands	PG
External thread	PG 29	Length of thread	8 mm
Protection degree	IP68 - 5 bar (30 min.)	Operating temperature range, min.	-40 °C
Operating temperature range, max.	100 °C	Head diameter	40 mm
Halogen	No	O-Ring	NBR
Sealing	NBR		

Classifications

ETIM 6.0	EC000451	ETIM 7.0	EC000451
eClass 9.0	27-14-44-25	eClass 9.1	27-14-44-33
eClass 10.0	27-14-44-25	UNSPSC	30-21-18-01

Approvals

Approvals



ROHS	Conform
------	---------

Downloads

Brochure/Catalogue	CAT 3 HDC 17/18 EN CAT 5 ENCL 17/18 EN
Engineering Data	EPLAN, WSCAD
Engineering Data	STEP

Data sheet

**VPMS (blanking plug in brass)
VP 29-MS65**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

