

**CableLine  
CLI R 02-3 GE/SW Q**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com



Similar to illustration

The Weidmüller range of conductor and cable marker products provides users with solutions for the most diverse applications. The range of applications extends from narrow conductors right up to cables with large outside diameters. Among the products in the range are combination systems with individual tags, transparent sleeves, shrink-fit sleeves and markers, which can be fixed with cable ties.

**General ordering data**

|            |   |
|------------|---|
| Type       | CLI R 02-3 GE/SW Q  |
| Order No.  | <a href="#">0560001670</a>                                  |
| Version    | CableLine, Mounting mandrel, 1.3 - 3 mm, 3 x 3.4 mm, yellow |
| GTIN (EAN) | 4008 190989989  |
| Qty.       | 10 pc(s).   |

**CableLine**  
**CLI R 02-3 GE/SW Q**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Dimensions and weights**

|            |        |                 |            |
|------------|--------|-----------------|------------|
| Width      | 3.4 mm | Width (inches)  | 0.134 inch |
| Height     | 3 mm   | Height (inches) | 0.118 inch |
| Depth      | 4 mm   | Depth (inches)  | 0.157 inch |
| Net weight | 1.4 g  |                 |            |

**General data**

|  |                    |                           |                            |
|--|--------------------|---------------------------|----------------------------|
| Colour                                       | yellow             | Colour of printing        | black                      |
| Halogen                                      | Yes                | Material                  | PVC, soft, without Cadmium |
| Material colour according to resistance code | 4                  | Number per mandrel        | 25                         |
| Operating temperature range                  | -30...80 °C        | Orientation of print      | horizontal                 |
| Printed characters                           | Upper-case letters | Printing                  | Q                          |
| Printing method                              | hot-embossing      | Recommended industries    | Process, Machinery         |
| Type of printing                             | Standard           | UL 94 flammability rating | V-0                        |
| Version                                      | MultiPack          | Width                     | 3.4 mm                     |

**Conductor and cable markers**

|                               |                     |                               |                     |
|-------------------------------|---------------------|-------------------------------|---------------------|
| Conductor O.D.                | 1.3 - 3 mm          | Conductor O.D., max.          | 3 mm                |
| Conductor O.D., min.          | 1.3 mm              | Conductor cross-section, max. | 1.5 mm <sup>2</sup> |
| Conductor cross-section, min. | 0.2 mm <sup>2</sup> | Halogen                       | Yes                 |

**Classifications**

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC001530    | ETIM 7.0   | EC001530    |
| eClass 9.0  | 27-40-04-01 | eClass 9.1 | 27-40-06-29 |
| eClass 10.0 | 27-40-04-01 | UNSPSC     | 44-12-17-08 |

**Approvals**

|      |         |
|------|---------|
| ROHS | Conform |
|------|---------|

**Downloads**

|                             |  |
|-----------------------------|--|
| Engineering Data            | <a href="#">WSCAD</a>  |
| Product Change Notification | <a href="#">PCN CableLine_DE</a><br><a href="#">PCN CableLine_EN</a> |