

KDSU (Klippon double seal universal Ex cable gland) KDSU M25 BS O SC 2 G25

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



The KDSU features a special ring in the shape of a truncated cone. The ring enables connections between single-wire-armoured and metal-foil-armoured cables and braided-armoured lines. This ensures a conductive connection between the cable and the cable gland. It is also possible to connect non-armoured cables and lines. In addition, the KDSU comes with two separate seals which provide sealing for the outer and inner parts of the cable insulation. The cable armouring is located between the inner and outer insulation. When the cable gland is ordered together with a neoprene seal, the seal allows temperatures from -20°C to +85°C. When using a silicone seal, a temperature range of -60°C to +180°C is possible. The O-ring and the cable gland included in the delivery are made from the same material. When using both sealing materials, IP66 or IP68 protection at a depth of 25 metres under water (a pressure of 2.5 bar) is guaranteed. The KDSU is permitted for use with pressure-resistant Ex d encapsulations and increased safety Ex e. Besides the mechanical protective function offered for cables and lines, this can also be used for EMC applications.

General ordering data

Type	KDSU M25 BS O SC 2 G25
Order No.	0930031212
Version	KDSU (Klippon double seal universal Ex cable gland), Cable glands, M 25, 16 mm, Single-wire armouring, Metal foil armouring, Braided armouring, 0.1 - 1.6 mm, OD min. 20.3 - OD max. 27.4 mm, ID min. 13.50 - ID max. 20.00 mm, IP66, IP68 - 2.5 bar, Brass
GTIN (EAN)	4032248917921
Qty.	20 pc(s).

**KDSU (Klippon double seal universal Ex cable gland)
KDSU M25 BS 0 SC 2 G25**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Dimensions and weights**

Length	90 mm	Length (inches)	3.543 inch
Net weight	400 g		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

General information

Material	Brass	Cable glands	metric, brass
External thread	M 25	Pitch of thread	1.5 mm
Length of thread	16 mm	AF size 1	38 mm
Protection degree	IP66, IP68 - 2.5 bar	Protection degree with GWDR	IP66, IP68 - 2.5 bar
Water depth	25 m (30 Min.)	Operating temperature range, min.	-60 °C
Operating temperature range, max.	180 °C	Outer cable diameter, min.	20.3 mm
Outer cable diameter, max.	27.4 mm	Inner cable diameter, min.	13.5 mm
Inner cable diameter, max.	20 mm	Type of armouring, short term	SWA, STA, SWB
Type of armouring	Single-wire armouring, Metal foil armouring, Braided armouring	Armour, min.	0.1 mm
Armour, max.	1.6 mm	Size of protective cap	EL38
O-Ring	Silicone	Seal insert	Silicone
Sealing	Silicone	Installation guidelines	See assembly instructions

Classifications

ETIM 6.0	EC000441	ETIM 7.0	EC000441
eClass 9.0	27-14-44-32	eClass 9.1	27-14-44-34
eClass 10.0	27-14-44-32		

Approvals

Approvals



Approvals	EAC; ATEX; IECEX
ROHS	Conform

Downloads

Approval/Certificate/Document of Conformity	EU Declaration of Conformity - Klippon KDSU cable Gland - DoC DE PS2680 160315 001ISS01
Brochure/Catalogue	MB OVERV. PROCESS WD DE MB PROCESS EN CAT 5 ENCL 17/18 EN PI KLIPPON CABLE GL EN
Engineering Data	EPLAN, WSCAD
Engineering Data	STEP
User Documentation	Notice to Installers Assembly guidelines

Creation date May 1, 2020 2:30:09 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

2

Data sheet

**KDSU (Klippon double seal universal Ex cable gland)
KDSU M25 BS O SC 2 G25**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Accessories

Klippon® KSWF vulcanised fibre



The KSWF is a flat seal made from fibre material suitable for optional large-surface sealing of cable glands on enclosures or electrical cabinets.

General ordering data

Type	KSWF M25	Version
Order No.	0899770000	KSWF (flat gasket - vulcanised fibre), Sealing ring, M 25, Vulcanized
GTIN (EAN)	4032248850167	fibre
Qty.	25 pc(s).	

Brass nuts, standard, nickel-plated



Weidmüller has a variety of different cable and wire entry systems in the Portfolio: with different designs of plastic, brass and stainless steel cable glands in the IP66, 67, 68 or IP69k protection classes. As a complete alternative to cable glands, pre-assembled cables with modular multi-wire or multi-cable entry systems can be simply and quickly inserted into electrical equipment. Last but not least, Weidmüller offers EX-certified cable glands and cable/wire entry systems.

- Cable glands made from plastic and brass
- EMC screwed joints
- for areas at risk of explosion
- VDE, CSA and UL approvals

General ordering data

Type	SKMU M25 MS	Version
Order No.	1737010000	SKMU MS (brass locknut), Locknut, M 25, 3 mm, Brass, nickel-plated
GTIN (EAN)	4008190956486	
Qty.	100 pc(s).	

**KDSU (Klippon double seal universal Ex cable gland)
KDSU M25 BS O SC 2 G25**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Accessories

Protective caps - PVC



The KSPs are protective caps made from PVC. They protect disconnected cable glands from external environmental influences (e.g., dust) when delivered in a pre-assembled enclosure.

General ordering data

Type	KSP EL38	Version
Order No.	1736680000	KSP (Klippon shroud), Protective cap, PVC
GTIN (EAN)	4008190956349	
Qty.	10 pc(s).	

Klippon® KSWN Nylon



The KSWN is a flat seal made from nylon suitable for optional large-surface sealing of cable glands on enclosures or electrical cabinets.

General ordering data

Type	KSWN M25	Version
Order No.	1076640000	KSWN (flat gasket - nylon), Sealing ring, M 25, Nylon 6
GTIN (EAN)	4032248838684	
Qty.	25 pc(s).	

**KDSU (Klippon double seal universal Ex cable gland)
KDSU M25 BS O SC 2 G25**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Accessories

Safety serrated washer



The range of cable glands is rounded off by a large number of accessories.

The serrated stainless steel washers are used to prevent loosening of the assembled cable glands.

General ordering data

Type	SZS M25	Version
Order No.	1736320000	SZS (serrated washer), Retaining toothed washers, M 25, Stainless
GTIN (EAN)	4008190963521	steel 1.4404 (316L)
Qty.	10 pc(s).	

Nickel-plated earthing ring



The range of cable glands is rounded off by a large number of accessories.

Earthing rings are best used when a cable shielding is being tightened onto the cable gland, and when it has the same potential as another cable gland on the housing.

General ordering data

Type	EA-RING MS/M 25	Version
Order No.	1736500000	EA (earthing rings), Earthing ring, M 25, Brass, nickel-plated
GTIN (EAN)	4008190963606	
Qty.	20 pc(s).	