

**VG MS ZR (standard brass cable gland, multiseal)
VG M32-MS54 ZR 16-26**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Each size of this standard cable gland consists of multiple, separable seal inserts (onion-ring shaped). By separating these individual inserts, it becomes possible to install cables of varying diameters (from 4 mm to 41 mm) into the cable gland.

General ordering data

Type	VG M32-MS54 ZR 16-26
Order No.	1009580000
Version	VG MS ZR (standard brass cable gland, multiseal), Cable glands, M 32, 8 mm, OD min. 16 - OD max. 26 mm, Brass, nickel-plated
GTIN (EAN)	4032248714353
Qty.	25 pc(s).

**VG MS ZR (standard brass cable gland, multiseal)
VG M32-MS54 ZR 16-26**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Dimensions and weights**

Length	33 mm	Length (inches)	1.299 inch
Net weight	60.48 g		

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

General information

Material	Brass, nickel-plated	Cable glands	metric, nickel-plated brass
External thread	M 32	Pitch of thread	1.5 mm
Length of thread	8 mm	AF size 1	32 mm
AF size 2	34 mm	Protection degree	IP54
Operating temperature range, min.	-20 °C	Operating temperature range, max.	80 °C
Outer cable diameter, min.	16 mm	Outer cable diameter, max.	26 mm
Notch multi-layer sealing diameter 1	16 mm	Notch multi-layer sealing diameter 2	19 mm
Notch multi-layer sealing diameter 3	22 mm	Notch multi-layer sealing diameter 4	25 mm
Seal insert	NBR	Torque for cap nut, min.	4.88 Nm
Torque for cap nut, max.	4.88 Nm	Torque for connecting adapter, min.	10 Nm
Torque for connecting adapter, max.	10 Nm		

Classifications

ETIM 6.0	EC000441	ETIM 7.0	EC000441
eClass 9.0	27-14-44-32	eClass 9.1	27-14-44-32
eClass 10.0	27-14-44-32		

Approvals

Approvals



ROHS Conform

DownloadsEngineering Data [EPLAN, WSCAD](#)

**VG MS ZR (standard brass cable gland, multiseal)
VG M32-MS54 ZR 16-26**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Accessories

Klippon® KSWF vulcanised fibre



The KSWF is a flat seal made from fibre material suitable for optional large-surface sealing of cable glands on enclosures or electrical cabinets.

General ordering data

Type	KSWF M32	Version
Order No.	1076690000	KSWF (flat gasket - vulcanised fibre), Sealing ring, M 32, Vulcanized
GTIN (EAN)	4032248838622	fibre
Qty.	25 pc(s).	

GWDR - neoprene flat gasket



The range of cable glands is rounded off by a large number of accessories.

General ordering data

Type	GWDR M32-NP	Version
Order No.	1736260000	GWDR NP (flat gasket - neoprene), Sealing ring, M 32, Neoprene
GTIN (EAN)	4008190956059	
Qty.	50 pc(s).	

**VG MS ZR (standard brass cable gland, multiseal)
VG M32-MS54 ZR 16-26**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Accessories
Brass nuts, standard, nickel-plated


Weidmüller has a variety of different cable and wire entry systems in the Portfolio: with different designs of plastic, brass and stainless steel cable glands in the IP66, 67, 68 or IP69k protection classes. As a complete alternative to cable glands, pre-assembled cables with modular multi-wire or multi-cable entry systems can be simply and quickly inserted into electrical equipment. Last but not least, Weidmüller offers EX-certified cable glands and cable/wire entry systems.

- Cable glands made from plastic and brass
- EMC screwed joints
- for areas at risk of explosion
- VDE, CSA and UL approvals

General ordering data

Type	SKMU M32 MS	Version
Order No.	1737020000	SKMU MS (brass locknut), Locknut, M 32, 4 mm, Brass, nickel-plated
GTIN (EAN)	4008190956493	
Qty.	100 pc(s).	

GWDR - Polyethylene flat gasket

The range of cable glands is rounded off by a large number of accessories.


General ordering data

Type	GWDR M32-PO	Version
Order No.	1777960000	GWDR PO (flat gasket - polyethylene), Sealing ring, M 32, Polyethylene
GTIN (EAN)	4032248158225	
Qty.	50 pc(s).	

**VG MS ZR (standard brass cable gland, multiseal)
VG M32-MS54 ZR 16-26**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Accessories
Brass nuts, standard, natural


Weidmüller has a variety of different cable and wire entry systems in the Portfolio: with different designs of plastic, brass and stainless steel cable glands in the IP66, 67, 68 or IP69k protection classes. As a complete alternative to cable glands, pre-assembled cables with modular multi-wire or multi-cable entry systems can be simply and quickly inserted into electrical equipment. Last but not least, Weidmüller offers EX-certified cable glands and cable/wire entry systems.

- Cable glands made from plastic and brass
- EMC screwed joints
- for areas at risk of explosion
- VDE, CSA and UL approvals

General ordering data

Type	SKMU M32 MS SC	Version
Order No.	0930640004	SKMU MS (brass locknut), Locknut, M 32, 4 mm, Brass
GTIN (EAN)	4032248976089	
Qty.	20 pc(s).	

Klippon® KSWN Nylon


The KSWN is a flat seal made from nylon suitable for optional large-surface sealing of cable glands on enclosures or electrical cabinets.

General ordering data

Type	KSWN M32	Version
Order No.	1076650000	KSWN (flat gasket - nylon), Sealing ring, M 32, Nylon 6
GTIN (EAN)	4032248838691	
Qty.	25 pc(s).	