

**W-Series
WDU 4 GN**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Product image**Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

| | |
|------------|---|
| Type | WDU 4 GN |
| Order No. | 1020160000 |
| Version | Feed-through terminal, Screw connection, 4 mm ² , 800 V, 32 A, green |
| GTIN (EAN) | 4008 190426293 |
| Qty. | 100 pc(s). |

W-Series
WDU 4 GN

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

| | | | |
|--------------------------|---------|-----------------|------------|
| Width | 6.1 mm | Width (inches) | 0.24 inch |
| Height | 60 mm | Height (inches) | 2.362 inch |
| Depth | 46.5 mm | Depth (inches) | 1.831 inch |
| Depth including DIN rail | 47 mm | Weight | 10.4 g |
| Net weight | 9.53 g | | |

Temperatures

| | | | |
|----------------------------------|---|----------------------------------|---------------|
| Operating temperature range | For operating temperature range see EC Design Test Certificate / IEC Ex-Certificate of Conformity | Storage temperature, max. | 40 °C |
| Storage temperature, min. | 10 °C | Storage temperature | 10 °C...40 °C |
| Continuous operating temp., min. | -60 °C | Continuous operating temp., max. | 130 °C |

Material data

| | | | |
|---------------------------|-------|--------|-------|
| Material | Wemid | Colour | green |
| UL 94 flammability rating | V-0 | | |

Rating data IECEx/ATEX

| | | | |
|--------------------------------|---|---------------------------------|-------------------|
| Certificate No. (ATEX) | DEMKO14ATEX1338U | Certificate No. (IECEX) | IECEXULD14.0005U |
| Max. voltage (ATEX) | 690 V | Current (ATEX) | 32 A |
| Wire cross section max. (ATEX) | 4 mm ² | Max. voltage (IECEX) | 690 V |
| Current (IECEX) | 32 A | Wire cross section max. (IECEX) | 4 mm ² |
| Operating temperature range | For operating temperature range see EC Design Test Certificate / IEC Ex-Certificate of Conformity | Marking EN 60079-7 | Ex eb II C Gb |
| Ex 2014/34/EU label | II 2 G D | | |

System specifications

| | | | |
|-------------------------------------|--|-------------------------------|-----|
| Version | Screw connection, for plug-in cross-connector, for screwable cross-connection, One end without connector | End cover plate required | Yes |
| Number of potentials | 1 | Number of levels | 1 |
| Number of clamping points per level | 2 | Number of potentials per tier | 1 |
| Levels cross-connected internally | No | PE connection | No |
| Rail | TS 35 | N-function | No |
| PE function | No | PEN function | No |

2 clampable conductors (H05V/H07V) with equal cross-section (rated connection)

| | | | |
|--|---------------------|--|---------------------|
| Wire connection cross section, finely stranded, two clampable wires, min. | 0.5 mm ² | Wire cross-section, finely stranded, two clampable wires, max. | 1.5 mm ² |
| Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, 2 clampable wires, min. | 0.5 mm ² | Wire connection cross section, finely stranded with wire-end ferrules DIN 46228/1, 2 clampable wires, max. | 1.5 mm ² |

W-Series
WDU 4 GN

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Additional technical data**

| | | | |
|--------------------------|-------|-----------------------------|---------|
| Explosion-tested version | Yes | Number of similar terminals | 1 |
| Open sides | right | Type of mounting | Snap-on |

CSA rating data

| | | | |
|-------------------------------|----------------|-------------------------------|--------|
| Certificate No. (CSA) | 200039-1057876 | Current size B (CSA) | 35 A |
| Current size C (CSA) | 35 A | Voltage size C (CSA) | 600 V |
| Wire cross section max. (CSA) | 10 AWG | Wire cross section min. (CSA) | 26 AWG |

Conductors for clamping (rated connection)

| | | | |
|---|----------------------|---|---------------------|
| Blade size | 0.6 x 3.5 mm | Clamping range, max. | 6 mm ² |
| Clamping range, min. | 0.13 mm ² | Clamping screw | M 3 |
| Connection cross-section, stranded, max. | 6 mm ² | Connection cross-section, stranded, min. | 1.5 mm ² |
| Connection direction | on side | Gauge to IEC 60947-1 | A4 |
| Number of connections | 2 | Stripping length | 10 mm |
| Tightening torque, max. | 1 Nm | Tightening torque, min. | 0.5 Nm |
| Torque level with DMS electric screwdriver | 2 | Twin wire-end ferrules, max. | 2.5 mm ² |
| Twin wire-end ferrules, min. | 0.5 mm ² | Type of connection | Screw connection |
| Wire connection cross section AWG, max. | AWG 10 | Wire connection cross section AWG, min. | AWG 26 |
| Wire connection cross section, finely stranded, max. | 6 mm ² | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max. | 4 mm ² |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min. | 0.5 mm ² | Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max. | 4 mm ² |
| Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min. | 0.5 mm ² | Wire connection cross-section, finely stranded, min. | 0.5 mm ² |
| Wire connection cross-section, solid core, max. | 6 mm ² | Wire connection cross-section, solid core, min. | 0.5 mm ² |

Rating data

| | | | |
|---|-------------------|--|-------|
| Rated cross-section | 4 mm ² | Rated voltage | 800 V |
| Rated current | 32 A | Current at maximum wires | 41 A |
| Standards | IEC 60947-7-1 | Volume resistance according to IEC 60947-7-x | 1 mΩ |
| Power loss in accordance with IEC 60947-7-x | 1.02 W | Rated impulse withstand voltage | 8 kV |
| Pollution severity | 3 | | |

UL rating data

| | | | |
|---|--------|---|--------|
| Certificate No. (UR) | E60693 | Conductor size Factory wiring max. (UR) | 10 AWG |
| Conductor size Factory wiring min. (UR) | 26 AWG | Conductor size Field wiring max. (UR) | 10 AWG |
| Conductor size Field wiring min. (UR) | 22 AWG | Current size C (UR) | 35 A |
| Voltage size C (UR) | 600 V | | |

Data sheet

**W-Series
WDU 4 GN**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Classifications

| | | | |
|-------------|-------------|------------|-------------|
| ETIM 6.0 | EC000897 | ETIM 7.0 | EC000897 |
| eClass 9.0 | 27-14-11-20 | eClass 9.1 | 27-14-11-20 |
| eClass 10.0 | 27-14-11-20 | UNSPSC | 30-21-18-11 |

Approvals

Approvals



ROHS Conform

Downloads

| | |
|---|--|
| Approval/Certificate/Document of Conformity | Attestation of Conformity CB Testreport CB Certificate DE_PT1001_20160414_204_ISSUE01.pdf |
| Engineering Data | EPLAN, WSCAD, Zuken E3.S |
| Engineering Data | STEP |
| User Documentation | NTI WDU/WPE 4 StorageConditionsTerminalBlocks |

Safety note

Safety notice [Safety Information](#)

Data sheet

W-Series
WDU 4 GN

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings



W-Series WDU 4 GN

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories

ZGB pivotable group tag holder



The ZGB 15 is a hinged group tag carrier. The tag carrier can hold the dekafix 5, WS 12/5 terminal markers or the inlay tag ESO 15.

The ZGB 30 is a hinged group tag carrier. The tag carrier can hold the dekafix 5, WS 12/5 terminal markers or the inlay tag ESO 7.

Inlay tags and protective strips can be found under "Accessories".

General ordering data

| | | |
|------------|----------------------------|---|
| Type | ZGB 30 | Version |
| Order No. | 1611930000 | Terminal markers, Terminal marker, 32 x 7 mm, Pitch in mm (P): 5.00 |
| GTIN (EAN) | 4008190002251 | white |
| Qty. | 20 pc(s). | |
| Type | ZGB 15 | Version |
| Order No. | 1636530000 | Terminal markers, Terminal marker, 15 x 7 mm, Pitch in mm (P): 5.00 |
| GTIN (EAN) | 4008190297053 | Weidmueller, white |
| Qty. | 20 pc(s). | |

Partition plates



Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

| | | |
|------------|----------------------------|----------------------------|
| Type | WTW EN | Version |
| Order No. | 1058800000 | W-Series, Separation plate |
| GTIN (EAN) | 4008190140175 | |
| Qty. | 20 pc(s). | |

**W-Series
WDU 4 GN**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories

End brackets



Klippon® Connect with clamping yoke Technology
 The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

| | | |
|------------|----------------------------|-----------------------|
| Type | WEW 35/2 | Version |
| Order No. | 1061200000 | W-Series, End bracket |
| GTIN (EAN) | 4008190030230 | |
| Qty. | 100 pc(s). | |

Blank



The WAD connector marker is suitable for W-series terminals and for the WEW 35/2 and ZEW 35/2 end brackets. The markers are available as blank markers, with custom printing or standard print with lightning symbol. The WAD MultiCard markers are suitable for labelling with PrintJet ADVANCED printers.

- High-quality and resistant printing with PrintJet
- WAD marker and cover for the W-series terminals and the WEW 35/2 or ZEW 35/2 end brackets
- Available as blank markers, with custom printing or standard print with lightning symbol
- Quick and easy installation

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

| | | |
|------------|----------------------------|---|
| Type | WAD 5 MC NE GE | Version |
| Order No. | 1112920000 | Group markers, Cover, 33.3 x 5 mm, Pitch in mm (P): 5.00 yellow |
| GTIN (EAN) | 4032248891771 | |
| Qty. | 48 pc(s). | |
| Type | WAD 5 MC NE WS | Version |
| Order No. | 1112910000 | Group markers, Cover, 33.3 x 5 mm, Pitch in mm (P): 5.00 white |
| GTIN (EAN) | 4032248891689 | |
| Qty. | 48 pc(s). | |

W-Series
WDU 4 GN

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories**ZQV 4N****Spring connection with PUSH IN Technology**

The innovative PUSH IN technology reduces the amount of time you spend on wiring to a minimum. Direct insertion guarantees high conductor pull-out forces and simple handling for all conductor types.

General ordering data

| | |
|------------|----------------------------|
| Type | ZQV 4N/8 BL |
| Order No. | 1528190000 |
| GTIN (EAN) | 4050118332858 |
| Qty. | 20 pc(s). |
| Type | ZQV 4N/9 |
| Order No. | 1528070000 |
| GTIN (EAN) | 4050118332797 |
| Qty. | 20 pc(s). |
| Type | ZQV 4N/10 |
| Order No. | 1528090000 |
| GTIN (EAN) | 4050118332896 |
| Qty. | 20 pc(s). |
| Type | ZQV 4N/50 BL |
| Order No. | 1528240000 |
| GTIN (EAN) | 4050118333121 |
| Qty. | 5 pc(s). |
| Type | ZQV 4N/7 RD |
| Order No. | 2460770000 |
| GTIN (EAN) | 4050118476194 |
| Qty. | 20 pc(s). |
| Type | ZQV 4N/3 |
| Order No. | 1527940000 |
| GTIN (EAN) | 4050118332865 |
| Qty. | 60 pc(s). |
| Type | ZQV 4N/30 RD |
| Order No. | 2561600000 |
| GTIN (EAN) | 4050118569964 |
| Qty. | 5 pc(s). |
| Type | ZQV 4N/4 |
| Order No. | 1527970000 |
| GTIN (EAN) | 4050118332889 |
| Qty. | 60 pc(s). |
| Type | ZQV 4N/5 BL |
| Order No. | 1528140000 |
| GTIN (EAN) | 4050118333015 |
| Qty. | 60 pc(s). |
| Type | ZQV 4N/2 |
| Order No. | 1527930000 |
| GTIN (EAN) | 4050118332766 |
| Qty. | 60 pc(s). |

Creation date May 1, 2020 6:48:30 AM CEST

W-Series
WDU 4 GN

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories

| | |
|------------|----------------------------|
| Type | ZQV 4N/10 BL |
| Order No. | 1528230000 |
| GTIN (EAN) | 4050118333138 |
| Qty. | 20 pc(s). |
| Type | ZQV 4N/8 |
| Order No. | 1528030000 |
| GTIN (EAN) | 4050118332841 |
| Qty. | 20 pc(s). |
| Type | ZQV 4N/4 BL |
| Order No. | 1528120000 |
| GTIN (EAN) | 4050118332872 |
| Qty. | 60 pc(s). |
| Type | ZQV 4N/4 RD |
| Order No. | 2460800000 |
| GTIN (EAN) | 4050118476224 |
| Qty. | 60 pc(s). |
| Type | ZQV 4N/2 BL |
| Order No. | 1528040000 |
| GTIN (EAN) | 4050118332773 |
| Qty. | 60 pc(s). |
| Type | ZQV 4N/10 RD |
| Order No. | 2460740000 |
| GTIN (EAN) | 4050118476163 |
| Qty. | 20 pc(s). |
| Type | ZQV 4N/7 BL |
| Order No. | 1528180000 |
| GTIN (EAN) | 4050118333114 |
| Qty. | 20 pc(s). |
| Type | ZQV 4N/30 BL |
| Order No. | 2561610000 |
| GTIN (EAN) | 4050118569971 |
| Qty. | 5 pc(s). |
| Type | ZQV 4N/50 RD |
| Order No. | 2460730000 |
| GTIN (EAN) | 4050118476156 |
| Qty. | 5 pc(s). |
| Type | ZQV 4N/3 BL |
| Order No. | 1528080000 |
| GTIN (EAN) | 4050118333008 |
| Qty. | 60 pc(s). |
| Type | ZQV 4N/6 |
| Order No. | 1527990000 |
| GTIN (EAN) | 4050118332919 |
| Qty. | 20 pc(s). |
| Type | ZQV 4N/5 |
| Order No. | 1527980000 |
| GTIN (EAN) | 4050118332759 |
| Qty. | 60 pc(s). |
| Type | ZQV 4N/9 RD |
| Order No. | 2460750000 |
| GTIN (EAN) | 4050118476170 |
| Qty. | 20 pc(s). |

Creation date May 1, 2020 6:48:30 AM CEST

W-Series WDU 4 GN

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Accessories

Type ZQV 4N/3 RD
Order No. [2460810000](#)
GTIN (EAN) 4050118476231
Qty. 60 pc(s).

Type ZQV 4N/30
Order No. [2561580000](#)
GTIN (EAN) 4050118570113
Qty. 5 pc(s).

Type ZQV 4N/9 BL
Order No. [1528220000](#)
GTIN (EAN) 4050118333107
Qty. 20 pc(s).

Type ZQV 4N/50
Order No. [1528130000](#)
GTIN (EAN) 4050118332902
Qty. 5 pc(s).

Type ZQV 4N/2 RD
Order No. [2460450000](#)
GTIN (EAN) 4050118476149
Qty. 60 pc(s).

Type ZQV 4N/6 RD
Order No. [2460780000](#)
GTIN (EAN) 4050118476200
Qty. 20 pc(s).

Type ZQV 4N/7
Order No. [1528020000](#)
GTIN (EAN) 4050118332780
Qty. 20 pc(s).

Type ZQV 4N/8 RD
Order No. [2460760000](#)
GTIN (EAN) 4050118476187
Qty. 20 pc(s).

Type ZQV 4N/5 RD
Order No. [2460790000](#)
GTIN (EAN) 4050118476217
Qty. 60 pc(s).

Type ZQV 4N/6 BL
Order No. [1528170000](#)
GTIN (EAN) 4050118332926
Qty. 20 pc(s).

W-Series
WDU 4 GN

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories**ZQV 4N****Spring connection with tension clamp Technology**

Tension clamp technology is a universal contact system for all common conductor connection types. Its fantastic level of flexibility makes the tension clamp a profitable alternative connection.

General ordering data

| | | |
|------------|----------------------------|------------------------------------|
| Type | ZQV 4N/20 GE | Version |
| Order No. | 1909020000 | Accessories, Cross-connector, 32 A |
| GTIN (EAN) | 4032248535644 | |
| Qty. | 20 pc(s). | |
| Type | ZQV 4N/4 GE | Version |
| Order No. | 1762620000 | Accessories, Cross-connector, 32 A |
| GTIN (EAN) | 4032248169771 | |
| Qty. | 60 pc(s). | |
| Type | ZQV 4N/3 GE | Version |
| Order No. | 1762630000 | Accessories, Cross-connector, 32 A |
| GTIN (EAN) | 4032248169788 | |
| Qty. | 60 pc(s). | |
| Type | ZQV 4N/2 GE | Version |
| Order No. | 1758250000 | Accessories, Cross-connector, 32 A |
| GTIN (EAN) | 4032248169795 | |
| Qty. | 60 pc(s). | |
| Type | ZQV 4N/10 GE | Version |
| Order No. | 1758260000 | Accessories, Cross-connector, 32 A |
| GTIN (EAN) | 4032248169764 | |
| Qty. | 20 pc(s). | |

End plates**Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

| | | |
|------------|----------------------------|---------------------|
| Type | WAP 2.5-10 | Version |
| Order No. | 1050000000 | W-Series, End plate |
| GTIN (EAN) | 4008190103149 | |
| Qty. | 50 pc(s). | |

Data sheet

W-Series WDU 4 GN

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories

| | | |
|------------|----------------------------|---------------------------------------|
| Type | WAP 2.5-10 BL | Version |
| Order No. | 1050080000 | W-Series, End plate |
| GTIN (EAN) | 4008190136611 | |
| Qty. | 50 pc(s). | |
| Type | WAP 16+35 WTW 2.5-10 | Version |
| Order No. | 1050100000 | W-Series, End plate, Separation plate |
| GTIN (EAN) | 4008190079901 | |
| Qty. | 20 pc(s). | |
| Type | WAP 16+35 WTW 2.5-10 BL | Version |
| Order No. | 1050180000 | W-Series, End plate, Separation plate |
| GTIN (EAN) | 4008190013899 | |
| Qty. | 20 pc(s). | |

PicoPak



PicoPak: the robust one

- Space-saving in the control cabinet thanks to the slim 6 mm width
- Passive isolator, loop-powered at the input and output
- Increased operating temperature range: -40°C ...+70°C
- Zero and Span adjustment possible

General ordering data


| | | |
|------------|----------------------------|--|
| Type | WS 12/6 MC NE WS | Version |
| Order No. | 1609900000 | WS, Terminal marker, 12 x 6 mm, Pitch in mm (P): 6.00 Weidmueller, |
| GTIN (EAN) | 4008190203467 | Allen-Bradley, white |
| Qty. | 600 pc(s). | |

W-Series WDU 4 GN

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories

Blank



The Dekafix (DEK) marker is the universal marker for all conductor and plug-in connectors as well as for electronic sub-assemblies. The system is ideal for short number sequences and covers a wide range of ready-printed markers.

Strips for fast installation in only one work step. The printing is easy to read, rich in contrast and available in various widths.

- Large range of ready-to-use markers
- Strips for fast installation
- Terminal markers, suitable for all Weidmüller cable connectors
- Available as blank MultiCard or with standard printing

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

| | | |
|------------|----------------------------|---|
| Type | DEK 5/6 MC NE WS | Version |
| Order No. | 1609820000 | Dekafix, Terminal marker, 5 x 6 mm, Pitch in mm (P): 6.00 |
| GTIN (EAN) | 4008190203436 | Weidmueller, white |
| Qty. | 1,000 pc(s). | |

Test adapter



Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

| | | |
|------------|----------------------------|------------------------|
| Type | WTA 3 WDU4 | Version |
| Order No. | 1632350000 | W-Series, Test adapter |
| GTIN (EAN) | 4008190209711 | |
| Qty. | 25 pc(s). | |
| Type | WTA 3/ZA WDU4 | Version |
| Order No. | 1632360000 | W-Series, Test adapter |
| GTIN (EAN) | 4008190209704 | |
| Qty. | 25 pc(s). | |

W-Series WDU 4 GN

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories

Non-insulated sockets



Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

| | | |
|------------|---------------------------|---------------------|
| Type | STB 8.5/5/2.3/M3 SAK2.5 | Version |
| Order No. | 028060000 | Accessories, Socket |
| GTIN (EAN) | 4008190023188 | |
| Qty. | 50 pc(s). | |

DEK 5/6



WS/ DEK

MultiMark DEK/WS connector markers use an innovative composite material made from two components. The hard base contour of the marker snaps securely into the connector. The elastic surface finish makes the marker easy to mount. This specially punched material enables the strips to be stretched to accommodate the slight variations in spacing that tend to add up, especially with long terminal blocks. Another advantage: the excellent printability of the surface material guarantees durable and wear-resistant labelling. A print resolution of 300 dpi also produces a very legible script.

Your benefits with MultiMark

- Firm hold and durable printing
- Continuous strips save installation time
- Easy mounting thanks to an innovative composite material
- Large label field for optimal legibility
- High flexibility thanks to manufacturer independence

General ordering data


| | | |
|------------|---------------------------|--|
| Type | DEK 5/6 MM WS | Version |
| Order No. | 200712000 | Dekafix, Terminal marker, 5 x 6 mm, Weidmueller, white |
| GTIN (EAN) | 4050118392104 | |
| Qty. | 600 pc(s). | |

**W-Series
WDU 4 GN**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories

SchT group marker carrier



The SchT 5 S group tag carriers are clipped directly onto the TS 32 mounting rail (G-rail) or the TS 35 mounting rail (top-hat rail). It is therefore possible to label the terminal strip irrespective of the terminal and the type of terminal. SchT 5 and SchT 5 S are fitted with ESO 5, STR 5 protective strips.

The SchT 7 is a hinged group tag carrier for inlay tags which enables easy access to the clamping screw. The SchT 7 is fitted with ESO 7, STR 7 protective strips or DEK 5.

SchT 9/4 and SchT 14/6 are hinged group tag carriers for single dekafix and WS tags that enable easy access to the clamping screw.

SchT 9/4 and SchT 14/6 are fitted with WS or DEK. Inlay tags and protective strips can be found under "Accessories".

General ordering data

| | | |
|------------|----------------------------|---|
| Type | SCHT 7 | Version |
| Order No. | 0517960000 | SCHT, Terminal marker, 39.3 x 8 mm, Pitch in mm (P): 7.00 |
| GTIN (EAN) | 4008190001742 | Weidmueller, white |
| Qty. | 20 pc(s). | |

Shielding bus



Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

| | | |
|------------|----------------------------|----------------------|
| Type | LS 2.8 WDU2.5-10 | Version |
| Order No. | 1056400000 | W-Series, Shield bus |
| GTIN (EAN) | 4008190036454 | |
| Qty. | 100 pc(s). | |

W-Series WDU 4 GN

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories

WQV 4



Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

| | | |
|------------|----------------------------|---|
| Type | WQV 4/2 | Version |
| Order No. | 1051960000 | W-Series, Cross-connector, For the terminals, Number of poles: 2 |
| GTIN (EAN) | 4008190026486 | |
| Qty. | 50 pc(s). | |
| Type | WQV 4/4 | Version |
| Order No. | 1054660000 | W-Series, Cross-connector, For the terminals, Number of poles: 4 |
| GTIN (EAN) | 4008190095758 | |
| Qty. | 50 pc(s). | |
| Type | WQV 4/3 | Version |
| Order No. | 1054560000 | W-Series, Cross-connector, For the terminals, Number of poles: 3 |
| GTIN (EAN) | 4008190168971 | |
| Qty. | 50 pc(s). | |
| Type | WQV 4/10 | Version |
| Order No. | 1052060000 | W-Series, Cross-connector, For the terminals, Number of poles: 10 |
| GTIN (EAN) | 4008190054687 | |
| Qty. | 20 pc(s). | |

Test sockets



Current and voltage transformer wiring

Our test disconnect terminal blocks featuring spring and screw connection technology allow you to create all the important converter circuits for measuring current, voltage and power in a safe and sophisticated way.

General ordering data

| | | |
|------------|----------------------------|---------------------|
| Type | STB 21.6/IH/BL WTL6/3 | Version |
| Order No. | 1071080000 | Accessories, Socket |
| GTIN (EAN) | 4008190043957 | |
| Qty. | 50 pc(s). | |
| Type | STB 21.6/IH/GN WTL6/3 | Version |
| Order No. | 1071020000 | Accessories, Socket |
| GTIN (EAN) | 4008190259228 | |
| Qty. | 50 pc(s). | |

W-Series
WDU 4 GN

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories

| | | |
|------------|----------------------------|---------------------|
| Type | STB 21.6/IH/GE WTL6/3 | Version |
| Order No. | 1071010000 | Accessories, Socket |
| GTIN (EAN) | 4008190259211 | |
| Qty. | 50 pc(s). | |
| Type | STB 21.6/IH/WS WTL6/3 | Version |
| Order No. | 1312520000 | Accessories, Socket |
| GTIN (EAN) | 4050118121704 | |
| Qty. | 50 pc(s). | |
| Type | STB 21.6/IH/RT WTL6/3 | Version |
| Order No. | 1778990000 | Accessories, Socket |
| GTIN (EAN) | 4032248169665 | |
| Qty. | 50 pc(s). | |
| Type | STB 21.6/IH/DB WTL6/3 | Version |
| Order No. | 1071000000 | Accessories, Socket |
| GTIN (EAN) | 4008190259204 | |
| Qty. | 50 pc(s). | |
| Type | STB 21.6/IH/VI WTL6/3 | Version |
| Order No. | 1071030000 | Accessories, Socket |
| GTIN (EAN) | 4008190259235 | |
| Qty. | 50 pc(s). | |
| Type | STB 21.6/IH/SW WTL6/3 | Version |
| Order No. | 1071040000 | Accessories, Socket |
| GTIN (EAN) | 4008190859985 | |
| Qty. | 50 pc(s). | |