

SAIL-VSA-M8W-3-3.0U

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





Weidmüller can supply valve plugs as connecting lines with M12 plugs and one end without connector. The status of the valve plug is shown by an LED. Every valve plug is fitted with a protective circuit. The Weidmüller range includes valve plugs of type A, B and C to DIN and industry standards. In the plugged condition they achieve IP 67 class of protection. The outlet direction is also a decisive factor: Weidmüller can also supply 0° versions, i.e. the cable outlet direction is located at the PE contact.

General ordering data

Туре	SAIL-VSA-M8W-3-3.0U
Order No.	<u>1026190300</u>
Version	Valve plug, 90° plug - valve plug, A
GTIN (EAN)	4032248753727
Qty.	1 pc(s).



SAIL-VSA-M8W-3-3.0U

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

-	-		
Dım	ensions	and	weights

Net weight	125 g

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Technical specifications for cable

Number of poles	3	Core cross-section	0.5 mm ²
Cable length	3 m	Sheath material	PUR
Sheathing colour	black	Halogen	No
Temperature range, moving	-2580 °C	Temperature range, stationary	-5080 °C
Suitable for cable carriers	Yes		

General technical data

Version	90° plug - valve plug	Connection thread	M8
Threaded ring material		Coding	Design A (18 mm), M8 =
	Brass, nickel-plated		none
Protection degree	IP67, when screwed in	Contact surface	tinned
LED	Yes	Rated voltage	24 V
Rated current	4 A	Temperature range of housing	-25+80 °C
All valve plugs are fitted with pr	rotective		
circuits	Suppressor diode		

Classifications

ETIM 6.0	EC001855	ETIM 7.0	EC001855
eClass 9.0	27-06-03-12	eClass 9.1	27-06-03-11
eClass 10.0	27-06-03-12		

Approvals

Approvals



ROHS Conform

Downloads

Brochure/Catalogue <u>FL FIELDWIRING EN</u>



SAIL-VSA-M8W-3-3.0U

Weidmüller Interface GmbH & Co. KG


Klingenbergstraße 26 D-32758 Detmold

Germany


Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Drawings

Dimensioned drawing





Dimensioned drawing



Pole scheme

Pole scheme





Wiring diagram

