

SlimFix X SFX 11/60 MC NE OR

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Similar to illustration

SlimFix X are halogen-free conductor and cable markers with a space-saving design. The markers can be fitted even after the conductor has been installed. SlimFix is an acknowledged and approved marker type in traffic engineering. The SF tool allows easy installation even in case of small markers.

- Halogen-free material
- Approved and accredited markers for traffic engineering applications, etc.
- Has to be fixed with cable ties if the conductor cross-section is larger than 16.0 mm²
- Markers in proven MultiCard format

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.



General ordering data

| | |
|---------------------|--|
| Type | SFX 11/60 MC NE OR |
| Order No. | 1051890000 |
| Version | SlimFix X, Conductor and cable markers, 7 - 40 mm, 60 x 11 mm, orange |
| GTIN (EAN) | 4032248790920 |
| Qty. | 60 pc(s). |
| compatible printer | 1324380000 2438520000 2438510000 |
| Alternative product | 1860140000 |

SlimFix X
SFX 11/60 MC NE OR

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

| | | | |
|------------|---------|-----------------|------------|
| Width | 11 mm | Width (inches) | 0.433 inch |
| Height | 60 mm | Height (inches) | 2.362 inch |
| Depth | 0.8 mm | Depth (inches) | 0.031 inch |
| Net weight | 2.067 g | | |

General data

| | | | |
|-----------------------------|--------------|--|------------------------------|
| Colour | orange | Halogen | No |
| Material | Polyamide 66 | Material colour according to resistance code | 3 |
| Operating temperature range | -40...100 °C | Recommended industries | Transportation, Machinery |
| Size of labelling field | 44 x 11 mm | Type of printing | neutral |
| UL 94 flammability rating | V-2 | Version | Installation with cable ties |
| Width | 11 mm | | |

Conductor and cable markers

| | | | |
|-------------------------------|--------------------|-------------------------------|---------------------|
| Conductor O.D. | 7 - 40 mm | Conductor O.D., max. | 40 mm |
| Conductor O.D., min. | 7 mm | Conductor cross-section, max. | 500 mm ² |
| Conductor cross-section, min. | 16 mm ² | Halogen | No |

Classifications

| | | | |
|-------------|-------------|------------|-------------|
| ETIM 6.0 | EC001530 | ETIM 7.0 | EC001530 |
| eClass 9.0 | 27-40-04-01 | eClass 9.1 | 27-40-04-01 |
| eClass 10.0 | 27-40-04-01 | | |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|------------------|--|
| Engineering Data | EPLAN, WSCAD, Zuken E3.S |
| Engineering Data | STEP |

Data sheet

SlimFix X
SFX 11/60 MC NE OR

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

