

**W-Series  
WQV 2.5/30**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Product image****Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

**General ordering data**

|            |  |
|------------|--|
| Type       | WQV 2.5/30   |
| Order No.  | <a href="#">1067500000</a>   |
| Version    | W-Series, Cross-connector, For the terminals,<br>Number of poles: 30 |
| GTIN (EAN) | 4008 190031107   |
| Qty.       | 10 pc(s).  |

**Data sheet**

**W-Series  
WQV 2.5/30**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

**Dimensions and weights**

|            |          |                 |            |
|------------|----------|-----------------|------------|
| Width      | 7 mm     | Width (inches)  | 0.276 inch |
| Height     | 151.9 mm | Height (inches) | 5.98 inch  |
| Depth      | 18 mm    | Depth (inches)  | 0.709 inch |
| Net weight | 25.8 g   |                 |            |

**Temperatures**

|                                  |               |                                  |        |
|----------------------------------|---------------|----------------------------------|--------|
| Storage temperature, max.        | 40 °C         | Storage temperature, min.        | 10 °C  |
| Storage temperature              | 10 °C...40 °C | Continuous operating temp., min. | -60 °C |
| Continuous operating temp., max. | 130 °C        |                                  |        |

**Material data**

|                           |       |        |        |
|---------------------------|-------|--------|--------|
| Material                  | PA 66 | Colour | yellow |
| UL 94 flammability rating | V-0   |        |        |

**System specifications**

|         |                   |
|---------|-------------------|
| Version | For the terminals |
|---------|-------------------|

**Additional technical data**

|                     |                 |                |                 |
|---------------------|-----------------|----------------|-----------------|
| Installation advice | Direct mounting | Type of fixing | when screwed in |
|---------------------|-----------------|----------------|-----------------|

**Cross-connector**

|                                     |                 |  |              |
|-------------------------------------|-----------------|--|--------------|
| Number of cross-connected terminals | 30              | Rated current, 2-pole                    | 32 A         |
| Rated current, multi-pole           | 32 A            | Tightening torque range for fixing screw | 0.4...0.8 Nm |
| Type                                | Cross-connector |  |              |

**Dimensions**

|                 |        |
|-----------------|--------|
| Pitch in mm (P) | 5.1 mm |
|-----------------|--------|


**Rating data**

|               |      |
|---------------|------|
| Rated current | 32 A |
|---------------|------|

**Classifications**

|             |             |            |             |
|-------------|-------------|------------|-------------|
| ETIM 6.0    | EC000489    | ETIM 7.0   | EC000489    |
| eClass 9.0  | 27-14-11-40 | eClass 9.1 | 27-14-11-40 |
| eClass 10.0 | 27-14-11-40 | UNSPSC     | 30-21-18-01 |

**Approvals**

|           |   |
|-----------|---|
| Approvals |  |
| ROHS      | Conform   |

**Data sheet****W-Series  
WQV 2.5/30**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Technical data****Downloads**

---

|                    |   |
|--------------------|---|
| Engineering Data   | <a href="#">EPLAN, WSCAD, Zuken E3.S</a>        |
| Engineering Data   | <a href="#">STEP</a>                            |
| User Documentation | <a href="#">StorageConditionsTerminalBlocks</a> |

---

**Data sheet****W-Series  
WQV 2.5/30**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

**Accessories****Cutting and notching tools for cross-connections**

- for Weidmüller Z-Series cross-connections
- for cross-connections from WQV 2.5 to WQV 35
- for cross-connection window of the terminal WSI 6

**General ordering data**

|            |                            |                     |
|------------|----------------------------|---------------------|
| Type       | WAW 1 NEUTRAL              | Version             |
| Order No.  | <a href="#">9004500000</a> | Miscellaneous tools |
| GTIN (EAN) | 4008190053925              |                     |
| Qty.       | 1 pc(s).                   |                     |