


W-Series
WBB ZA WDU1.5/BL 10/10**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com**Product image****Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

Type	WBB ZA WDU1.5/BL 10/10
Order No.	1068260000
Version	W-Series, Fixing bracket, orange, 5 mm
GTIN (EAN)	4008 1900 15657
Qty.	10 pc(s).

Data sheet

W-Series WBB ZA WDU1.5/BL 10/10

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Width	5 mm	Width (inches)	0.197 inch
Height	45.4 mm	Height (inches)	1.787 inch
Depth	36.7 mm	Depth (inches)	1.445 inch
Net weight	4.31 g		

Temperatures

Storage temperature, max.	40 °C	Storage temperature, min.	10 °C
Storage temperature	10 °C...40 °C	Continuous operating temp., min.	-50 °C
Continuous operating temp., max.	100 °C		

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Material data

Material	PA 66	Colour	orange
UL 94 flammability rating	V-2		

System specifications

Version End and intermediate plate

Additional technical data

Installation advice Direct mounting Snap-on No

Classifications

ETIM 6.0	EC000886	ETIM 7.0	EC000886
eClass 9.0	27-14-11-92	eClass 9.1	27-14-11-33
eClass 10.0	27-14-11-92	UNSPSC	30-21-18-27

Approvals

ROHS Conform

Downloads

Brochure/Catalogue	CAT 1 TERM 16/17 EN
Engineering Data	EPLAN, WSCAD, Zuken E3.S
Engineering Data	STEP
User Documentation	StorageConditionsTerminalBlocks