

**KSWF (flat gasket - vulcanised fibre)
KSWF M32**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



The KSWF is a flat seal made from fibre material suitable for optional large-surface sealing of cable glands on enclosures or electrical cabinets.

General ordering data

Type	KSWF M32
Order No.	1076690000
Version	KSWF (flat gasket - vulcanised fibre), Sealing ring, M 32, Vulcanized fibre
GTIN (EAN)	4032248838622
Qty.	25 pc(s).

Data sheet

KSWF (flat gasket - vulcanised fibre) KSWF M32

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Dimensions and weights

Net weight	1.24 g
------------	--------

General information

Material	Vulcanized fibre	External thread	M 32
Pitch of thread	1.5 mm	Operating temperature range, min.	-40 °C
Operating temperature range, max.	95 °C	Thickness	1.5 mm
Inside diameter D2	32.5 mm	Diameter of sealing ring	42.5 mm

Classifications

ETIM 6.0	EC001181	ETIM 7.0	EC001181
eClass 9.0	27-43-03-19	eClass 9.1	27-14-44-90
eClass 10.0	27-43-03-19		

Approvals

ROHS	Conform
------	---------

Downloads

Brochure/Catalogue	CAT 3 HDC 17/18 EN CAT 5 ENCL 17/18 EN
Engineering Data	EPLAN, WSCAD

Data sheet

**KSWF (flat gasket - vulcanised fibre)
KSWF M32**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings

