

### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com





The new RockStar® enclosures are resistant to seawater and offer a high degree of shock resistance, meet IP 68 and IP 69K, and have been developed for use under extreme environmental conditions and designed for the high vibration requirements acc. to DIN EN 61373 cat. 2 (bogie). As such, this housing family is ideally suited for fault- and maintenance-free operation of heavy-duty connectors in transport and traffic engineering as well as in power engineering and in applications with extreme requirements. During development, measures were also implemented to make the enclosures extremely EMCresistant.

#### General ordering data

Туре	HDC IP68 10B SS 1PG29
Order No.	<u>1081290000</u>
Version	HDC enclosures, Size: 4, Protection degree: IP68,
	IP69K, Closed base, Clamping yoke connection,
	Standard, Size of cable entries: PG 29
GTIN (EAN)	4032248877355
Qty.	1 pc(s).

## Creation date May 1, 2020 5:17:15 PM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

# **Technical data**




## Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Dimensions and weights			
\ A /: -1+1-	00	Middle (in the c)	0.15 in th
Width	80 mm	Width (inches)	3.15 inch
Height Mounting dimonsion, width	100.5 mm 140 mm	Height (inches)	3.957 inch
Mounting dimension - width Net weight	903 g	Mounting dimension - height	60 mm
-	303 y		
Temperatures			
Limit temperature	-50 °C 125 °C		
Dimensions			
Cable entry	w. threading	Hole pitch length A2	140 mm
Total length housing	169 mm		
General data			
EMC housings	Yes	Housing main material	diecast aluminium
Protection degree	IP68, IP69K	Surface finish	Powder coating
Version			
Cable entry	w. threading	Clamp version	Clamping yoke connection
Design	Standard	Design of housing	Closed base
Design of locking system	Clamping yoke connection	Internal thread	PG 29
Number of cable entry on top	0	Number of cable entry sideways	1
Sealing	Silicone rubber	Size	4
Size of cable entries	PG 29	Suitable for ModuPlug <sup>®</sup>	Yes
Top part/bottom part/lid	lower part	Туре	Base housing
Classifications			
ETIM 6.0	EC000437	ETIM 7.0	EC000437
eClass 9.0	27-44-02-02	eClass 9.1	27-44-02-02
eClass 10.0	27-44-02-02	UNSPSC	30-21-18-01
Approvals			
Approvals			
ROHS	Conform		
Downloads			
Brochure/Catalogue	<u>CAT 3 HDC 17/18 EN</u> FL FIELDWIRING EN		

# Drawings





## Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

# Accessories

### IP68 O-ring seals





### Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold Germany Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

We offer a variety of accessories, including seals, to accompany the housings. Because of the excellent sealing, you can achieve the best

seal possible with our housings. Extensive testing has confirmed it – RockStar® remains impermeable to water to a depth of 50 metres This allows you to use heavy-duty connectors in environments which previously required fixed-wire installation.

### **General ordering data**

Туре	HDC DG 10B IP68	Version
Order No.	<u>1987510000</u>	Accessories, Enclosures accessories, Protection degree: Design of
GTIN (EAN)	4050118379228	housing: Clamp version: Design: Approvals :
Qty.	1 pc(s).	