

Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com















Sensor/actuator cables are used for wiring sensors and actuators and for transmitting data or power in various applications. The moulded cable offers connected and tested connection of the plug-in connector to the cable ex-works. The cables may be exposed to a wide range of conditions, such as humidity, dust, heat, cold, shock or vibration.

Our developers have focused specifically on this issue and designed a host of different M8 and M12 sensor-actuator cables so you are bound to find the solution you need for your application.

The M8 and M12 sensor-actuator cables are supplied as standard with brass nickel-plated nuts. However if you are looking to use our products in an extremely harsh environment, we can also supply a variant with a plastic nut. This enables use in environments where cables with nickel-plated M8 and M12 nuts would rust.

Is there something you have not managed to find or you feel needs explanation? Talk to us!

General ordering data

Туре	SAIP-M12GM12W-5-10U
Order No.	<u>1108891000</u>
Version	Sensor/actuator line, Connecting line, M12 / M12, Number of poles : 5, 10 m, pin, straight - socket, 90°, Shielded: No, LED: No, Sheath material: PUR, Halogen: No
GTIN (EAN)	4032248887606
Qty.	1 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Dimensions and weights

Net weight	366 g

Environmental Product Compliance

REACH SVHC Lead 7439-92-1

Technical specifications for cable

Number of poles	5	Core cross-section
Outside diameter	5 mm ± 0.2 mm	Cable length
Shielded	No	Insulation
Colour coding	brown, white, blue, black, grey	Sheath material
Sheathing colour	black	Halogen
Temperature range, moving	-2580 °C	Temperature range, stati
Core in accordance with UL AWM sty	/le 10493 (80 °C / 300 V)	Outer cladding in accord AWM style
Suitable for cable carriers	Yes	Torsion resistance
Bending radius, min., stationary	5 x cable diameter	Bending radius, min., mo
Acceleration	5 m/s ²	Speed
Bending cycles	2 Mio	Resistant to welding bea
Configurable cable length	No	Hydrolysis and microbe i
LABS-free	Yes	Resistance to oils
Resistance to spread of flame	In accordance with UL1581 UL/ CUL FT1, in accordance with IEC 60332-1-2, in accordance with IEC 60332-1-3, in	

accordance with IEC 60332-2-2

Core cross-section	0.34 mm ²
Cable length	10 m
Insulation	PP
Sheath material	
	PUR
Halogen	No
Temperature range, stationary	-4080 °C
Outer cladding in accordance with UL	
AWM style	20233 (80 °C / 300 V)
Torsion resistance	360 °/m
Bending radius, min., moving	10 x cable diameter
Speed	5 m/s
Resistant to welding beads	No
Hydrolysis and microbe resistant	Yes
Resistance to oils	in accordance with IEC 60811:404

General technical data

AF size		Version	pin, straight - socket,
	12 mm		90°
Connection thread	M12 / M12	Housing main material	PUR
Threaded ring material	Plastic	Coding	Α
Protection degree	IP65, IP66, IP67, IP68,	Contact surface	
-	when screwed in		Gold-plated
LED	No	Rated voltage	125 V
Rated current	4 A	Insulation strength	10 ⁸ Ω
Temperature range of housing	-25+80 °C	Tightening torque	M12 (plastic): 0.9 - 1.1 Nm
Plugging cycles	≥ 100	Pollution severity	3
jumpered	No		

Standards

Connector standard IEC 61076-2-101 Certificate no. (cULus) E307231				
	Connector standard	IEC 61076 0 101	Certificate no. (cULus)	E307231

Classifications

ETIM 6.0	EC001855	ETIM 7.0	EC001855
eClass 9.0	27-06-03-11	eClass 9.1	27-06-03-11
eClass 10.0	27-06-03-11		



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Technical data

Approvals

Approvals



ROHS Conform

Downloads

Brochure/Catalogue	FL FIELDWIRING EN	
Engineering Data	EPLAN, WSCAD	



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold


Germany


Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Drawings

Dimensioned drawing

Dimensioned drawing







Angled socket

Male, straight

Pole scheme


Pole scheme





Wiring diagram

The ideal tool: Screwty ® with torque function





Light, securely screwed-in round plug-in connectors. Screwty set DM / VPE: 1 / Order No.: 1920000000 Adapters: M12, M12 F, M8, M8 F



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Tools

Qty.

Sheathing stripper for PVC cables



General ordering data

Type AM 12
Order No. 9030060000
GTIN (EAN) 4008190337827

1 pc(s).

Versior

Tools, Sheathing strippers, UTP and STP data cables

Cutting tools for outside diameters up to 22 mm



Cutting tools for conductors up to 8 mm, 12 mm, 14 mm and 22 mm outside diameter. The special blade geometry allows pinch-free cutting of copper and aluminium conductors with minimum physical effort. The cutting tools also come with VDE and GS-tested protective insulation up to 1,000 V in accordance with EN/IEC 60900.

General ordering data

 Type
 KT 8
 Version

 Order No.
 9002650000
 Cutting tools ,Cutting tool for one-hand operation

 GTIN (EAN)
 4008190020163

 Qty.
 1 pc(s).



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Tools



- · Stripping tools with automatic self-adjustment
- For flexible and solid conductors
- · Ideally suitable for mechanical and plant engineering, railway and rail traffic, wind energy, robot technology, explosion protection as well as marine, offshore and ship building sectors
- Stripping length adjustable via end stop
- · Automatic opening of clamping jaws after stripping
- No fanning-out of individual conductors
- Adjustable to diverse insulation thicknesses
- Double-insulated cables in two process steps without special adjustment
- No play in self-adjusting cutting unit
- · Long service life
- · Optimised ergonomic design

General ordering data

STRIPPER 6-16 RED-LINE Туре

Order No. 9203110000 GTIN (EAN)

4032248541423

Qty. 1 pc(s). Version

Stripping and cutting tool, 16mm²

Tool



Tools for stripping the sheathing from uncut power lines and outlet lines, plus screwdrivers for installing Pick-to-Light components.

General ordering data

SCREWTY-M12-DM Туре

Order No. 1900001000 4032248436408 GTIN (EAN)

Qty. 1 pc(s).

Tools, Cable gland tool for moulded M12 lines



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Blank



TM-I is an acknowledged and accredited marker type for traffic engineering applications. There are five different tag lengths available for individual labelling with long character strings. Easy handling of separation and installation thanks to the project marker field. Preattachment of sleeves and retrofitting of tags offer excellent versatility

The special contour of TM-I allows easy assembly and secures firm positioning. They are compatible with a number of commercially available sleeves. Thanks to the MultiCard format, the tags can be printed quickly and conveniently with the SMark laser printer, PrintJet ADVANCED, plotter, MC-Mobilo or the STI pen.

- Easy handling of separation and installation thanks to the project marker field.
- Acknowledged and accredited marker for traffic engineering applications
- Pre-attachment of sleeves and retrofitting of tags offer excellent versatility
- Not suited for labelling with P-lnk or STI pen in connection with CLI T sleeves

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Туре	TM-I 18 MC NE GE	Version
Order No.	<u>1718431687</u>	TM-I, Insert markers, 18 x 4 mm, yellow
GTIN (EAN)	4008190349028	
Qty.	320 pc(s).	
Туре	TM-I 18 MC NE WS	Version
Type Order No.	TM-I 18 MC NE WS 1718431044	Version TM-I, Insert markers, 18 x 4 mm, white



Weidmüller Interface GmbH & Co. KG

Klingenbergstraße 26 D-32758 Detmold

Germany

Fon: +49 5231 14-0 Fax: +49 5231 14-292083 www.weidmueller.com

Accessories

Screwty® cable gland tool with torque function



The ideal tool for any application

Screwty® is the ideal, all-purpose tool for tightening all common sensor and actuator cables. Even difficult-to-reach round plugs are accessible using the Screwty®. A simple turning movement tightens and loosens the connectors without the need for excessive force. The Screwty® is a unique and global solution since it fits with most cables and plugs from other vendors (over 90 %). The Screwty® consists of a handle with a conventional 1/4" adapter. Thus it can be used for all sizes: for M12 and M8 round plug-in connectors, and for M12F and M8F customisable plugs and sockets, as well as for all M23 plugs and sockets.

General ordering data

Туре	SAI-SCREWTY BOX	Version
Order No.	<u>1939180000</u>	Tools, Bolting tool
GTIN (EAN)	4032248615506	
Qty.	1 pc(s).	
Туре	SCREWTY SW12	
Order No.	<u>2598970000</u>	
GTIN (EAN)	4050118781151	
Qty.	1 pc(s).	