

W-Series
WSI 25/1 10X38/LED 1KV**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com**Product image****Klippon® Connect with clamping yoke Technology**

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

Type	WSI 25/1 10X38/LED 1KV
Order No.	1137780000
Version	W-Series, Fuse terminal, Rated cross-section: 25 mm ² , Screw connection
GTIN (EAN)	4032248957392
Qty.	12 pc(s).

W-Series
WSI 25/1 10X38/LED 1KV

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

Width	18 mm	Width (inches)	0.709 inch
Height	81 mm	Height (inches)	3.189 inch
Depth	58 mm	Depth (inches)	2.283 inch
Net weight	52.75 g		

Temperatures

Storage temperature, max.	40 °C	Storage temperature, min.	10 °C
Storage temperature	10 °C...40 °C	Continuous operating temp., min.	-50 °C
Continuous operating temp., max.	120 °C		

Material data

Material	PA 66/6	Colour	dark beige
UL 94 flammability rating	V-0		

System specifications

Version	Screw connection, Fuse cartridge, with LED, in closed state	End cover plate required	No
Number of potentials	1	Number of levels	1
Number of clamping points per level	2	Number of potentials per tier	1
Levels cross-connected internally	No	PE connection	No
Rail	TS 35	N-function	No
PE function	No	PEN function	No

Additional technical data

Open sides	closed	Type of mounting	Snap-on
------------	--------	------------------	---------

CSA rating data

Certificate No. (CSA)	238018-1868186	Wire cross section max. (CSA)	8 AWG
Wire cross section min. (CSA)	18 AWG		

W-Series
WSI 25/1 10X38/LED 1KV

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data**Conductors for clamping (rated connection)**

Clamping range, max.	25 mm ²	Clamping range, min.	1.5 mm ²
Connection cross-section, stranded, max.	25 mm ²	Connection cross-section, stranded, min.	1.5 mm ²
Connection direction	on side	Number of connections	2
Stripping length	11 mm	Tightening torque, max.	2.5 Nm
Tightening torque, min.	2 Nm	Type of connection	Screw connection
Wire connection cross section AWG, max.	AWG 4	Wire connection cross section AWG, min.	AWG 18
Wire connection cross section, finely stranded, max.	25 mm ²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, max.	25 mm ²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/1, min.	1.5 mm ²	Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, max.	25 mm ²
Wire connection cross-section, finely stranded with wire-end ferrules DIN 46228/4, min.	1.5 mm ²	Wire connection cross-section, finely stranded, min.	1.5 mm ²
Wire connection cross-section, solid core, max.	25 mm ²	Wire connection cross-section, solid core, min.	1.5 mm ²

Fuse terminals

Current for fuse with semiconductor protection	25 A	Permitted power loss for fuse with semiconductor protection	4.300000 W/ 10.000000 mm ² / 25.000000 A/
Permitted power loss for the standard fuse variants	3 W	Power loss for fuse with semiconductor protection	4.3 W
Power loss, 1-pole	0.3 W	Power loss, 1-pole ; 2-pole ; 3-pole	0.300000 W/ 0.600000 W/ 0.900000 W/
Power loss, 2-pole	0.6 W	Power loss, 3-pole	0.9 W
Wire cross-section for fuse with semiconductor protection	10 mm ²		

Rating data

Rated cross-section	25 mm ²	Rated voltage	1,000 V
Rated voltage to adjoining terminal	1,000 V	Rated DC voltage	1,000 V DC
Rated current	30 A	Current at maximum wires	30 A
Standards	IEC 60269-1	Volume resistance according to IEC 60947-7-x	0.32 mΩ
Power loss in accordance with IEC 60947-7-x	3.23 W	Rated impulse withstand voltage	6 kV
Pollution severity	3		

UL rating data

Certificate No. (UL)	E355388
----------------------	---------

Classifications

ETIM 6.0	EC000899	ETIM 7.0	EC000899
eClass 9.0	27-14-11-16	eClass 9.1	27-14-11-16
eClass 10.0	27-14-11-16		

Data sheet

W-Series
WSI 25/1 10X38/LED 1KV

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data

Product information

Product information The clamping points must be checked depending on the operating conditions. For normal environmental conditions and load cases, we recommend checking at intervals of 6 months. With unfavourable operating conditions or frequent temperature changes at the clamping points, a shorter interval may be necessary.

Approvals

Approvals



ROHS Conform

Downloads

- Brochure/Catalogue [CAT 1 TERM 16/17 EN](#)
- Engineering Data [EPLAN, WSCAD, Zuken E3.S](#)
- Engineering Data [STEP](#)
- User Documentation [StorageConditionsTerminalBlocks](#)

Safety note

Safety notice [Safety Information](#)

**W-Series
WSI 25/1 10X38/LED 1KV**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories

Blank



ESG is the tried-and-tested marker in MultiCard format for use on many well-known electrical devices. The result is high-quality device marking with a high-contrast appearance.

Various types are available for devices from the following manufacturers:

- Siemens
- Télémecanique
- ABB
- Beckhoff
- Lumberg
- Tags for all-purpose usage; self-adhesive or clip-on tags, depending on the type

Advantages at a glance:

- Tags for universal usage, self-adhesive or clip-on tags, depending on type
- For aligned equipment, e.g. circuit breakers, we supply ESG markers for clipping onto tag rails
- Individual laser-quality printing according to specifications

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

Please note that these markers are not intended for printing with the SpeedMarking laser.

General ordering data

Type	ESG 6/15 K MC NE WS	Version
Order No.	1880100000	ESG, Device markers x 15 mm, PA 66, Colour: white, Self-adhesive
GTIN (EAN)	4032248478781	
Qty.	200 pc(s).	

W-Series WSI 25/1 10X38/LED 1KV

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories

Fuses 1 kV



Klippon® Connect with clamping yoke Technology

The high reliability and variety of designs of the terminal blocks with clamping yoke connections make planning easier and optimises operational safety. Klippon® Connect provides a proven response to a range of different requirements.

General ordering data

Type	FUSE 1KV DC 16A 10/38	Version
Order No.	1224930000	Accessories, Fuse
GTIN (EAN)	4050118008913	
Qty.	10 pc(s).	
Type	FUSE 1KV DC 12A 10/38	Version
Order No.	1224920000	Accessories, Fuse
GTIN (EAN)	4050118008944	
Qty.	10 pc(s).	
Type	FUSE 1KV DC 4A 10/38	Version
Order No.	1224880000	Accessories, Fuse
GTIN (EAN)	4050118008920	
Qty.	10 pc(s).	
Type	FUSE 1KV DC 8A 10/38	Version
Order No.	1224900000	Accessories, Fuse
GTIN (EAN)	4050118008692	
Qty.	10 pc(s).	
Type	FUSE 1KV DC 6A 10/38	Version
Order No.	1224890000	Accessories, Fuse
GTIN (EAN)	4050118008906	
Qty.	10 pc(s).	
Type	FUSE 1KV DC 10A 10/38	Version
Order No.	1224910000	Accessories, Fuse
GTIN (EAN)	4050118008746	
Qty.	10 pc(s).	
Type	FUSE 1KV DC 20A 10/38	Version
Order No.	1224950000	Accessories, Fuse
GTIN (EAN)	4050118008821	
Qty.	10 pc(s).	

W-Series WSI 25/1 10X38/LED 1KV

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories

Blank



MultiFit is the Weidmüller marker system used for other makes of terminals in 4, 5, 6, 6.5, 7.5, 8, 10 and 12 mm pitches. Similar to the Weidmüller dekafix, the markers of the MultiFit family are available ready-for-use with standard printing.

We recommend to carry out a test with sample markers on the terminals used when using MultiFit for the first time.

- One marker, suitable for different makes of terminals.
- Ready-to-use markers with standard printing
- Blank markers for printing with the SMark laser, PrintJet ADVANCED, plotter or MC-Mobilo,
- Delivery of individually printed markers according to customer CAE data or specifications
- One marking system for all applications

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

Type	MF 5/12 MC NE WS	Version
Order No.	1250090000	MultiFit, Terminal marker, 5 x 12 mm, Pitch in mm (P): 5.00 Phoenix,
GTIN (EAN)	4050118040463	white
Qty.	250 pc(s).	