

**Industrial Ethernet
IE-C5ES8UG0015M40M40-G**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



Assembled cables, patch cable Cabinet Line, Cat. 5, PUR,
green

General ordering data

| | |
|------------|---|
| Type | IE-C5ES8UG0015M40M40-G |
| Order No. | 1166000015 |
| Version | System cable, RJ45 IP 20, RJ45 IP 20, Cat.5 (ISO/IEC 11801), PUR, 1.5 m |
| GTIN (EAN) | 4032248956548 |
| Qty. | 1 pc(s). |

Creation date May 2, 2020 9:44:25 AM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

Industrial Ethernet IE-C5ES8UG0015M40M40-G

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

Dimensions and weights

| | | | |
|------------|-------|--------------------------|------------|
| Length | 1.5 m | Length (inches) | 0.059 inch |
| Net weight | 72 g | Insulation cross-section | 0.98 mm |

Temperatures

| | | | |
|-----------------------------|----------------|-----------------------------|----------------|
| Operating temperature, max. | 75 °C | Operating temperature, min. | -40 °C |
| Operating temperature | -40 °C...75 °C | Installation temperature | -10 °C...60 °C |

Environmental Product Compliance

| | |
|------------|----------------|
| REACH SVHC | Lead 7439-92-1 |
|------------|----------------|

Electrical properties

| | |
|------------|-------------------------------|
| PoE / PoE+ | conforming to IEEE 802.3at |
|------------|-------------------------------|

General standards

| | |
|--------------------|-----------------|
| Connector standard | IEC 60603-7-5 1 |
|--------------------|-----------------|

Cable structure

| | | | |
|---------------------------------------|--|-----------------------|----------------|
| Wire material | Stranded tin-plated copper wire | Strands | 7 |
| Cross-section | 4*2*AWG 26/7 - 4*2*0.128 mm ² | Insulation | PE |
| Insulation cross-section | 0.98 mm | Number of wires | 8 |
| Arrangement of wire cores | Twisted pair | Wire pair shielding | Aluminium foil |
| Colour sequence or wires - wire pairs | white/blue - blue, white/ orange - orange, white/ green - green, white/ brown - brown | Shielding | SF/UTP |
| Complete shielding | Shielding braid made from copper wiring | Material sheath | PUR |
| Sheath diameter, min. | 5.6 mm | Sheath diameter, max. | 6 mm |
| Sheathing colour | green (RAL 6018) | | |

Electrical properties of cable

| | | | |
|----------|-----------------------|--------------------------------|-----------------|
| Category | Cat.5 (ISO/IEC 11801) | Test voltage: wire-wire-shield | 750 V DC, 1 min |
|----------|-----------------------|--------------------------------|-----------------|

Mechanical and material properties of cable

| | | | |
|--------------------------------|---|---------------------------------|-----------------------------------|
| Min. bending radius, once only | 5 x cable diameter | Min. bending radius, repetitive | 10 x cable diameter |
| Abrasion resistance | very good | Resistance to spread of flame | in accordance with IEC 60332-1 |
| Resistance to oils | EN 50305 | Silicone-free | Yes |
| Halogen | halogen-free, according to IEC 60754-2 | | |

plug

| | | | |
|----------------|------------|-----------------|------------|
| Connector left | RJ45 IP 20 | Connector right | RJ45 IP 20 |
|----------------|------------|-----------------|------------|

**Industrial Ethernet
IE-C5ES8UG0015M40M40-G**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data**Classifications**

| | | | |
|-------------|-------------|------------|-------------|
| ETIM 6.0 | EC002599 | ETIM 7.0 | EC002599 |
| eClass 9.0 | 27-06-03-08 | eClass 9.1 | 27-06-03-08 |
| eClass 10.0 | 27-06-03-08 | | |

Approvals

| | |
|------|---------|
| ROHS | Conform |
|------|---------|

Downloads

| | |
|-----------------------------|--|
| Brochure/Catalogue | CAT 9 IETH 18/19 EN FL FIELDWIRING EN PI PROFINET CABLING EN |
| Product Change Notification | PCN-PB47-20180213-00-A_EN PCN-PB47-20180213-00-A_DE |
| User Documentation | MAN IE GUIDE DE MAN IE GUIDE EN |

Data sheet**Industrial Ethernet
IE-C5ES8UG0015M40M40-G**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Drawings**Wiring**

| | | | | |
|------|---|---------------|---|------|
| RJ45 | 1 | white, orange | 1 | RJ45 |
| | 2 | orange | 2 | |
| | 3 | white, green | 3 | |
| | 4 | blue | 4 | |
| | 5 | white, blue | 5 | |
| | 6 | green | 6 | |
| | 7 | white, brown | 7 | |
| | 8 | brown | 8 | |

**Industrial Ethernet
IE-C5ES8UG0015M40M40-G**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories

Blank



TM-I is an acknowledged and accredited marker type for traffic engineering applications. There are five different tag lengths available for individual labelling with long character strings. Easy handling of separation and installation thanks to the project marker field. Pre-attachment of sleeves and retrofitting of tags offer excellent versatility

The special contour of TM-I allows easy assembly and secures firm positioning. They are compatible with a number of commercially available sleeves. Thanks to the MultiCard format, the tags can be printed quickly and conveniently with the SMark laser printer, PrintJet ADVANCED, plotter, MC-Mobilo or the STI pen.

- Easy handling of separation and installation thanks to the project marker field.
- Acknowledged and accredited marker for traffic engineering applications
- Pre-attachment of sleeves and retrofitting of tags offer excellent versatility
- Not suited for labelling with P-Ink or STI pen in connection with CLI T sleeves

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

| | | |
|------------|----------------------------|--|
| Type | TM-I 18 MC NE WS | Version |
| Order No. | 1718431044 | TM-I, Insert markers, 18 x 4 mm, white |
| GTIN (EAN) | 4008190349011 | |
| Qty. | 320 pc(s). | |

**Industrial Ethernet
IE-C5ES8UG0015M40M40-G**

Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Accessories

Blank



TM-I is an acknowledged and accredited marker type for traffic engineering applications. There are five different tag lengths available for individual labelling with long character strings. Easy handling of separation and installation thanks to the project marker field. Pre-attachment of sleeves and retrofitting of tags offer excellent versatility

The special contour of TM-I allows easy assembly and secures firm positioning. They are compatible with a number of commercially available sleeves. Thanks to the MultiCard format, the tags can be printed quickly and conveniently with the SMark laser printer, PrintJet ADVANCED, plotter, MC-Mobilo or the STI pen.

- Easy handling of separation and installation thanks to the project marker field.
- Acknowledged and accredited marker for traffic engineering applications
- Pre-attachment of sleeves and retrofitting of tags offer excellent versatility
- Not suited for labelling with P-Ink or STI pen in connection with CLI T sleeves

For custom printing: Please send us a file of our labeling software M-Print PRO or M-Print PRO Online (without installation) for your labeling specifications.

General ordering data

| Type | TM-I 12 MC NE WS | Version |
|------------|----------------------------|--|
| Order No. | 1718411044 | TM-I, Insert markers, 12 x 4 mm, white |
| GTIN (EAN) | 4008190348977 | |
| Qty. | 320 pc(s). | |