

**Pro-E**  
**CP E SNT 50W 24V 2.2A****Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
www.weidmueller.com

With your applications in industrial automation, you appreciate a power supply with high levels of stability yet wish to remain flexible at the same time.

Our new wall-mounted PRO-E power supply offers outstanding value for money and has been developed for universal usage. Thanks to the wide variety of models with output voltages of 5 V, 12 V, 24 V and 48 V as well as extensive international approvals, it is suitable for use in many applications. The power bandwidth ranges from 25 W up to 350 W. Individual adaptability makes PRO-E the right choice for your power supply

**General ordering data**

Type	CP E SNT 50W 24V 2.2A
Order No.	<a href="#">1202450000</a>
Version	Power supply, switch-mode power supply unit
GTIN (EAN)	4050118031522
Qty.	1 pc(s).

**Pro-E**  
**CP E SNT 50W 24V 2.2A**
**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**
**Dimensions and weights**

Width	100 mm	Width (inches)	3.937 inch
Height	35 mm	Height (inches)	1.378 inch
Depth	105 mm	Depth (inches)	4.134 inch
Net weight	320 g		

**Temperatures**

Storage temperature, max.	85 °C	Storage temperature, min.	-20 °C
Ambient temperature	-20°C...70°C (>50°C derating, refer derated curve); 70% rated load @ 70°C	Storage temperature	-20 °C...85 °C

**Environmental Product Compliance**

REACH SVHC	Lead 7439-92-1
------------	----------------

**Rated data UL**

Certificate No. (cURus)	E349964
-------------------------	---------

**Input**

AC current consumption	0.6 A @ 230 V AC / 1.2 A @ 120 V AC	AC input voltage range	85...264 V AC
Connection system	Screw connection	DC input voltage range	110...370 V DC
Frequency range AC	47...63 Hz	Input fuse (internal)	yes / max. 20A
Rated input voltage	100...240 V AC (wide-range input)	Recommended back-up fuse	2 A at 230 V AC, characteristic curve C

**Output**

Mains failure bridge-over time	20 ms	Output current	2.2 A@24 V DC
Output power	50 W	Output voltage	± 10% nominal output voltage tolerance, adjustable with potentiometer
Overload protection	120~150% I <sub>konst.</sub> of max. output power, automatic restart	Parallel connection option	Recommended with diode module
Rated output voltage	24 V DC	Residual ripple, breaking spikes	< 100 mV <sub>pp</sub>
Surge protection	28...32 V @ 24 V DC		

**General data**

AC failure bridging time @ I <sub>nom</sub>	min. 20 ms	Ambient temperature	-20°C...70°C (>50°C derating, refer derated curve); 70% rated load @ 70°C
Degree of efficiency	84 % @ 24 V DC	EMC standards	EN 55011, EN 55022, EN 55024, EN 61000-6 /-2, -3
Indication	Operation, green LED	Max. perm. air humidity (operational)	5 %...95 % RH
Mounting position, installation notice	Panel mount, screw fix	Protection degree	IP20
Short-circuit protection	Yes	Standards	EN 60950

Creation date May 2, 2020 2:01:09 PM CEST

Catalogue status 17.04.2020 / We reserve the right to make technical changes.

**Data sheet**

**Pro-E  
CP E SNT 50W 24V 2.2A**

**Weidmüller Interface GmbH & Co. KG**  
 Klingenbergstraße 26  
 D-32758 Detmold  
 Germany  
 Fon: +49 5231 14-0  
 Fax: +49 5231 14-292083  
 www.weidmueller.com

**Technical data**

**System data**

Output current 2.2 A@24 V DC

**EMC / shock / vibration**

Noise emission in accordance with EN55032 Class A

**Insulation coordination**

electrical isolation, input-earth	2 kV	electrical isolation, input-output	3 kV
electrical isolation, output-earth	0.5 kV		

**Electrical safety (applied standards)**

Safety extra-low voltage SELV according to EN 60950

**Connection data (input)**

Connection system Screw connection

**Approvals**

Institute (cURus)  Certificate No. (cURus)

E349964

**Classifications**

ETIM 6.0	EC002540	ETIM 7.0	EC002540
eClass 9.0	27-04-07-01	eClass 9.1	27-04-07-01
eClass 10.0	27-04-07-01		

**Approvals**

Approvals



ROHS Conform

**Downloads**

Approval/Certificate/Document of Conformity	<a href="#">DE_PA5200_160418_001.pdf</a>
Engineering Data	<a href="#">EPLAN, WSCAD</a>
Engineering Data	<a href="#">STEP</a>

**Data sheet**

**Pro-E**  
**CP E SNT 50W 24V 2.2A**

**Weidmüller Interface GmbH & Co. KG**  
Klingenbergstraße 26  
D-32758 Detmold  
Germany  
Fon: +49 5231 14-0  
Fax: +49 5231 14-292083  
[www.weidmueller.com](http://www.weidmueller.com)

**Drawings**

