

**Pro-E
CP E SNT 350W 24V 14.6A**

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com



With your applications in industrial automation, you appreciate a power supply with high levels of stability yet wish to remain flexible at the same time.

Our new wall-mounted PRO-E power supply offers outstanding value for money and has been developed for universal usage. Thanks to the wide variety of models with output voltages of 5 V, 12 V, 24 V and 48 V as well as extensive international approvals, it is suitable for use in many applications. The power bandwidth ranges from 25 W up to 350 W. Individual adaptability makes PRO-E the right choice for your power supply

General ordering data

Type	CP E SNT 350W 24V 14.6A
Order No.	1202550000
Version	Power supply, switch-mode power supply unit
GTIN (EAN)	4050118031614
Qty.	1 pc(s).

Pro-E
CP E SNT 350W 24V 14.6A
Weidmüller Interface GmbH & Co. KG
 Klingenbergstraße 26
 D-32758 Detmold
 Germany
 Fon: +49 5231 14-0
 Fax: +49 5231 14-292083
 www.weidmueller.com

Technical data
Dimensions and weights

Width	115 mm	Width (inches)	4.528 inch
Height	49.5 mm	Height (inches)	1.949 inch
Depth	230 mm	Depth (inches)	9.055 inch
Net weight	1,030 g		

Temperatures

Storage temperature, max.	85 °C	Storage temperature, min.	-20 °C
Ambient temperature	-20°C...70°C (>50°C derating, refer derated curve); 70% rated load @ 70°C	Storage temperature	-20 °C...85 °C

Environmental Product Compliance

REACH SVHC	Lead 7439-92-1
------------	----------------

Rated data UL

Certificate No. (cURus)	E349964
-------------------------	---------

Input

AC current consumption	3 A @ 230 V AC / 5.6 A @ 120 V AC	AC input voltage range	85...264 V AC
Connection system	Screw connection	DC input voltage range	110...370 V DC
Frequency range AC	47...63 Hz	Input fuse (internal)	yes / max. 35A
Rated input voltage	100...240 V AC (wide-range input)	Recommended back-up fuse	6 A at 230 V AC, characteristic curve C

Output

Control at 10...100% load	2%	Mains failure bridge-over time	20 ms
Output current	14.6 A@24 V DC	Output power	350 W
Output voltage	± 10% nominal output voltage tolerance, adjustable with potentiometer	Overload protection	120~150% I _{konst.} of max. output power, automatic restart
Parallel connection option	Recommended with diode module	Rated output voltage	24 V DC
Residual ripple, breaking spikes	< 100 mV _{pp}	Surge protection	28...32 V @ 24 V DC

General data

AC failure bridging time @ I _{nom}	min. 20 ms	Ambient temperature	-20°C...70°C (>50°C derating, refer derated curve); 70% rated load @ 70°C
Degree of efficiency	83 % @ 24 V DC	EMC standards	EN 55011, EN 55022, EN 55024, EN 61000-6 /-2, -3
Indication	Operation, green LED	Max. perm. air humidity (operational)	5 %...95 % RH
Mounting position, installation notice	Panel mount, screw fix	Protection degree	IP20
Short-circuit protection	Yes	Standards	EN 60950

Data sheet

Pro-E
CP E SNT 350W 24V 14.6A

Weidmüller Interface GmbH & Co. KG
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com

Technical data

System data

Output current 14.6 A@24 V DC

EMC / shock / vibration

Noise emission in accordance with EN55032 Class A

Insulation coordination

electrical isolation, input-earth	2 kV	electrical isolation, input-output	3 kV
electrical isolation, output-earth	0.5 kV		


Electrical safety (applied standards)

Safety extra-low voltage SELV according to EN 60950

Connection data (input)

Connection system Screw connection

Approvals

Institute (cURus)  Certificate No. (cURus)

E349964

Classifications

ETIM 6.0	EC002540	ETIM 7.0	EC002540
eClass 9.0	27-04-07-01	eClass 9.1	27-04-07-01
eClass 10.0	27-04-07-01		

Approvals


Approvals



ROHS Conform

Downloads

Approval/Certificate/Document of Conformity	DE_PA5200_160418_001.pdf
Engineering Data	EPLAN, WSCAD
Engineering Data	STEP

Data sheet**Pro-E**
CP E SNT 350W 24V 14.6A**Weidmüller Interface GmbH & Co. KG**
Klingenbergstraße 26
D-32758 Detmold
Germany
Fon: +49 5231 14-0
Fax: +49 5231 14-292083
www.weidmueller.com**Drawings**

Bei DC-Anschluss auf Polarität achten